



FCI
Copyright FCI

CATALOG PART NUMBER	LEAD FREE VERSION
7832C0435X01	7832C0435X01LF

IMPLANTATION C.I
PCB FOOTPRINT

LEAD FREE VERSION:
"This product meets European Union Directives and other country regulations as described in GS-22-008"
The housing will withstand exposure to 260°C peak temperature for 3-5seconds in a wave solder application with a 1.6mm minimum thick circuit board.
Use protective adhesive tape (Kapton orTeflon) or protective metallic devices on the areas which are directly exposed to wave soldering as it is used in classical leaded wave soldering.
Sn Matte plating on solder tail for Lead Free Versions

General Tolerances	
0 to 10mm:	±0.1mm
10 to 30mm:	±0.15mm
30 to 60mm:	±0.2mm
60 and more:	±0.3mm

rev	ecn no	dr	date
E	105-0167	NT	2005/09/24
F	106-0084	SSC	2006/06/21
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com			surface -	tolerance std	projection	mm	
			ISO 1302	ISO 406	ISO 1101		
			TOLERANCES UNLESS OTHERWISE SPECIFIED				
Dr	D LEGRAND	2002/04/29	ANGULAR	0.X	±	size	Scale
Eng	F TISSERAND	2002/04/29	LINEAR	0.XX	±	A2	5:1
Chr	DILIP THOMAS	2006/06/21	0° ±°	0.XXX	±	ECN	106-0084
Appr	K.V.SIVADAS	2006/06/21	Product family			Spec ref	-
FCI			MODULE 16 CONTACTS			dwg no	Rev.
			C04			VRW10359	F
			catalog no			CUSTOMER	sheet 1 of 1
			7832C0435X01				