NTHS2101P

Power MOSFET

−8.0 V, −7.5 A P−Channel ChipFET™

ON Semiconductor®

http://onsemi.com

$V_{(BR)DSS}$	Ultra Low $R_{DS(on)}$ TYP	I_D MAX
−8.0 V	19 mΩ @ −4.5 V_{GS}	−7.5 A
	25 mΩ @ −2.5 V_{GS}	
	34 mΩ @ −1.8 V_{GS}	

Features

- Offers an Ultra Low $R_{DS(on)}$ Solution in the ChipFET Package
- Miniature ChipFET Package 40% Smaller Footprint than TSOP−6 making it an Ideal Device for Applications where Board Space is at a Premium
- Low Profile (<1.1 mm) Allows it to Fit Easily into Extremely Thin Environments such as Portable Electronics
- Designed to Provide Low $R_{DS(on)}$ at Gate Voltage as Low as 1.8 V, the Operating Voltage used in many Logic ICs in Portable Electronics
- Simplifies Circuit Design since Additional Boost Circuits for Gate Voltages are not Required
- Operated at Standard Logic Level Gate Drive, Facilitating Future Migration to Lower Levels using the same Basic Topology
- Pb−Free Package is Available

Applications

- Optimized for Battery and Load Management Applications in Portable Equipment such as MP3 Players, Cell Phones, Digital Cameras, Personal Digital Assistant and other Portable Applications
- Charge Control in Battery Chargers
- Buck and Boost Converters



P−Channel MOSFET



ChipFET
CASE 1206A
STYLE 1

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	−8.0	V_{dc}
Gate−to−Source Voltage − Continuous	V_{GS}	±8.0	V_{dc}
Drain Current − Continuous − 5 seconds	I_D	−5.4 −7.5	A
Total Power Dissipation Continuous @ T_A = 25°C (5 sec) @ T_A = 25°C Continuous @ 85°C (5 sec) @ 85°C	P_D	 1.3 2.5 0.7 1.3	W
Continuous Source Current	Is	−1.1	A
Thermal Resistance (Note 1) Junction−to−Ambient, 5 sec Junction−to−Ambient, Continuous	$R_{\theta JA}$	 50 95	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 10 seconds	T_L	260	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. Surface Mounted on FR4 Board using 1 in sq pad size (Cu area = 1.27 in sq [1 oz] including traces).

PIN CONNECTIONS



MARKING DIAGRAM



D4 = Specific Device Code
M = Month Code

ORDERING INFORMATION

Device	Package	Shipping†
NTHS2101PT1	ChipFET	3000/Tape & Reel
NTHS2101PT1G	ChipFET (Pb−Free)	3000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2004

October, 2004 − Rev. 4

Publication Order Number:
NTHS2101P/D

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage (Note 2) Temperature Coefficient (Positive)	$V_{(Br)DSS}$	V_{GS} = 0 V_{dc}, I_D = −250 μA_{dc}	−8.0			V_{dc}
Gate−Body Leakage Current Zero	I_{GSS}	V_{DS} = 0 V_{dc}, V_{GS} = ±8.0 V_{dc}			±100	nA_{dc}
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = −6.4 V_{dc}, V_{GS} = 0 V_{dc} V_{DS} = −6.4 V_{dc}, V_{GS} = 0 V_{dc}, T_J = 85°C			−1.0 −5.0	μA_{dc}
ON CHARACTERISTICS (Note 2)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = −250 μA_{dc}	−0.45		−1.5	V_{dc}
Static Drain−to−Source On−Resistance	$R_{DS(on)}$	V_{GS} = −4.5 V_{dc}, I_D = −5.4 A_{dc} V_{GS} = −2.5 V_{dc}, I_D = −4.5 A_{dc} V_{GS} = −1.8 V_{dc}, I_D = −2.0 A_{dc}		19 25 34	25 36 48	mΩ
Forward Transconductance	g_{FS}	V_{DS} = −5.0 V_{dc}, I_D = −5.2 A_{dc}		20		S
Diode Forward Voltage	V_{SD}	I_S = −1.1 A_{dc}, V_{GS} = 0 V_{dc}		−0.62	−1.2	V
DYNAMIC CHARACTERISTIC						
Input Capacitance	C_{iss}	V_{DS} = −6.4 V_{dc} V_{GS} = 0 V f = 1.0 MHz		2400		pF
Output Capacitance	C_{oss}			550		
Transfer Capacitance	C_{rss}			420		
SWITCHING CHARACTERISTICS (Note 3)						
Turn−On Delay Time	$t_{d(on)}$	V_{DD} = −6.4 V_{dc} V_{GS} = −4.5 V_{dc} I_D = −5.4 A_{dc} R_G = 2.0 Ω (Note 2)		7.0		ns
Rise Time	t_r			28		
Turn−Off Delay Time	$t_{d(off)}$			73		
Fall Time	t_f			60		
Gate Charge	Q_G	V_{GS} = −4.5 V_{dc} I_D = −5.4 A_{dc} V_{DS} = −6.4 V_{dc}		15	30	nC
	Q_{GS}			4.0		
	Q_{GD}			8.0		
Source−Drain Reverse Recovery Time	T_{rr}	I_F = −1.1 A, di/dt = 100 A/μs		90		ns

2. Pulse Test: Pulse Width = 250 μs, Duty Cycle = 2%.
3. Switching characteristics are independent of operating junction temperatures.

Downloaded from Arrow.com.

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance versus Drain Current and Gate Voltage



Figure 4. On−Resistance Variation with Temperature



Figure 5. Drain−to−Source Leakage Current vs. Voltage



Figure 6. Capacitance Variation

Downloaded from Arrow.com.

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 7. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 8. Resistive Switching Time Variation vs. Gate Resistance



Figure 9. Diode Forward Voltage vs. Current



Figure 10. Normalized Thermal Transient Impedance, Junction−to−Ambient

ChipFET is a trademark of Vishay Siliconix.

Downloaded from Arrow.com.

ChipFET™
CASE1206A−03
ISSUE K

DATE 19 MAY 2009



SCALE 1:1



RESET

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. MOLD GATE BURRS SHALL NOT EXCEED 0.13 MM PER SIDE.
4. LEADFRAME TO MOLDED BODY OFFSET IN HORIZONTAL AND VERTICAL SHALL NOT EXCEED 0.08 MM.
5. DIMENSIONS A AND B EXCLUSIVE OF MOLD GATE BURRS.
6. NO MOLD FLASH ALLOWED ON THE TOP AND BOTTOM LEAD SURFACE.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	1.00	1.05	1.10	0.039	0.041	0.043
b	0.25	0.30	0.35	0.010	0.012	0.014
c	0.10	0.15	0.20	0.004	0.006	0.008
D	2.95	3.05	3.10	0.116	0.120	0.122
E	1.55	1.65	1.70	0.061	0.065	0.067
e	0.65 BSC			0.025 BSC		
e1	0.55 BSC			0.022 BSC		
L	0.28	0.35	0.42	0.011	0.014	0.017
H_E	1.80	1.90	2.00	0.071	0.075	0.079
θ	5° NOM			5° NOM		

STYLE 1:
PIN 1. DRAIN
2. DRAIN
3. DRAIN
4. GATE
5. SOURCE
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 2:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 3:
PIN 1. ANODE
2. ANODE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. CATHODE
8. CATHODE

STYLE 4:
PIN 1. COLLECTOR
2. COLLECTOR
3. COLLECTOR
4. BASE
5. EMITTER
6. COLLECTOR
7. COLLECTOR
8. COLLECTOR

STYLE 5:
PIN 1. ANODE
2. ANODE
3. DRAIN
4. DRAIN
5. SOURCE
6. GATE
7. CATHODE
8. CATHODE

STYLE 6:
PIN 1. ANODE
2. DRAIN
3. DRAIN
4. GATE
5. SOURCE
6. DRAIN
7. DRAIN
8. CATHODE / DRAIN

SOLDERING FOOTPRINT



Basic Style

GENERIC MARKING DIAGRAM*

XXX = Specific Device Code
M = Month Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

OPTIONAL SOLDERING FOOTPRINTS ON PAGE 2

DOCUMENT NUMBER:	98AON03078D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	ChipFET	PAGE 1 OF 2

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.

ChipFET™
CASE 1206A−03
ISSUE K

DATE 19 MAY 2009

ADDITIONAL SOLDERING FOOTPRINTS*



Styles 1 and 4



Style 2



Style 3



Style 5

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON03078D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**ChipFET**	**PAGE 2 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

Downloaded from Arrow.com.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Downloaded from Arrow.com.