

### NFM41PC155B1H3#

"#" indicates a package specification code.










< List of part numbers with package codes > NFM41PC155B1H3B NFM41PC155B1H3L



### Appearance & Shape







# **Applications**

Other Usage

For general



### Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	4000



### **Features**

The chip "EMIFIL" NFM41PC series consists of three terminal structure. These components are able to be applied to large current DC power lines. NFM41PC series are suitable in noise suppression in DC lines where relatively large currents operate.

### Features

- 1. Large rated current 6A(max.) is suitable for the application in DC power lines.
- 2. High electrostatic capacitance and remarkable high frequency performance are effective for immunity against surge noise and pulse noise.

### Applications

- 1. Personal computers, word processors and peripherals
- 2. Telephones, PPCs, communication equipment, etc.
- 3. Digital TVs, DVDs

1 of 3

Attention:

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: http://www.murata.com/

Last updated :2015/11/25



## NFM41PC155B1H3#

"#" indicates a package specification code.

1.5µF

±20%

Capacitance

Torelance



Shape	SMD
Size Code (in mm)	4516
Size Code (in inch)	1806
Length	4.5mm
Length Tolerance	±0.3mm
Width	1.6mm
Width Tolerance	±0.3mm
Thickness	1.0mm
Thickness Tolerance	±0.2mm
Rated Current	6.0A
Operating Temperature Range	-55℃ to 85℃
Mass(Typ.)	0.039g
Number of Circuit	1
DC Resistance(Max.)	0.009Ω
Insulation Resistance(Min.)	100.0ΜΩ
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc

2 of 3

ALIGHTON

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.com/


Last updated : 2015/11/25




## NFM41PC155B1H3#

"#" indicates a package specification code.







Insertion Loss Characteristics (Main Items)

**Equivalent Circuit** 

ACCENTION

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed space.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: http://www.murata.com/

Last updated : 2015/11/25

3 of 3