

Product Standards

PGA26E19BA

Revision. 008

Panasonic

PGA26E19BA

Type	GaN-Tr		
Application	For power switching		
Structure	N-channel enhancement mode FET		
Equivalent Circuit	Figure 1		
Out Line	DFN 8X8	Marking	PGA26E19

A. ABSOLUTE MAXIMUM RATINGS ($T_j = 25^\circ\text{C}$, unless otherwise specified)

No.	Item	Symbol	Values			Unit	Note
			Min.	Typ.	Max.		
1	Drain-source voltage (DC) *1	VDSS	-	-	600	V	
2	Drain-source voltage (pulse) *2	VDSP	-	-	750	V	
3	Gate-source voltage (DC) *1	VGSS	-10	-	-	V	*VGSS+ is given by IG ratings *See application note
4	Gate current (DC) *1	IG	-	-	19	mA	*See application note
5	Gate current (pulse) *3,4	IGP	-	-	0.6	A	*See application note
6	Electric gate charge (pulse)	QGP	-	-	12	nC	*f=200kHz *See application note
7	Drain current (DC) ($T_c = 25^\circ\text{C}$) *1	ID	-	-	15	A	Figure 4
8	Drain reverse current (DC) ($T_c = 25^\circ\text{C}$) *1	IDR	-	-	15	A	
9	Drain current (pulse) *5 ($T_c = 25^\circ\text{C}$) *1	ID pulse	-	-	23	A	Figure 4
10	Drain reverse current (pulse) *5 ($T_c = 25^\circ\text{C}$) *1	IDR pulse	-	-	23	A	
11	Power dissipation ($T_c = 25^\circ\text{C}$)	PD	-	-	83	W	Figure 2
12	Junction temperature	T_j	-55	-	150	$^\circ\text{C}$	
13	Storage temperature	T_{stg}	-55	-	150	$^\circ\text{C}$	
14	Drain-source voltage slope	dv/dt	-	-	200	V/ns	

[Special instructions]

*1 : Please use this product to meet a condition of T_j within 150°C .

*2 : Spike duty cycle $D < 0.1$, spike duration $< 1\mu\text{s}$, total spike time $< 1\text{hour}$.

*3 : IGP is defined as $(V_{cc} - V_{plateau}) / R_{gon}$, as shown in Figure A.
Vplateau is the voltage between Gate and Kelvin Source.

*4 : Please use this product to meet both a maximum gate current and a maximum gate pulse charge
of IGP(0.6A) and Q(12nC) respectively, as shown in Figure H.

*5 : Pulse width limited by T_{jmax} .

Established: 2014-09-25
Revised: 2019-03-07

Page 2 of 13

Established : 2019-12-02

Revision. 008



PGA26E19BA

B. ELECTRICAL CHARACTERISTICS (T_j = 25 °C, unless otherwise specified)

No.	Item	Symbol	Measurement Condition	Min.	Typ.	Max.	Unit
1	Drain cut-off current	IDSS	VDS=600 V, VGS=0 V, Tj=25 °C	-	-	39	μA
			VDS=600 V, VGS=0 V, Tj=150 °C	-	39	-	μA
2	Gate-source leakage current	IGSS	VGS=-3 V VDS=0 V	-1	-	-	μA
3	Gate forward voltage	VGSF	IGS=10 mA open drain	2.8	3.5	4.2	V
4	Gate threshold voltage	VTH	VDS=10 V IDS=1 mA	0.9	1.2	1.6	V
5	Drain-source on-state resistance	RDS(on)	IGS=10 mA, IDS=5 A, Tj=25 °C	-	140	190	mΩ
			IGS=10 mA, IDS=5 A, Tj=150 °C	-	290	-	mΩ
6	Gate resistance	RG	f=100MHz open drain	-	0.8	-	Ω
7	Transfer conductance	gfs	VDS=8 V IDS=5 A	-	15	-	S
8	Input capacitance	Ciss	VDS=400 V VGS=0 V f=1 MHz	-	160	-	pF
9	Output capacitance	Coss		-	28	-	pF
10	Reverse transfer capacitance	Crss		-	0.2	-	pF
11	Turn-on delay time	td(on)	VDD=400 V IDS=5 A (Figure A, Figure B) Vcc=12 V Rgon=15 Ω, Rgoff=4.7 Ω, Rig=1500 Ω, Cs=680 pF	-	3.4	-	ns
12	Rise time	tr		-	5.2	-	ns
13	Turn-off delay time	td(off)		-	3.4	-	ns
14	Fall time	tf		-	2.4	-	ns
15	Effective output capacitance (energy related)	Co(er)	VDS=0-480 V	-	33	-	pF
16	Effective output capacitance (time related)	Co(tr)		-	37	-	pF

Revision. 008

Panasonic

PGA26E19BA

C. GATE CHARGE CHARACTERISTICS (T_j = 25 °C, unless otherwise specified)

No.	Item	Symbol	Measurement Condition	Min.	Typ.	Max.	Unit
1	Gate charge	Qg	VDD=400 V IDS=5 A (Figure C, Figure D)	-	2.0	-	nC
2	Gate-source charge	Qgs		-	0.3	-	nC
3	Gate-drain charge	Qgd		-	1.0	-	nC
4	Gate plateau voltage	V plateau	VDD=400 V IDS=5 A	-	1.8	-	V

D. REVERSE CONDUCTING CHARACTERISTICS (T_j = 25 °C, unless otherwise specified)

No.	Item	Symbol	Measurement Condition	Min.	Typ.	Max.	Unit
1	Source-drain forward voltage	VSD	VGS=0 V ISD=5 A	-	2.6	-	V
2	Reverse recovery charge	Qrr	VDS=400 V ISD=5 A	-	0	-	nC
3	Reverse recovery time	trr		-	0	-	ns
4	Peak reverse recovery current	Irrm		-	0	-	A
5	Output charge	Qoss		-	17	-	nC


E. THERMAL RESISTANCE CHARACTERISTICS

No.	Item	Symbol	Measurement Condition	Min.	Typ.	Max.	Unit
1	Thermal resistance (junction to case)	Rth(j-c)		-	-	1.5	°C/W
2	Thermal resistance (junction to ambient) *1	Rth(j-a)		-	-	46	°C/W
3	Reflow soldering temperature	Tsold	reflow MSL3	-	-	260	°C


[Notes]

*1 : Device mounted on four layers epoxy PCB (6.45 cm² copper area and 70 μm thickness).


■ Equivalent circuit / Electrical characteristics




【Figure 1: Pin layout / Equivalent circuit】




【Figure 2: Max. power dissipation】




【Figure 3: Transient thermal impedance】




【Figure 4: Safe operating area $T_c = 25\ ^\circ\text{C}$ 】




【Figure 5: Safe operating area $T_c = 125\ ^\circ\text{C}$ 】




【Figure 6: Output characteristics Tc=25 °C】




【Figure 7: Output characteristics Tc=125 °C】




【Figure 8: Gate characteristics】




【Figure 9: Gate characteristics】




【Figure 10: Drain-source on-state resistance(RDS(on)-IGS)】




【Figure 11: Drain-source on-state resistance(RDS(on)-VGS)】




【Figure 12: Transfer characteristics (Tc=25°C)】




【Figure 13: Transfer characteristics (Tc=125°C)】




【Figure 14: Reverse channel characteristics (Tc=25°C)】




【Figure 15: Reverse channel characteristics (Tc=125°C)】




【Figure 16: Gate charge characteristics】




【Figure 17: Capacitance characteristics】




【Figure 18:Output capacitance stored energy】




【Figure 19:Output charge】




【Figure 20:Threshold voltage (VTH-Tj)】




【Figure 21:Drain-source on-state resistance(RDS(on)-Tj)】




【Figure 22:Drain-Source leakage current (Tc=25°C)】




【Figure A : Switching time measurement】




【Figure B : Switching wave form】




【Figure C : Gate charge measurement】




【Figure D : Gate charge wave form】




【Figure E : Reverse bias safe operating area dv/dt measurement circuit】




【Figure F : Reverse bias safe operating area dv/dt wave form】




【Figure G : di/dt measurement circuit】




【Figure H : IGP wave form】




【Figure 17:Output capacitance stored energy】



【Figure 18:Output charge】



【Figure.19:Threshold voltage (V_{TH} - T_j)】



【Figure.20:Drain-Source leakage current ($T_c=25^{\circ}C$)】

Revision. 008

Panasonic

PGA26E19BA

[Precautions for Use]

- 1) The product has risks for break-down or burst or giving off smoke in following conditions. Avoid the following use. Fuse should be added at the input side or connect zener diode between Gate pin and GND, etc as a countermeasure to pass regulatory Safety Standard. Concrete countermeasure could be provided individually. However, customer should make the final judgment.
 - (1) Reverse the Drain pin and gate pin connection to the power supply board.
 - (2) Drain pin short to Kelvin Source pin and Source pin.
 - (3) Drain pin short to Gate pin.
 - (4) Gate pin open.
- 2) This product is under development and is subject to change without notice standards.

Maintenance/Discontinued

Maintenance/Discontinued includes following four Product lifecycle stage.
(planned maintenance type, maintenance type, planned discontinued type, discontinued type)

Established: 2014-09-25
Revised: 2019-03-07

Page 11 of 13

Established : 2019-12-02


Revision. 008

Panasonic

PGA26E19BA

Outline

Unit: mm



SYMBOL	DIMENSION		
	MIN	NOM	MAX
A	1.15	1.25	1.35
A1	0.00	0.02	0.05
A2	0.40	0.50	0.60
b	0.90	1.00	1.10
D	7.90	8.00	8.10
D1	6.84	6.94	7.04
D2	0.40	0.50	0.60
E	7.90	8.00	8.10
E1	0.90	1.00	1.10
E2	3.10	3.20	3.30
E3	2.70	2.80	2.90
e	2.00 B.S.C.		
L	0.40	0.50	0.60

*Please note that technical specifications are subject to change without notice.

Revision. 008

■ Revision History

Revision No	Date	Description of change
007	2017-01-24	1st edition
008	2019-03-07	Drain current(DC), Power dissipation, Thermal resistance (junction to case), Pin name, Symbol mark, Safe operation area, Output characteristics, Transfer characteristics

Maintenance/Discontinued

Maintenance/Discontinued includes following four Product lifecycle stage.
(planned maintenance type, maintenance type, planned discontinued typed, discontinued type)

Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information de-scribed in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
Please consult with our sales staff in advance for information on the following applications, moreover please exchange documents separately on terms of use etc.: Special applications (such as for in-vehicle equipment, airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, medical equipment and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
Unless exchanging documents on terms of use etc. in advance, it is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. We do not guarantee quality for disassembled products or the product re-mounted after removing from the mounting board.
When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) When reselling products described in this book to other companies without our permission and receiving any claim of request from the resale destination, please understand that customers will bear the burden.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.

No.010618