



MJE371 PNP MJE521 NPN

SILICON COMPLEMENTARY POWER TRANSISTORS

JEDEC TO-126 CASE

# DESCRIPTION

The CENTRAL SEMICONDUCTOR MJE371, MJE521 types are Complementary Silicon Power Transistors designed for use in general purpose amplifier and switching applications.

# MAXIMUM RATINGS (TC=25°C)

	SYMBOL		UNIT
Collector-Base Voltage Collector-Emitter Voltage Emitter-Base Voltage Collector Current Collector Current (PEAK) Power Dissipation	V <sub>CBO</sub> V <sub>CEO</sub> V <sub>EBO</sub> I <sub>C</sub> I <sub>CM</sub> P <sub>D</sub>	40 40 4.0 4.0 8.0 40	V V V A A W
Operating and Storage Junction Temperature	T <sub>J</sub> , T <sub>stg</sub>	-65 TO +150	OC
Thermal Resistance	θJC	3.1	°c/w

# ELECTRICAL CHARACTERISTICS (T<sub>C</sub>=25°C)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
СВО	V <sub>CB</sub> =40V		100	μА
I <sub>EBO</sub>	V <sub>EB</sub> =4.0V		100	μΑ
BV <sub>CEO</sub>	I_=100mA	40		V
hFE	V <sub>CE</sub> =1.0V, I <sub>C</sub> =1.0A	40		



To-126

145 Adams Avenue, Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824

## **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- · Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

### REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### **CONTACT US**

### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

**Worldwide Distributors:** 

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <a href="https://www.centralsemi.com/terms">www.centralsemi.com/terms</a>