



+ CONNECTORS
RF CONNECTORS



✓ Active

TE CONNECTIVITY (TE)
2056 5168 00
Subminiature Coax | SM , SMA

1053111-1
TE Internal Number: 1053111-1
Alias ID: 2056-5168-00

EU RoHS Compliant with Exemptions
EU ELV Compliant with Exemptions

Connector Interface SMA

Connector Style Jack

Mated Outer Diameter (Approximate) 6.35 mm [.25 in]

Impedance (Ω) 50

Operating Frequency (GHz) 18

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

DOCUMENTATION

Product Drawings

OSM BULKHEAD FEEDTHRU JACK RECEPTACLE-SOLDER POT TERMINAL

PDF (TIFF AVAILABLE)

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Interface SMA

Connector Style Jack

Electrical Characteristics

Impedance (Ω) 50

Body Features

Cable Connector Orientation Straight

Body Material Stainless Steel

Body Plating Material Gold

Contact Features

Center Contact Plating Material Gold over Copper

Center Contact Material Beryllium Copper

Connector Product Type Connector Assembly

RF Connector Contact Configuration Captivated Contacts

Termination Features

Termination Method to Wire & Cable Solder

Mechanical Attachment

Connector Mounting Type Panel

Panel Attachment Style Rear Mount

Dimensions

Mated Outer Diameter (Approximate) 6.35 mm [.25 in]

Length 17 mm [.669 in]

Operation/Application

Operating Frequency (GHz) 18

Packaging Features

Packaging Method Bag

Other

Dielectric Material TFE Fluorocarbon

Lockwasher Material Stainless Steel

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF