| REV SYMBOL | ZONE | REVISION HISTORY | APP | DATE |
|---|---|---|---|---|
| CNP11 | B | 20 | 16 TO PARTS - CLOSED REV AS NOW. CHANGED TOP PART AND CRIMP. | KEITH | JUN.03.2010 |
| CNP10 | B | 19 | DESCRIPTION CHANGED FOR EAR. ADDED NEW CAVITIES: 1,2,9,10,11,12. CHALCOT - BASE MAT'L SPEC WAS CHANGED. | KEENER | JUN.24.2008 |
| CNP10 | B | 18 | ALL PARTS - UPDATED PDM ATTRIBUTES | KEENER | JUN.24.2008 |

| CAVITY A | WIRE SIZE RANGE (AWG) | WIRE INSULATION DIA. | WIRE BARREL DIA. | CONDUCTOR CRIMP HEIGHT (+/- 0.02) | CONDUCTOR CRIMP WIDTH (+/- 0.02) | INSULATION CRIMP HEIGHT (+/- 0.02) | INSULATION CRIMP WIDTH (+/- 0.02) | INSULATION CRIMP OPTION | REQ. TOOLS |
|---|---|---|---|---|---|---|---|---|---|
| A1 | 20 | 0.45 | | 1.16 | 1.19 | 1.85 | 1.75 | 1.85 | 2 |
| A2 | 18 | 0.51 | | 1.16 | 1.19 | | 1.85 | 2.00 | 2 |
| A3 | 18 | 0.58 | | 1.30 | 1.35 | 2.03 | 2.00 | 2.20 | 2 |
| A4 | 18 | 0.70/.02 | | 1.30 | 1.35/.01 | | 2.03 | 2.10/.02 | 2 |
| A5 | 20 | 0.58 | | 1.30 | 1.35 | | 2.00 | 2.20 | 2 |
| A6 | 18 | 0.80/.02 | | 1.70 | 1.80/.01 | | 4.00 | 4.10/.05 | 4.00 | OPTION 2 | 2 |
| A7 | 16 | 1.58 | | 1.70 | 1.84 | 2.41 | 4.25 | 4.00/4.05 | 2 |
| A8 | 16 | 1.80/.05 | | 1.70 | 1.80/.01 | | 3.75 | 3.80/3.85 | 2 |
| A9 | 16 | 1.58 | | 1.70 | 1.84 | | 2.00 | 2.00/2.05 | 2.00 | OPTION 1 | 2 |
| A10 | 16 | 2.00/.05 | | NARROW | NARROW | 3.41 | NARROW | NARROW | 4.20 | OPTION 1 | 2 |
| A11 | 12 | 3.56 | | 1.81 | 1.95 | 3.41 | 4.00 | 4.00 | 4.80 | | 2 |
| A12 | 12 | 3.56 | | | | | 3.19 | 3.30 | 3.85 | OPTION 2 | 2 |
| A13 | 12 | 1.80/.05 | | 2.23 | 2.40/.01 | 4.41 | N/A | N/A | N/A | | 2 |
| A14 | 12 | 2.00 | | 1.81 | 2.05 | | N/A | N/A | N/A | | 2 |
| A15 | 12 | 1.80/.05 | | 2.23 | 2.40/.01 | | 4.75 | 4.30 | 4.20 | OPTION 1 | 2 |
| A16 | 12 | 2.00 | | 1.81 | 2.05 | | (2.0 IN 3MM) | 3.30 | | | 2 |

* NOT VERIFIED TO VECAM-21

| CRIMP A | CRIMP DIMENSIONS | | | | |