

**GLASS PASSIVATED BRIDGE RECTIFIERS**

REVERSE VOLTAGE - **50 to 1000** Volts  
FORWARD CURRENT - **15** Amperes


**FEATURES**

- Rating to 1000V PRV
- High efficiency
- Glass passivated chip junction
- Electrically isolated metal case for maximum heat dissipation
- The plastic material has UL flammability classification 94V-0
- UL Recognition File # E95060


**MECHANICAL DATA**

- Case : Molded plastic with Heatsink internally mounted in the bridge encapsulation
- Polarity : As marked on Body
- Mounting : Hole for # 10 screw
- Weight : 0.63 ounces , 18.0 grams (terminal)  
: 0.51 ounces , 14.5 grams (wire)

**GBPC-W (Wire)**



**GBPC (Terminal)**



**GBPC/GBPC-W**

| DIM. | MIN.                  | MAX.  |
|------|-----------------------|-------|
| A    | 31.80                 | -     |
| B    | 7.40                  | 8.00  |
| C    | 28.30                 | 28.80 |
| D    | 17.60                 | 18.60 |
| E    | 0.97                  | 1.07  |
| F    | 10.90                 | 11.90 |
| G    | 17.60                 | 18.60 |
| H    | 13.80                 | 14.80 |
| I    | 16.10                 | 17.10 |
| J    | 16.10                 | 17.10 |
| K    | 18.80                 | 21.30 |
| L    | 0.76                  | 0.86  |
| M    | 6.30                  | 6.50  |
| N    | HOLE FOR NO. 10 SCREW |       |
|      | 5.08                  | 5.59  |

All Dimensions in millimeter

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

| CHARACTERISTICS                                                                                              | SYMBOL            | GBPC<br>15005/W | GBPC<br>1501/W | GBPC<br>1502/W | GBPC<br>1504/W | GBPC<br>1506/W | GBPC<br>1508/W | GBPC<br>1510/W | UNIT             |
|--------------------------------------------------------------------------------------------------------------|-------------------|-----------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|
| Maximum Recurrent Peak Reverse Voltage                                                                       | V <sub>RRM</sub>  | 50              | 100            | 200            | 400            | 600            | 800            | 1000           | V                |
| Maximum RMS Voltage                                                                                          | V <sub>RMS</sub>  | 35              | 70             | 140            | 280            | 420            | 560            | 700            | V                |
| Maximum DC Blocking Voltage                                                                                  | V <sub>DC</sub>   | 50              | 100            | 200            | 400            | 600            | 800            | 1000           | V                |
| Maximum Average Forward Rectified Current @T <sub>c</sub> = T <sub>a</sub>                                   | I <sub>(AV)</sub> | 15.0            |                |                |                |                |                |                | A                |
| Peak Forward Surge Current<br>8.3ms single half sine-wave<br>superimposed on rated load                      | I <sub>FSM</sub>  | 300             |                |                |                |                |                |                | A                |
| Maximum forward Voltage at 7.5A DC                                                                           | V <sub>F</sub>    | 1.1             |                |                |                |                |                |                | V                |
| Maximum DC Reverse Current<br>at Rated DC Blocking Voltage @T <sub>J</sub> = 25°C<br>@T <sub>J</sub> = 125°C | I <sub>R</sub>    | 5.0<br>500      |                |                |                |                |                |                | uA               |
| Typical Junction Capacitance<br>per element (Note 1)                                                         | C <sub>J</sub>    | 110             |                |                |                |                |                |                | pF               |
| I <sup>2</sup> t Rating for fusing (t < 8.3ms), (Note 2)                                                     | I <sup>2</sup> t  | 374             |                |                |                |                |                |                | A <sup>2</sup> S |
| Typical Thermal Resistance (Note 3)                                                                          | R <sub>θJC</sub>  | 5.0             |                |                |                |                |                |                | °C/W             |
| Operating Temperature Range                                                                                  | T <sub>J</sub>    | -55 to +150     |                |                |                |                |                |                | °C               |
| Storage Temperature Range                                                                                    | T <sub>STG</sub>  | -55 to +150     |                |                |                |                |                |                | °C               |

NOTES : 1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2.Measured at non-repetitive, for greater than 1ms and less than 8.3ms

3.Device mounted on 300mm x 300mm x 1.6mm Cu Plate Heatsink.

REV. 4, Sep-2010, KBDH01

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL JUNCTION CAPACITANCE




FIG.4 - TYPICAL FORWARD CHARACTERISTICS





FIG.5 - TYPICAL REVERSE CHARACTERISTICS



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.