

# C3M0900170J

1700V 900mΩ Silicon Carbide Power MOSFET  
N-Channel Enhancement Mode

## Features

- High blocking voltage with low on-resistance
- High-speed switching with low capacitances
- 12V..18V / 0V  $V_{GS}$  compatible with most flyback controllers
- Ultra-low drain-gate capacitance
- Qualified to operate under high humidity and high temperature environmental conditions
- Halogen free, RoHS compliant


## Benefits

- Smooth switching waveforms
- Reduce switching losses and minimize gate ringing
- Higher system efficiency
- Increases system switching frequency
- Increases system reliability


## Typical Applications

- Auxiliary power supplies
- Switch Mode Power Supplies
- High-Voltage capacitive loads

## Package



TO-263-7



Orderable Part Number	Package	Marking
C3M0900170J-TR	TO-263-7L	C3M0900170J

## Key Parameters

Parameter	Symbol	Min.	Typ.	Max	Unit	Conditions	Note
Drain - Source Voltage	$V_{DS}$			1700	V	$T_c = 25^\circ C$	Note 2
Maximum Gate - Source Voltage (Transient)	$V_{GS(max)}$	-8		+20		Transient	
Operational Turn-On Gate-Source Voltage			+12...+18			Static	
Operational Turn-Off Gate-Source Voltage			-4...0		A	$V_{GS} = 15 V, T_c = 25^\circ C, T_j \leq 175^\circ C$	Note 2
DC Continuous Drain Current	$I_D$			4.4		$V_{GS} = 15 V, T_c = 100^\circ C, T_j \leq 175^\circ C$	
Pulsed Drain Current	$I_{DM}$			15	W	$t_{pmax}$ limited by $T_{jmax}$ $V_{GS} = 15 V, T_c = 25^\circ C$	Fig. 22
Power Dissipation	$P_D$			41		$T_c = 25^\circ C, T_j = 175^\circ C$	
Operating Junction and Storage Temperature	$T_j, T_{stg}$			-55 to +175	°C		Fig. 20
Solder Temperature	$T_L$			260			

Note (1): Review application Note PRD-04814 for additional details

Note (2): Verified by design

Electrical Characteristics ( $T_c = 25^\circ C$  unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	1700			V	$V_{GS} = 0 V, I_D = 100 \mu A$	
$V_{GS(th)}$	Gate Threshold Voltage	1.8	3.1	4.2	V	$V_{DS} = V_{GS}, I_D = 0.55 mA$	Fig. 11
			2.6		V	$V_{DS} = V_{GS}, I_D = 0.55 mA, T_J = 175^\circ C$	
$I_{DSS}$	Zero Gate Voltage Drain Current		1	50	$\mu A$	$V_{DS} = 1700 V, V_{GS} = 0 V$	
$I_{GSS}$	Gate-Source Leakage Current		10	250	nA	$V_{GS} = 15 V, V_{DS} = 0 V$	
$R_{DS(on)}$	Drain-Source On-State Resistance		900	1250	$m\Omega$	$V_{GS} = 15 V, I_D = 1.99 A$	Fig. 4, 5, 6
			1938			$V_{GS} = 15 V, I_D = 1.99 A, T_J = 175^\circ C$	
$g_{fs}$	Transconductance		1		S	$V_{DS} = 20 V, I_{DS} = 1.99 A$	Fig. 7
			1			$V_{DS} = 20 V, I_{DS} = 1.99 A, T_J = 175^\circ C$	
$C_{iss}$	Input Capacitance		202		pF	$V_{GS} = 0 V, V_{DS} = 0 V$ to 1200 V $F = 100 kHz$ $V_{AC} = 25 mV$	Fig. 17, 18
$C_{oss}$	Output Capacitance		8				
$C_{rss}$	Reverse Transfer Capacitance		1.4				
$E_{oss}$	$C_{oss}$ Stored Energy		8		$\mu J$	$V_{GS} = 0 V, V_{DS} = 0 V$ to 1200V	Fig. 16
$C_{o(er)}$	Effective Output Capacitance (Energy Related)		10		pF		
$C_{o(tr)}$	Effective Output Capacitance (Time Related)		13		pF		
$E_{ON}$	Turn-On Switching Energy (External Diode)		128		$\mu J$	$V_{DS} = 1200 V, V_{GS} = -4 V/15 V, I_D = 1.99 A, R_{G(ext)} = 2.5 \Omega, L = 1707 \mu H, T_J = 175^\circ C$ FWD = External SiC DIODE	Fig. 26, 28
$E_{OFF}$	Turn Off Switching Energy (External Diode)		13				
$t_{d(on)}$	Turn-On Delay Time		20				
$t_r$	Rise Time		16				
$t_{d(off)}$	Turn-Off Delay Time		20		ns	$V_{DD} = 1200 V, V_{GS} = -4 V/15 V$ $I_D = 1.99 A, R_{G(ext)} = 2.5 \Omega, T_J = 175^\circ C$ $L = 1707 \mu H$ Timing relative to $V_{DS}$ Inductive load	Fig. 27, 28
$t_f$	Fall Time		42				
$R_{G(int)}$	Internal Gate Resistance		31		$\Omega$	$f = 1 MHz, V_{AC} = 25 mV$	
$Q_{gs}$	Gate to Source Charge		4		nC	$V_{DS} = 1200 V, V_{GS} = -4 V/15 V$ $I_D = 1.99 A$ Per IEC60747-8-4 pg 21	Fig. 12
$Q_{gd}$	Gate to Drain Charge		2				
$Q_g$	Total Gate Charge		8				

Note (3):  $C_{o(er)}$ , a lumped capacitance that gives same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 1200V  
 $C_{o(tr)}$ , a lumped capacitance that gives same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 1200V


**Reverse Diode Characteristics ( $T_c = 25^\circ C$  unless otherwise specified)**

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$V_{SD}$	Diode Forward Voltage	4.7		V	$V_{GS} = -4 V, I_{SD} = 1 A, T_j = 25^\circ C$	Fig. 8, 9, 10
		4.2		V	$V_{GS} = -4 V, I_{SD} = 1 A, T_j = 175^\circ C$	
$I_S$	Continuous Diode Forward Current	5.8		A	$V_{GS} = -4 V, T_c = 25^\circ C$	
$I_{SM}$	Diode pulse Current		15	A	$V_{GS} = -4 V$ , pulse width $t_p$ limited by $T_{jmax}$	
$t_{rr}$	Reverse Recover time	22		ns	$V_{GS} = -4 V, I_{SD} = 1.99 A, V_R = 1200 V$ $dif/dt = 546 A/\mu s, T_j = 25^\circ C$	
$Q_{rr}$	Reverse Recovery Charge	50		nC		
$I_{rrm}$	Peak Reverse Recovery Current	5		A	$V_{GS} = -4 V, I_{SD} = 1.99 A, V_R = 1200 V$ $dif/dt = 246 A/\mu s, T_j = 25^\circ C$	
$t_{rr}$	Reverse Recover time	28		ns		
$Q_{rr}$	Reverse Recovery Charge	46		nC		
$I_{rrm}$	Peak Reverse Recovery Current	3		A		

**Thermal Characteristics**

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$R_{0JC}$	Thermal Resistance from Junction to Case	3.0	3.6	°C/W		Fig. 21

## Typical Performance













Figure 1. Output Characteristics  $T_J = -55 \text{ }^{\circ}\text{C}$ Figure 2. Output Characteristics  $T_J = 25 \text{ }^{\circ}\text{C}$ Figure 3. Output Characteristics  $T_J = 175 \text{ }^{\circ}\text{C}$ 

Figure 5. On-Resistance vs. Drain Current For Various Temperatures



## Typical Performance



## Typical Performance





Figure 13. 3rd Quadrant Characteristic at  $-55\text{ }^{\circ}\text{C}$ Figure 14. 3rd Quadrant Characteristic at  $25\text{ }^{\circ}\text{C}$ Figure 15. 3rd Quadrant Characteristic at  $175\text{ }^{\circ}\text{C}$ 

Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1700V)

## Typical Performance




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature




Figure 21. Transient Thermal Impedance (Junction - Case)






Figure 22. Safe Operating Area

Figure 23. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 900V$ )Figure 24. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 1200V$ )

## Typical Performance




Figure 25. Clamped Inductive Switching Energy vs.  $R_{G(\text{ext})}$ Figure 26. Switching Times vs.  $R_{G(\text{ext})}$ 

Figure 27. Switching Times Definition



Test Circuit Schematic

Figure 28. Clamped Inductive Switching  
Waveform Test Circuit


## Package Dimensions





## Recommended Solder Pad Layout

All dimensions in mm





## Revision history

---

Document Version	Date of release	Description of changes
1.0	December-2024	Initial datasheet
2.0	February-2025	Updated with latest characterization data



## Notes & Disclaimer

WOLFSPEED PROVIDES TECHNICAL AND RELIABILITY DATA, DESIGN RESOURCES, APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRDPARTY INTELLECTUAL PROPERTY RIGHTS.

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Wolfspeed. No communication from any employee or agent of Wolfspeed or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.

The information contained in this document (excluding examples, as well as figures or values that are labeled as "typical") constitutes Wolfspeed's sole published specifications for the subject product. "Typical" parameters are the average values expected by Wolfspeed in large quantities and are provided for informational purposes only. Any examples provided herein have not been produced under conditions intended to replicate any specific end use. Product performance can and does vary due to a number of factors.

This product has not been designed or tested for use in, and is not intended for use in, any application in which failure of the product would reasonably be expected to cause death, personal injury, or property damage. For purposes of (but without limiting) the foregoing, this product is not designed, intended, or authorized for use as a critical component in equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment; air traffic control systems; or equipment used in the planning, construction, maintenance, or operation of nuclear facilities. Notwithstanding any application-specific information, guidance, assistance, or support that Wolfspeed may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer's purposes, including without limitation (1) selecting the appropriate Wolfspeed products for the buyer's application, (2) designing, validating, and testing the buyer's application, and (3) ensuring the buyer's application meets applicable standards and any other legal, regulatory, and safety-related requirements.

### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented February 2, 2013. RoHS Declarations for this product can be obtained from your Wolfspeed representative or from the Product Documentation sections of [www.wolfspeed.com](http://www.wolfspeed.com).

### REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Wolfspeed representative to ensure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

### Contact info:

4600 Silicon Drive  
Durham, NC 27703 USA  
Tel: +1.919.313.5300  
[www.wolfspeed.com/power](http://www.wolfspeed.com/power)

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed® and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.  
PATENT: <https://www.wolfspeed.com/legal/patents>

The information in this document is subject to change without notice.

Rev. 2, February 2025

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed® and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.  
The information in this document is subject to change without notice.