Part Number : 2065600100
Product Description : 1558MHz-1610MHz GNSS Flex Antenna, 100.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors
Series Number : 206560
Status : Active
Product Category : Antennas



Documents and Resources

Drawings

2065600100_sd.pdf

2065600050-001.pdf

3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Specifications

2065600050-AS.pdf

2065600050-PS.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)7771-DC (04 Feb 2026)
EU RoHS	Compliant per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

Downloaded from Arrow.com.

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	Antennas
Series	206560
Description	1558MHz-1610MHz GNSS Flex Antenna, 100.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors
Component Type	Flexible Antenna with Cable
Function	Signal
Product Name	1558MHz-1610MHz GNSS Flexible
Protocol	BeiDou, GLONASS, GPS
Type	GNSS Antenna, Internal
UPC	191128769112

Electrical

Band#1 F_End (MHz)	1564
Band#1 F_Start (MHz)	1558
Band#2 F_End (MHz)	1578
Band#2 F_Start (MHz)	1572
Band#3 F_End (MHz)	1605
Band#3 F_Start (MHz)	1599
Electrical Connectivity	Cable
Peak Gain (dBi)	0.9 @ 1561 MHz, 1.0 @ 1575 MHz, 1.37 @ 1602 MHz
Return Loss - S11 (dB)	< -8

Downloaded from Arrow.com.

Total Efficiency	>72% @ 1575 MHz, >72% @ 1561 MHz, >73% @ 1602 MHz

Physical

Cable Length	100.00mm
Length	40.40mm
Mounting Style	Adhesive
Net Weight	0.593/g
Packaging Type	PET Film
Polarization	Linear
Radiation Pattern	Omnidirectional
Thickness	0.10mm
Width	15.40mm

Mates With / Use With

Mates with Part(s)

Description	Part Number
MCRF Jack, Straight, PCB Receptacle, Surface Mount, 1.25mm Mounted Height, 50 Ohms	734120110

Downloaded from Arrow.com.