

# Product data sheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, 48U, Shock Packaging, 2000 lbs, Black, 2258H x 600W x 1200D mm

AR3307SP

### Overview

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentation | NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 2000 lbs (907 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS). |
| Lead time    | Usually in Stock                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### Main

|                           |                                                                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Product or component type | Rack enclosure                                                                                                                             |
| Number of rack unit       | 48U                                                                                                                                        |
| Provided equipment        | Baying hardware<br>Documentation CD<br>Key(s)<br>Leveling feet<br>Mounting hardware<br>Pre-installed casters<br>Side panels<br>User manual |

### Physical

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Height                     | 225.8 cm                                                                                                                          |
| Width                      | 60 cm                                                                                                                             |
| Depth                      | 120 cm                                                                                                                            |
| Net weight                 | 149.55 kg                                                                                                                         |
| Colour                     | Black                                                                                                                             |
| Mounting preference        | No preference                                                                                                                     |
| Mounting mode              | Not rack-mountable                                                                                                                |
| Maximum mounting depth     | 105.99 cm                                                                                                                         |
| minimum mounting depth     | 19.1 cm                                                                                                                           |
| Rack width                 | 19"                                                                                                                               |
| Marking                    | 14 gauge EIA mounting rail<br>16 gauge front door<br>16 gauge post<br>18 gauge rear door<br>18 gauge roof<br>18 gauge side panels |
| Permanent permissible load | 1020.6 kg dynamic<br>1701.0 kg static                                                                                             |

### Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|           |                                   |
|-----------|-----------------------------------|
| Standards | UL 2416<br>UL 60950-1<br>EIA-310E |
|-----------|-----------------------------------|

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 245.1 cm  |
| Package 1 Width              | 132.1 cm  |
| Package 1 Length             | 110.5 cm  |
| Package 1 Weight             | 272.61 kg |

## Contractual warranty

|          |                          |
|----------|--------------------------|
| Warranty | 5 year repair or replace |
|----------|--------------------------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

| Environmental footprint                               |     |
|-------------------------------------------------------|-----|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 827 |

| Use Better |  |
| Materials and Substances |  |
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| [EU RoHS Directive](#) | Pro-active compliance (Product out of EU RoHS legal scope) |
| REACH Regulation | [REACH Declaration](#) |
| Use Again |  |
| Repack and remanufacture |  |
| Circularity Profile | [End of Life Information](#) |
| Take-back | Yes |