

SuperChassis 101i



- ▶ [Chassis Manual](#)
- ▶ [Optimization](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Features

1. Slim & Space-saving Chassis Design
2. Optional 60W/80W DC-in Power adapter or DC/DC Power converter board
3. 1x 2.5" internal HDD support
4. 1x 6cm Cooling Fan
5. Front I/O: 2x USB 2.0 & 2x Audio port
6. Power switch w/ 1x LED
7. VESA/Wall-mount ready

Specifications ^

Product SKUs

- CSE-101i ■ SuperChassis 101i

Form Factor

- Mini-ITX Chassis for motherboard support size: (Mini-ITX 6.75" x 6.75")

Processor Support

- Intel® Atom™ processors
- Single Intel® and AMD processors

Dimensions

- Height** ■ 2.68" (68 mm)
- Width** ■ 7.68" (195 mm)
- Depth** ■ 7.68" (195 mm)
- Net Weight** ■ 2.76 lbs (1.25 kg)
- Gross Weight** ■ 7.5 lbs (3.4 kg)
- Packaging (W x H x L)** ■ 15" (381 mm) x 10.87" (276 mm) x 5.59" (142 mm)
- Available Color** ■ Black

Drive Bays

- 1 x 2.5" fixed drive bay
- Enterprise SATA HDD only recommended

Front Panel

- Buttons** ■ Power On/Off button
- LEDs** ■ HDD activity LED
■ Power Status LED
■ Power off LED
- Ports** ■ 2x USB 2.0 Port(s)
■ 2x Audio Jack(s)

Systems Cooling

- Fans** ■ 1 x 6cm 4-pin high performance cooling fan(s)

Operating Environment (System)

- Operating Temperature Range** ■ 0°C - 40°C (32°F - 104°F)
- Non-Operating Temperature Range** ■ -20°C - 60°C (-4°F - 140°F)
- Operating Relative Humidity Range** ■ 10% - 85% (non-condensing)
- Non-Operating Relative Humidity Range** ■ 10% - 95% (non-condensing)

Power Supply

Optional 60W/84W, DC-DC Power Adapter or DC/DC Power converter board

- Certification** ■ N/A

Regulatory (Power Supply)

- Power Supply Safety / EMC** ■ CCC
■ CE/EMC
■ FCC
■ TUV/CB
■ UL/CUL

Components ^

Standard Parts List

	Part Number	Qty	Description
Front Panel	FPB-FP101-U2	1	Front control board for CSE-101i with USB2.0 and audio

	Part Number	Qty	Description
Cable	CBL-0296L	-	9" 4 pin fan extension cord, for fan guide pin at 1&3 or 1&4
Cable	CBL-0080L	-	SATA Power Adapter Cable 6"
Power Board	MCP-250-10103-0N	-	80W DC-ATX PWR Board
Power Adapter	MCP-250-10117-0N	-	60W DC power adapter with US power cord 18AWG 6ft
Power Adapter	MCP-250-10122-0N	-	84W DC power adapter with US power cord 18AWG 6ft
Chassis parts	MCP-290-10108-0B	-	Dual system tray for Mini-ITX system

Motherboard (for CSE- 101i)

X9SCV-Q	X9SCV-QV4	X9SPV-F-3610ME	X9SPV-F-3217UE
X9SPV-LN4F-3LE	X9SPV-LN4F-3QE	X9SPV-M4	X9SBAA-F
X9SCAA	X9SCAA-L	X9SPV-M4-3QE	X9SPV-M4-3UE
X10SLV	X10SBA-L	A1SAI-2750F	A1SAI-2550F
X10SBA	A1SRi-2758F	X10SLV-Q	A1SRi-2558F
X11SBA-LN4F	X11SBA-F	X11SSV-Q	A1SRi-2358F
X11SSV-LVDS	A2SAV	A2SAV-L	X11SAA
A2SDi-2C-HLN4F	A2SDi-4C-HLN4F	A2SDi-8C+-HLN4F	A2SDi-12C-HLN4F
A2SDi-16C-HLN4F	A2SDi-8C-HLN4F		

● = Most optimized Chassis for SuperServer Configuration
Blue color = Compatible
Green color = Global SKU & Compatible
Red dot & green color = Optimized + Global SKU

Servers (for CSE- 101i)

1018L-MP

Home » Products » Chassis » Mini-ITX » SC101i

Global SKU  English 

About Us

Company Profile
Green Computing
Investor Relations
Careers
Site Map

Resources

Solutions Briefs
Success Stories
Videos
White Papers
MySupermicro

News

Press Releases
Supermicro in the News
Product Reviews
Events
Webinars

Connect & Follow

Locations
Newsletter Sign-up



This site uses cookies. By continuing to browse the site you are agreeing to our use of cookies. Review our cookies information here for more details.

Copyright © 20192019 Super Micro Computer, Inc. All Rights Reserved
referred to herein are trademarks or registered trademarks of their respective companies or mark holders.
Click for Logo Guidelines

