Home

Design Resources &

Application Notes

Design Notes

Design &

Collateral Brochures

**Development Tools** 

**Evaluation Board** 

Package Drawings

Recommendation

Sample Kits and

Printed Documents

Reference Designs

Reference Manuals

Simulation Models

**Documents** 

Product

Tools

Tutorials

Software White Papers

▶ Technical Support

Videos

Community GreenPoint® Design

Evaluation / **Development Tools** 

Conformance Reports Data Sheets

▼ Design Support

Documents

Products

Design Support

#### **Energy Efficient Innovations**

💽 Part #/Keyword

Quality

MyON

Search

🕒 Cross-Reference 🐡 Search Help

Previously Viewed **Products** 

Clear List

|Select Product...

#### Design Support

- >> Technical
- Documentation Design Resources & Documents
- » Technical Support
- » Sales Support

Home > Support > Design Support > Design Resources & Documents > Evaluation/Development Tools

# NCP702MX30TCGEVB: 3.0 V LDO Linear Regulator Evaluation

Applications

# Board

## Evaluation/Development Tool Description

The NCP702 is a high performance 200mA Low Dropout Linear Regulator, This device delivers excellent noise and dynamic performance. Thanks to its adaptive ground current feature the device consumes only 10µA of quiescent current

The regulator features ultra-low noise of 11µVRMS, the PSRR of 68dB at 1kHz and very good load/line transient performance. Such excellent dynamic parameters and small package size make the device an ideal choice for powering the precision analog and noise sensitive circuitry in portable applications. The LDO achieves this ultra-low noise level without the need for a noise bypass capacitor.

A Logic EN input provides ON/OFF control of the output voltage. When the EN is low the device consumes as low as typ. 10nA from the IN terminal. The device is fully protected in case of output overload, output short circuit condition and overheating assuring a very robust design.

This demonstration board operates from a dc input voltage: VIN ≤ 5.5V and produces fixed output voltage which is set internally within the IC. External waveform generator could be connected to the EN (Enable) pin in order to verify the ON/OFF operation.

# at no-load condition. ON SEMICONDUCTOR

### Evaluation/Development Tool Information

Product	Statu	s Compliance	Short Description	Parts Used	Action
NCP702MX30TC	GEVB Active	Pb-free	3.0 V LDO Linear Regulator Evaluation Board	NCP702MX30TCG	Buy Now Contact Local Sales Office Inventory

Technical Documents						
Туре	Document Title	Document ID/Size	Rev			
Eval Board: BOM	NCP702MX30TCGEVB Bill of Materials ROHS Compliant	NCP702MX30TCGEVB_BOM_ROHS.PDF - 70.0 KB	0			
Eval Board: Gerber	NCP702MX30TCGEVB Gerber Layout Files (Zip Format)	NCP702MX30TCGEVB_GERBER.ZIP - 30.0 KB				
Eval Board: Schematic	NCP702MX30TCGEVB Schematic	NCP702MX30TCGEVB_SCHEMATIC.PDF - 28.0 KB				
Eval Board: Test Procedure	NCP702MX30TCGEVB Test Procedure	NCP702MX30TCGEVB_TEST_PROCEDURE.PDF - 242.0 KB	0			

Privacy Policy | Terms of Use | Site Map | Careers | Contact Us | Terms and Conditions | Mobile Portal | Mobile App









Copyright © 1999-2015 ON Semiconductor Follow Us