


User's manual FLIR T6xx series



Important note

Before operating the device, you must read, understand, and follow all instructions, warnings, cautions, and legal disclaimers.

Důležitá poznámka

Před použitím zařízení si přečtěte veškeré pokyny, upozornění, varování a vyvázání se ze záruky, ujistěte se, že jim rozumíte, a řiďte se jimi.

Vigtig meddelelse

Før du betjener enheden, skal du du læse, forstå og følge alle anvisninger, advarsler, sikkerhedsforanstaltninger og ansvarsfraskrivelser.

Wichtiger Hinweis

Bevor Sie das Gerät in Betrieb nehmen, lesen, verstehen und befolgen Sie unbedingt alle Anweisungen, Warnungen, Vorsichtshinweise und Haftungsausschlüsse

Σημαντική σημείωση

Πριν από τη λειτουργία της συσκευής, πρέπει να διαβάσετε, να κατανοήσετε και να ακολουθήσετε όλες τις οδηγίες, προειδοποιήσεις, προφυλάξεις και νομικές αποποιήσεις.

Nota importante

Antes de usar el dispositivo, debe leer, comprender y seguir toda la información sobre instrucciones, advertencias, precauciones y renuncias de responsabilidad.

Tärkeä huomautus

Ennen laitteen käyttämistä on luettava ja ymmärrettävä kaikki ohjeet, vakavat varoitukset, varoitukset ja lakitiedotteet sekä noudatettava niitä.

Remarque importante

Avant d'utiliser l'appareil, vous devez lire, comprendre et suivre l'ensemble des instructions, avertissements, mises en garde et clauses légales de non-responsabilité.

Fontos megjegyzés

Az eszköz használata előtt figyelmesen olvassa el és tartsa be az összes utasítást, figyelmeztetést, óvintézkedést és jogi nyilatkozatot.

Nota importante

Prima di utilizzare il dispositivo, è importante leggere, capire e seguire tutte le istruzioni, avvertenze, precauzioni ed esclusioni di responsabilità legali.

重要な注意

デバイスをご使用になる前に、あらゆる指示、警告、注意事項、および免責条項をお読み頂き、その内容を理解して従ってください。 중요한 참고 사항

장치를 작동하기 전에 반드시 다음의 사용 설명서와 경고, 주의사항, 법적 책임제한을 읽고 이해하며 따라야 합니다.

Viktig

Før du bruker enheten, må du lese, forstå og følge instruksjoner, advarsler og informasjon om ansvarsfraskrivelse.

Belangrijke opmerking

Zorg ervoor dat u, voordat u het apparaat gaat gebruiken, alle instructies, waarschuwingen en juridische informatie hebt doorgelezen en begrepen, en dat u deze opvolgt en in acht neemt.

Ważna uwaga

Przed rozpoczęciem korzystania z urządzenia należy koniecznie zapoznać się z wszystkimi instrukcjami, ostrzeżeniami, przestrogami i uwagami prawnymi. Należy zawsze postępować zgodnie z zaleceniami tam zawartymi.

Nota importante

Antes de utilizar o dispositivo, deverá proceder à leitura e compreensão de todos os avisos, precauções, instruções e isenções de responsabilidade legal e assegurar-se do seu cumprimento.

Важное примечание

До того, как пользоваться устройством, вам необходимо прочитать и понять все предупреждения, предостережения и юридические ограничения ответственности и следовать им.

Viktig information

Innan du använder enheten måste du läsa, förstå och följa alla anvisningar, varningar, försiktighetsåtgärder och ansvarsfriskrivningar.

Önemli not

Cihazı çalıştırmadan önce tüm talimatları, uyarıları, ikazları ve yasal açıklamaları okumalı, anlamalı ve bunlara uymalısınız.

重要注意事项

在操作设备之前,您必须阅读、理解并遵循所有说明、警告、注意事项和法律免责声明。

重要注意事項

操作裝置之前,您務必閱讀、了解並遵循所有說明、警告、注意事項與法律免責聲明。



User's manual FLIR T6xx series



	Discla	imers	
	1.1	Legal disclaimer	
	1.2	Usage statistics	1
	1.3	Changes to registry	1
	1.4	U.S. Government Regulations	1
	1.5	Copyright	
	1.6	Quality assurance	1
	1.7	Patents	1
	1.8	EULA Terms	1
	1.9	EULA Terms	2
2	Safety	information	3
3	Notice	to user7	
	3.1	User-to-user forums	7
	3.2	Calibration	7
	3.3	Accuracy	7
	3.4	Disposal of electronic waste	
	3.5	Training	7
	3.6	Documentation updates	
	3.7	Important note about this manual	
	3.8	Note about authoritative versions	
4	Custo	mer help	
-	4.1	General	
	4.2	Submitting a question	
	4.3	Downloads	
5	Quick	start guide	
•	5.1	Procedure	
6	•	accessories and services	
-			
7		about ergonomics	
	7.1	General	14
	7 0		
	7.2	Figure	. 14
8	Camer	Figurera parts	. 14 . 15
8		Figurera parts	. 14 . 15 . 15
8	Camer	Figure ra parts View from the right 8.1.1 Figure	. 14 . 15 . 15 . 15
8	Camer 8.1	Figure ra parts View from the right	. 14 . 15 . 15 . 15 . 15
8	Camer	Figure	. 14 . 15 . 15 . 15 . 15
8	Camer 8.1	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure	. 14 . 15 . 15 . 15 . 15 . 16
8	Camer 8.1	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation	. 14 . 15 . 15 . 15 . 16 . 16
8	Camer 8.1	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear	. 14 . 15 . 15 . 15 . 16 . 16 . 16
8	Camer 8.1	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure	. 14 . 15 . 15 . 15 . 16 . 16 . 16 . 17
8	Camer 8.1 8.2 8.3	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation	. 14 . 15 . 15 . 15 . 16 . 16 . 16 . 17
8	Camer 8.1	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17
8	Camer 8.1 8.2 8.3	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure	. 14 . 15 . 15 . 15 . 16 . 16 . 16 . 17 . 17 . 17
8	Camer 8.1 8.2 8.3 8.4	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure 8.4.2 Explanation	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17 . 18 . 18
8	Camer 8.1 8.2 8.3	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure 8.4.2 Explanation Battery condition LED indicator	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17 . 17 . 18 . 18
8	Camer 8.1 8.2 8.3 8.4	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure 8.4.2 Explanation Battery condition LED indicator 8.5.1 Figure	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17 . 17 . 18 . 18 . 18 . 19
8	Camer 8.1 8.2 8.3 8.4 8.5	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure 8.4.2 Explanation Battery condition LED indicator 8.5.1 Figure 8.5.2 Explanation	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17 . 18 . 18 . 19 . 19
8	Camer 8.1 8.2 8.3 8.4	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure 8.4.2 Explanation Battery condition LED indicator 8.5.1 Figure 8.5.2 Explanation Power LED indicator	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17 . 18 . 18 . 19 . 19
8	Camer 8.1 8.2 8.3 8.4 8.5	Figure ra parts View from the right 8.1.1 Figure 8.1.2 Explanation View from the left 8.2.1 Figure 8.2.2 Explanation View from the rear 8.3.1 Figure 8.3.2 Explanation View from the bottom 8.4.1 Figure 8.4.2 Explanation Battery condition LED indicator 8.5.1 Figure 8.5.2 Explanation	. 14 . 15 . 15 . 15 . 16 . 16 . 17 . 17 . 17 . 18 . 18 . 19 . 19 . 19

	8.7	Laser pointer	
		8.7.1 Figure	
		8.7.2 Laser warning label	20
		8.7.3 Laser rules and regulations	20
9	Screen	n elements	21
	9.1	Figure	21
	9.2	Explanation	21
10	Naviga	iting the menu system	22
	10.1	Figure	22
	10.2	Explanation	22
11	Pairing	Bluetooth devices	23
	11.1	General	23
	11.2	Procedure	23
12	Config	uring Wi-Fi	24
	12.1	General	
	12.2	Setting up a peer-to-peer connection (most common use)	24
	12.3	Connecting the camera to a wireless local area network (less	
		common use)	24
13	Handli	ng the camera	26
	13.1	Charging the battery	
		13.1.1 Using the power supply to charge the battery	26
		13.1.2 Using the stand-alone battery charger to charge the	
	10.0	battery	
	13.2	Turning on the camera	
	13.3	13.2.1 Procedure	
	13.3	13.3.1 Procedure	
	13.4	Adjusting the viewfinder's dioptric correction	
	10.4	13.4.1 Figure	
		13.4.2 Procedure	
	13.5	Adjusting the angle of the lens	
	10.0	13.5.1 Figure	
	13.6	Adjusting the infrared camera focus manually	
		13.6.1 Figure	
		13.6.2 Procedure	
	13.7	Autofocusing the infrared camera	29
		13.7.1 Figure	29
		13.7.2 Procedure	29
	13.8	Continuous autofocus	29
		13.8.1 General	29
		13.8.2 Procedure	
	13.9	Operating the laser pointer	
		13.9.1 Figure	
		13.9.2 Procedure	
	13.10	Using the digital zoom function	
		13.10.1 Figure	
		13.10.2 Procedure	
	13.11	Changing lenses	
	13.12	9 1	
		13.12.1 Procedure	33

	13.13	Changing the viewfinder eyecup	34
	13.14	Using the camera lamp as a flash	36
		13.14.1 General	36
		13.14.2 Procedure	36
14	Workin	ng with images:	37
	14.1	Saving an image	
		14.1.1 General	37
		14.1.2 About UltraMax	37
		14.1.3 Image capacity	37
		14.1.4 Naming convention	37
		14.1.5 Procedure	37
	14.2	Previewing an image	38
		14.2.1 General	38
		14.2.2 Procedure	38
	14.3	Opening a saved image	38
		14.3.1 General	38
		14.3.2 Procedure	
	14.4	Editing a saved image	38
		14.4.1 General	
		14.4.2 Procedure	
	14.5	Adjusting an infrared image	
		14.5.1 General	
		14.5.2 Example 1	
		14.5.3 Example 2	
		14.5.4 Procedure	
	14.6	Performing a non-uniformity correction (NUC)	
		14.6.1 What is a non-uniformity correction?	
		14.6.2 When to perform a non-uniformity correction?	
		14.6.3 Procedure	
	14.7	Changing the temperature range	
		14.7.1 General	
		14.7.2 Procedure	
	14.8	Hiding overlay graphics (programmable button)	
		14.8.1 General	
		14.8.2 Procedure	
	14.9	Changing the color palette	
		14.9.1 General	
		14.9.2 Procedure	
	14.10	Deleting an image	
		14.10.1 General	
		14.10.2 Procedure	
	14.11	Deleting all images	
		14.11.1 General	
		14.11.2 Procedure	
	14.12	Creating a PDF report in the camera	
		14.12.1 General	
		14.12.2 Naming convention	
		14.12.3 Procedure	
15	Workin	ng with image modes	
	15.1	General	44

	15.2	Image examples	. 44
	15.3	Selecting the image mode	. 45
16	Workir	ng with measurement tools	. 46
	16.1	General	
	16.2	Adding/removing measurement tools	
	16.3	Working with user presets	
		16.3.1 General	
		16.3.2 Procedure	. 46
	16.4	Resizing or moving a measurement tool	. 47
		16.4.1 General	. 47
		16.4.2 Procedure	. 47
	16.5	Changing object parameters	. 48
		16.5.1 General	. 48
		16.5.2 Types of parameters	. 48
		16.5.3 Recommended values	. 48
		16.5.4 Procedure	. 49
		16.5.5 Related topics	. 50
	16.6	Displaying values in the result table and displaying a graph	. 50
		16.6.1 General	. 50
		16.6.2 Procedure	. 50
	16.7	Creating and setting up a difference calculation	. 51
		16.7.1 General	. 51
		16.7.2 Procedure	. 51
	16.8	Setting a measurement alarm	. 51
		16.8.1 General	. 51
		16.8.2 Types of alarm	. 52
		16.8.3 Alarm signals	. 52
		16.8.4 Procedure	. 52
17	Fetchi	ng data from external FLIR meters	. 54
	17.1	General	. 54
	17.2	Supported FLIR meters	. 54
	17.3	Technical support for external meters	. 54
	17.4	Typical moisture measurement and documentation procedure	. 54
		17.4.1 General	
		17.4.2 Procedure	. 55
	17.5	More information	. 55
18	Workir	ng with color alarms and isotherms	. 56
	18.1	Color alarms	
		18.1.1 General	
		18.1.2 Image examples	. 56
	18.2	Setting up above, below, and interval alarms	
	18.3	Building isotherms	
		18.3.1 About the Condensation alarm	
		18.3.2 About the Insulation alarm	
		18.3.3 Setting up condensation and insulation alarms	. 58
19	Annota	ating images	
. •	19.1	General	
	19.1	Adding a note	
	10.2	19.2.1 General	
		19.2.2 Procedure	
		10.2.2 1 1000dulo	. აა

	19.3	Adding a table60
		19.3.1 General60
		19.3.2 Procedure
	19.4	Adding a voice annotation60
		19.4.1 General60
		19.4.2 Procedure
	19.5	Adding a sketch61
		19.5.1 General61
		19.5.2 Procedure
20	Progra	amming the camera (time lapse)62
	20.1	General
	20.2	Procedure62
21	Recor	ding video clips63
	21.1	General
	21.2	Procedure63
22	Scree	ning alarm64
	22.1	General
	22.2	Procedure64
23	Chano	ging settings65
	23.1	General65
		23.1.1 Define user presets
		23.1.2 <i>Save options</i>
		23.1.3 Programmable button
		23.1.4 Reset options
		23.1.5 Device settings
	23.2	Procedure
24	Techn	ical data67
	24.1	Online field-of-view calculator
	24.2	Note about technical data
	24.3	Note about authoritative versions
	24.4	FLIR T600 15° (incl. Wi-Fi and Ext. cal.)
	24.5	FLIR T600 15° (incl. Wi-Fi)
	24.6	FLIR T600 25° (incl. Wi-Fi and Ext. cal.)
	24.7	FLIR T600 25° (incl. Wi-Fi)87
	24.8	FLIR T600 25° and 15° w/case
	24.9	FLIR T600 25° and 45° w/case99
	24.10	FLIR T600 45° (incl. Wi-Fi and Ext. cal.)
	24.11	FLIR T600 45° (incl. Wi-Fi)
	24.12	FLIR T600bx 25° (incl. Wi-Fi and Ext. cal.)
	24.13	FLIR T600bx 25° (incl. Wi-Fi)
	24.14	FLIR T600bx 45° (incl. Wi-Fi and Ext. cal.)
	24.15	FLIR T600bx 45° (incl. Wi-Fi)
	24.16	FLIR T610 15° (incl. Wi-Fi)
	24.17	FLIR T610 25° (incl. Wi-Fi)
	24.18	FLIR T610 45° (incl. Wi-Fi)
	24.19	FLIR T620 15° (incl. Wi-Fi and Ext. cal.)
	24.20	FLIR T620 15° (incl. Wi-Fi)
	24.21	FLIR T620 25° (incl. Wi-Fi and Ext. cal.)
	24.22	FLIR T620 25° (incl. Wi-Fi)
	24.23	FLIR T620 25° and 15° (incl. Wi-Fi)

24.24	FLIR T620 25° and 45° (incl. Wi-Fi)	189
24.25	FLIR T620 45° (incl. Wi-Fi and Ext. cal.)	
24.26	FLIR T620 45° (incl. Wi-Fi)	
24.27	FLIR T620bx 15° (incl. Wi-Fi and Ext. cal.)	
24.28	FLIR T620bx 15° (incl. Wi-Fi)	
24.29	FLIR T620bx 25° (incl. Wi-Fi and Ext. cal.)	
24.30	FLIR T620bx 25° (incl. Wi-Fi)	
24.31	FLIR T620bx 45° (incl. Wi-Fi and Ext. cal.)	
24.32	FLIR T620bx 45° (incl. Wi-Fi)	
24.33	FLIR T630 15° (incl. Wi-Fi)	
24.34	FLIR T630 25° (incl. Wi-Fi)	
24.35	FLIR T630 45° (incl. Wi-Fi)	
24.36	FLIR T630sc 15° (incl. Wi-Fi)	
24.37	FLIR T630sc 25° (incl. Wi-Fi)	
24.38	FLIR T630sc 25° and 45° w/case	
24.39	FLIR T630sc 45° (incl. Wi-Fi)	
24.40	FLIR T640 15° (incl. Wi-Fi and Ext. cal.)	
24.41	FLIR T640 15° (incl. Wi-Fi)	
24.42	FLIR T640 25° (incl. Wi-Fi and Ext. cal.)	
24.43	FLIR T640 25° (incl. Wi-Fi)	
24.44	FLIR T640 25° and 15° (incl. Wi-Fi)	
24.45	FLIR T640 25° and 45° (incl. Wi-Fi)	
24.46	FLIR T640 45° (incl. Wi-Fi and Ext. cal.)	
24.47	FLIR T640 45° (incl. Wi-Fi)	
24.48	FLIR T640bx 15° (incl. Wi-Fi and Ext. cal.)	
24.49	FLIR T640bx 15° (incl. Wi-Fi)	
24.50	FLIR T640bx 25° (incl. Wi-Fi and Ext. cal.)	
24.51	FLIR T640bx 25° (incl. Wi-Fi)	359
24.52	FLIR T640bx 45° (incl. Wi-Fi and Ext. cal.)	366
24.53	FLIR T640bx 45° (incl. Wi-Fi)	373
24.54	FLIR T650sc 15° (incl. Wi-Fi)	380
24.55	FLIR T650sc 25° (incl. Wi-Fi)	387
24.56	FLIR T650sc 25° and 15° w/case	394
24.57	FLIR T650sc 25° and 45° w/case	401
24.58	FLIR T650sc 45° (incl. Wi-Fi)	408
24.59	FLIR T660 15° (incl. Wi-Fi and Ext. cal.)	415
24.60	FLIR T660 15° (incl. Wi-Fi)	422
24.61	FLIR T660 25° (incl. Wi-Fi and Ext. cal.)	429
	FLIR T660 25° (incl. Wi-Fi)	
24.63	FLIR T660 25° and 15° w/case	443
24.64	FLIR T660 25° and 45° w/case	450
24.65	FLIR T660 45° (incl. Wi-Fi and Ext. cal.)	
24.66	FLIR T660 45° (incl. Wi-Fi)	464
Mecha	nical drawings	471
CE Dec	claration of conformity	481
	ng the camera	
27.1	Camera housing, cables, and other items	
<i>⊆ι</i> .Ι	27.1.1 Liquids	
	27.1.1 Equipment	
	27.1.3 Procedure	
	E1.1.0 1 1000UUIO	TUL

25 26 27

	27.2	Infrared lens	. 483
		27.2.1 Liquids	. 483
		27.2.2 Equipment	. 483
		27.2.3 Procedure	. 483
	27.3	Infrared detector	. 484
		27.3.1 General	. 484
		27.3.2 Procedure	. 484
28	Applic	eation examples	. 485
	28.1	Moisture & water damage	
		28.1.1 General	
		28.1.2 Figure	
	28.2	Faulty contact in socket	
		28.2.1 General	
		28.2.2 Figure	
	28.3	Oxidized socket	
		28.3.1 General	
		28.3.2 Figure	
	28.4	Insulation deficiencies	
		28.4.1 General	
		28.4.2 Figure	. 487
	28.5	Draft	
		28.5.1 General	
		28.5.2 Figure	. 488
29	About	FLIR Systems	
	29.1	More than just an infrared camera	
	29.2	Sharing our knowledge	
	29.3	Supporting our customers	
30		, laws, and definitions	
		nographic measurement techniques	
31	31.1	Introduction	
	31.1		
	31.2	Emissivity	
	01.0	31.2.1 Finding the emissivity of a sample	
	31.3	Reflected apparent temperature	
	31.4	Distance	
	31.5 31.6	Relative humidity	
		Other parameters	
32	Histor	y of infrared technology	. 500
33	Theor	y of thermography	
	33.1	Introduction	
	33.2	The electromagnetic spectrum	
	33.3	Blackbody radiation	
		33.3.1 Planck's law	
		33.3.2 Wien's displacement law	. 506
		33.3.3 Stefan-Boltzmann's law	
		33.3.4 Non-blackbody emitters	
	33.4	Infrared semi-transparent materials	. 510
34	The m	easurement formula	. 511
35	Emiss	ivity tables	. 515
		References	515

35.2	Tahles		5-	5

Disclaimers

1.1 Legal disclaimer

All products manufactured by FLIR Systems are warranted against defective materials and workmanship for a period of one (1) year from the delivery date of the original purchase, provided such products have been under normal storage, use and service, and in accordance with FLIR Systems instruction.

Uncooled handheld infrared cameras manufactured by FLIR Systems are warranted against defective materials and workmanship for a period of two (2) years from the delivery date of the original purchase, provided such products have been under normal storage, use and service, and in accordance with FLIR Systems instruction, and provided that the camera has been registered within 60 days of original purchase.

Detectors for uncooled handheld infrared cameras manufactured by FLIR Sys tems are warranted against defective materials and workmanship for a period of ten (10) years from the delivery date of the original purchase, provided such products have been under normal storage, use and service, and in accordance with FLIR Systems instruction, and provided that the camera has been registered within 60 days of original purchase.

Products which are not manufactured by FLIR Systems but included in systems delivered by FLIR Systems to the original purchaser, carry the warranty, i any, of the particular supplier only. FLIR Systems has no responsibility whatsoever for such products.

The warranty extends only to the original purchaser and is not transferable. It is not applicable to any product which has been subjected to misuse, neglect, accident or abnormal conditions of operation. Expendable parts are excluded from the warranty.

In the case of a defect in a product covered by this warranty the product must not be further used in order to prevent additional damage. The purchaser shall promptly report any defect to FLIR Systems or this warranty will not apply.

FLIR Systems will, at its option, repair or replace any such defective product free of charge if, upon inspection, it proves to be defective in material or work-manship and provided that it is returned to FLIR Systems within the said one-

FLIR Systems has no other obligation or liability for defects than those set forth

No other warranty is expressed or implied. FLIR Systems specifically disclaims the implied warranties of merchantability and fitness for a particular purpose.

FLIR Systems shall not be liable for any direct, indirect, special, incidental or consequential loss or damage, whether based on contract, tort or any other le-

This warranty shall be governed by Swedish law

Any dispute, controversy or claim arising out of or in connection with this warranty, shall be finally settled by arbitration in accordance with the Rules of the Arbitration Institute of the Stockholm Chamber of Commerce. The place of an bitration shall be Stockholm. The language to be used in the arbitral proceedings shall be English.

1.2 Usage statistics

FLIR Systems reserves the right to gather anonymous usage statistics to help maintain and improve the quality of our software and services

1.3 Changes to registry

The registry entry HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet \ControlLsa\LmCompatibilityLevel will be automatically changed to level 2 if the FLIR Camera Monitor service detects a FLIR camera connected to the computer with a USB cable. The modification will only be executed if the camera device implements a remote network service that supports network logons.

1.4 U.S. Government Regulations

This product may be subject to U.S. Export Regulations. Please send any inquiries to exportquestions@flir.com

1.5 Copyright

© 2016, FLIR Systems, Inc. All rights reserved worldwide. No parts of the software including source code may be reproduced, transmitted, transcribed or translated into any language or computer language in any form or by any means, electronic, magnetic, optical, manual or otherwise, without the prior written permission of FLIR Systems.

The documentation must not, in whole or part, be copied, photocopied, reproduced, translated or transmitted to any electronic medium or machine readable form without prior consent, in writing, from FLIR Systems.

Names and marks appearing on the products herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

1.6 Quality assurance

The Quality Management System under which these products are developed and manufactured has been certified in accordance with the ISO 9001

FLIR Systems is committed to a policy of continuous development; therefore we reserve the right to make changes and improvements on any of the products without prior notice.

1.7 Patents

 $000439161; 000653423; 000726344; 000859020; 001707738; 001707746; \\001707787; 001776519; 001954074; 002021543; 002021543-0002;$ 002058180; 002249953; 002531178; 002816795; 002816795; 011200326; 014347553; 057692; 061609; 0702405; 100414275; 101796816; 011796817; 101796818; 102334141; 1062100; 11063060001; 11517895; 1226865; 12300216; 12300224; 1285345; 1299699; 1325808; 1336775; 1391114; 1402918; 1404291; 1411581; 1415075; 1421497; 1458284; 1678485; 1732314; 17399650; 1880950; 1886650; 2007301511414; 2007303395047; 2008301285812; 2009301900619; 20100060357; 2010301761271; 2010301761303; 2010301761572; 2010305959313; 2011304423549; 2012304717443; 2012306207318; 2013302676195; 2015202354035; 2015304259171; 204465713; 204967995; 2106017; 2107799; 2115696; 2172004; 2315433; 2381417; 2794760001; 3006596; 3006597: 303330211: 4358936: 483782: 484155: 4889913: 4937897 4995790001; 5177595; 540838; 579475; 584755; 599392; 60122153; 6020040116815; 602006006500.0; 6020080347796; 6020110003453 615113; 615116; 664580; 664581; 665004; 665440; 67023029; 6707044; 677298; 68657; 69036179; 70022216; 70028915; 70028923; 70057990; 7034300; 710424; 7110035; 7154093; 7157705; 718801; 723605; 7237946; 7312822; 7332716; 7336823; 734803; 7544944; 7606484; 7634157; 7667198; 7809258; 7826736; 8018649; 8153971; 8212210; 8289372; 8340414; 8354639; 8384783; 8520970; 8565547; 8595689; 8599262; 8654239; 8680466; 8803093; 8823803; 8853631; 8933403; 9171361; 9191583; 9279728; 9280812; 9338352; 9423940; 9471970; 9595087;

1.8 EULA Terms

- You have acquired a device ("INFRARED CAMERA") that includes software licensed by FLIR Systems AB from Microsoft Licensing, GP or its af-filiates ("MS"). Those installed software products of MS origin, as well as associated media, printed materials, and "online" or electronic documentation ("SOFTWARE") are protected by international intellectual property laws and treaties. The SOFTWARE is licensed, not sold. All rights reserved.
- IF YOU DO NOT AGREE TO THIS END USER LICENSE AGREEMENT ("EULA"), DO NOT USE THE DEVICE OR COPY THE SOFTWARE. IN-STEAD, PROMPTLY CONTACT FLIR Systems AB FOR INSTRUCTIONS ON RETURN OF THE UNUSED DEVICE(S) FOR A REFUND. ANY USE OF THE SOFTWARE, INCLUDING BUT NOT LIMITED TO USE ON THE DEVICE, WILL CONSTITUTE YOUR AGREEMENT TO THIS EU-LA (OR RATIFICATION OF ANY PREVIOUS CONSENT).
 GRANT OF SOFTWARE LICENSE. This EULA grants you the following
- - You may use the SOFTWARE only on the DEVICE.

 NOT FAULT TOLERANT. THE SOFTWARE IS NOT FAULT TOLERANT. FLIR Systems AB HAS INDEPENDENTLY DETERMINED
 HOW TO USE THE SOFTWARE IN THE DEVICE, AND MS HAS RELIED UPON FLIR Systems AB TO CONDUCT SUFFICIENT TESTING TO DETERMINE THAT THE SOFTWARE IS SUITABLE FOR SUCH USE.
 - NO WARRANTIES FOR THE SOFTWARE. THE SOFTWARE IS NO WARHANI LES FOR THE SOFT WARE. THE SOFT WARLE IS provided "AS IS" and with all faults. THE ENTIRE RISK AS TO SATISFACTORY QUALITY, PERFORMANCE, ACCURACY, AND EFFORT (INCLUDING LACK OF NEGLIGENCE) IS WITH YOU. ALSO, THERE IS NO WARRANTY AGAINST INTERFERENCE WITH YOUR ENJOYMENT OF THE SOFTWARE OR AGAINST IN-FRINCEMENT. IF YOU HAVE RECEIVED ANY WARRANTIES REGARDING THE DEVICE OR THE SOFTWARE, THOSE WARRANTIES DO NOT ORIGINATE FEROM, AND ASE NOT WARRANTIES DO NOT ORIGINATE FROM, AND ARE NOT
 - WARRANTIES DO NOT ORIGINATE FROM, AND ARE NOT BINDING ON, MS.

 No Liability for Certain Damages. EXCEPT AS PROHIBITED BY LAW, MS SHALL HAVE NO LIABILITY FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE SOFTWARE. THIS LIMITATION SHALL APPLY EVEN IF ANY REMEDY FAILS OF ITS ESSENTIAL PURPOSE. IN NO EVENT ENAUL MS EVENT BE LADIL E GOD ANY AMOUNT IN EXP. NO EVENT SHALL MS BE LIABLE FOR ANY AMOUNT IN EX-CESS OF U.S. TWO HUNDRED FIFTY DOLLARS (U.S. 2250.00). Limitations on Reverse Engineering, Decompilation, and Dis-assembly. You may not reverse engineer, decompile, or disassem-
 - ble the SOFTWARE, except and only to the extent that such activity is expressly permitted by applicable law notwithstanding this
 - SOFTWARE TRANSFER ALLOWED BUT WITH RESTRICTIONS. SOFTWARE THANSFER ALLOWED BUT WITH RESTRICTIONS. You may permanently transfer rights under this EULA nily as part of a permanent sale or transfer of the Device, and only if the recipient agrees to this EULA. If the SOFTWARE is an upgrade, any transfer must also include all prior versions of the SOFTWARE.

 EXPORT RESTRICTIONS. You acknowledge that SOFTWARE is subject to U.S. export jurisdiction. You agree to comply with all applicable integrational and exited laws that show the SOFTWARE.
 - cable international and national laws that apply to the SOFTWARE, including the U.S. Export Administration Regulations, as well as end-user, end-use and destination restrictions issued by U.S. and other governments. For additional information see http://www.microsoft.com/exporting/.

1.9 EULA Terms

Qt4 Core and Qt4 GUI, Copyright ©2013 Nokia Corporation and FLIR Systems AB. This Qt library is a free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version. This library is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MER-CHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License, http://www.gnu.org/licenses/lgpl-2.1.html. The source code for the libraries Qt4 Core and Qt4 GUI may be requested from FLIR Systems AB.

Safety information



WARNING

Applicability: Class B digital devices.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- · Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



WARNING

Applicability: Digital devices subject to 15.19/RSS-247.

NOTICE: This device complies with Part 15 of the FCC Rules and with RSS-247 of Industry Canada. Operation is subject to the following two conditions:

- 1. this device may not cause harmful interference, and
- this device must accept any interference received, including interference that may cause undesired operation.



WARNING

Applicability: Digital devices subject to 15.21.

NOTICE: Changes or modifications made to this equipment not expressly approved by FLIR Systems may void the FCC authorization to operate this equipment.



WARNING

Applicability: Devices subject to RSS-102/47CFR2.1093.

This device has been tested and meets the FCC/ISED RF exposure guidelines, or the device is exempted from SAR because of the low output power. Nevertheless, the device should be used in such a manner that the potential for human contact during normal operation is minimized.



WARNING

Applicability: Cameras with one or more laser pointers.

Do not look directly into the laser beam. The laser beam can cause eye irritation.



WARNING

Applicability: Cameras with one or more batteries.

Do not disassemble or do a modification to the battery. The battery contains safety and protection devices which, if damage occurs, can cause the battery to become hot, or cause an explosion or an ignition.



WARNING

Applicability: Cameras with one or more batteries.

If there is a leak from the battery and you get the fluid in your eyes, do not rub your eyes. Flush well with water and immediately get medical care. The battery fluid can cause injury to your eyes if you do not do this



WARNING

Applicability: Cameras with one or more batteries.

Do not continue to charge the battery if it does not become charged in the specified charging time. If you continue to charge the battery, it can become hot and cause an explosion or ignition. Injury to persons can occur.



WARNING

Applicability: Cameras with one or more batteries.

Only use the correct equipment to remove the electrical power from the battery. If you do not use the correct equipment, you can decrease the performance or the life cycle of the battery. If you do not use the correct equipment, an incorrect flow of current to the battery can occur. This can cause the battery to become hot, or cause an explosion. Injury to persons can occur.



WARNING

Make sure that you read all applicable MSDS (Material Safety Data Sheets) and warning labels on containers before you use a liquid. The liquids can be dangerous. Injury to persons can occur.



CAUTION

Do not point the infrared camera (with or without the lens cover) at strong energy sources, for example, devices that cause laser radiation, or the sun. This can have an unwanted effect on the accuracy of the camera. It can also cause damage to the detector in the camera.



CAUTION

Do not use the camera in temperatures more than +50°C (+122°F), unless other information is specified in the user documentation or technical data. High temperatures can cause damage to the camera.



CAUTION

Applicability: Cameras with one or more laser pointers.

To prevent damage, put the protective cap on the laser pointer when you do not operate the laser pointer. Damage to the laser pointer can occur if you do not do this.



CAUTION

Applicability: Cameras with one or more batteries.

Do not attach the batteries directly to a car's cigarette lighter socket, unless FLIR Systems supplies a specific adapter to connect the batteries to a cigarette lighter socket. Damage to the batteries can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not connect the positive terminal and the negative terminal of the battery to each other with a metal object (such as wire). Damage to the batteries can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not get water or salt water on the battery, or permit the battery to become wet. Damage to the batteries can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not make holes in the battery with objects. Damage to the battery can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not hit the battery with a hammer. Damage to the battery can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not put your foot on the battery, hit it or cause shocks to it. Damage to the battery can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not put the batteries in or near a fire, or into direct sunlight. When the battery becomes hot, the built-in safety equipment becomes energized and can stop the battery charging procedure. If the battery becomes hot, damage can occur to the safety equipment and this can cause more heat, damage or ignition of the battery.



CAUTION

Applicability: Cameras with one or more batteries.

Do not put the battery on a fire or increase the temperature of the battery with heat. Damage to the battery and injury to persons can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not put the battery on or near fires, stoves, or other high-temperature locations. Damage to the battery and injury to persons can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not solder directly onto the battery. Damage to the battery can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Do not use the battery if, when you use, charge, or put the battery in storage, there is an unusual smell from the battery, the battery feels hot, changes color, changes shape, or is in an unusual condition. Speak with your sales office if one or more of these problems occurs. Damage to the battery and injury to persons can occur.



CAUTION

Applicability: Cameras with one or more batteries.

Only use a specified battery charger when you charge the battery. Damage to the battery can occur if you do not do this.



CAUTION

Applicability: Cameras with one or more batteries.

Only use a specified battery for the camera. Damage to the camera and the battery can occur if you do not do this.



CAUTION

Applicability: Cameras with one or more batteries.

The temperature range through which you can charge the battery is 0°C to +45°C (+32°F to +113°F). If you charge the battery at temperatures out of this range, it can cause the battery to become hot or to break. It can also decrease the performance or the life cycle of the battery.



CAUTION

Applicability: Cameras with one or more batteries.

The temperature range through which you can remove the electrical power from the battery is -15° C to $+50^{\circ}$ C ($+5^{\circ}$ F to $+122^{\circ}$ F), unless other information is specified in the user documentation or technical data. If you operate the battery out of this temperature range, it can decrease the performance or the life cycle of the battery.



CAUTION

Applicability: Cameras with one or more batteries.

When the battery is worn, apply insulation to the terminals with adhesive tape or equivalent materials before you discard it. Damage to the battery and injury to persons can occur if you do not do this.



CAUTION

Applicability: Cameras with one or more batteries.

Remove any water or moisture on the battery before you install it. Damage to the battery can occur if you do not do this.



CAUTION

Do not apply solvents or equivalent liquids to the camera, the cables, or other items. Damage to the battery and injury to persons can occur.



CAUTION

Be careful when you clean the infrared lens. The lens has an anti-reflective coating which is easily damaged. Damage to the infrared lens can occur.



CAUTION

Do not use too much force to clean the infrared lens. This can cause damage to the anti-reflective coating.

Note The encapsulation rating is only applicable when all the openings on the camera are sealed with their correct covers, hatches, or caps. This includes the compartments for data storage, batteries, and connectors.



CAUTION

Applicability: Cameras with a viewfinder.

Make sure that the beams from the intensive energy sources do not go into the viewfinder. The beams can cause damage to the camera. This includes the devices that emit laser radiation, or the sun.

Notice to user

3.1 User-to-user forums

Exchange ideas, problems, and infrared solutions with fellow thermographers around the world in our user-to-user forums. To go to the forums, visit:

http://forum.infraredtraining.com/

3.2 Calibration

We recommend that you send in the camera for calibration once a year. Contact your local sales office for instructions on where to send the camera.

3.3 Accuracy

For very accurate results, we recommend that you wait 5 minutes after you have started the camera before measuring a temperature.

3.4 Disposal of electronic waste

Electrical and electronic equipment (EEE) contains materials, components and substances that may be hazardous and present a risk to human health and the environment when waste electrical and electronic equipment (WEEE) is not handled correctly.

Equipment marked with the below crossed-out wheeled bin is electrical and electronic equipment. The crossed-out wheeled bin symbol indicates that waste electrical and electronic equipment should not be discarded together with unseparated household waste, but must be collected separately.

For this purpose all local authorities have established collection schemes under which residents can dispose waste electrical and electronic equipment at a recycling centre or other collection points, or WEEE will be collected directly from households. More detailed information is available from the technical administration of the relevant local authority.



3.5 Training

To read about infrared training, visit:

- http://www.infraredtraining.com
- http://www.irtraining.com
- · http://www.irtraining.eu

3.6 Documentation updates

Our manuals are updated several times per year, and we also issue product-critical notifications of changes on a regular basis.

To access the latest manuals, translations of manuals, and notifications, go to the Download tab at:

http://support.flir.com

It only takes a few minutes to register online. In the download area you will also find the latest releases of manuals for our other products, as well as manuals for our historical and obsolete products.

3.7 Important note about this manual

FLIR Systems issues generic manuals that cover several cameras within a model line.

This means that this manual may contain descriptions and explanations that do not apply to your particular camera model.


3.8 Note about authoritative versions

The authoritative version of this publication is English. In the event of divergences due to translation errors, the English text has precedence.

Any late changes are first implemented in English.

4

Customer help



4.1 General

For customer help, visit:

http://support.flir.com

4.2 Submitting a question

To submit a question to the customer help team, you must be a registered user. It only takes a few minutes to register online. If you only want to search the knowledgebase for existing questions and answers, you do not need to be a registered user.

When you want to submit a question, make sure that you have the following information to hand:

- · The camera model
- The camera serial number
- The communication protocol, or method, between the camera and your device (for example, SD card reader, HDMI, Ethernet, USB, or FireWire)
- Device type (PC/Mac/iPhone/iPad/Android device, etc.)
- · Version of any programs from FLIR Systems
- Full name, publication number, and revision number of the manual

4.3 Downloads

On the customer help site you can also download the following, when applicable for the product:

- Firmware updates for your infrared camera.
- Program updates for your PC/Mac software.
- Freeware and evaluation versions of PC/Mac software.
- User documentation for current, obsolete, and historical products.
- Mechanical drawings (in *.dxf and *.pdf format).
- Cad data models (in *.stp format).
- · Application stories.
- · Technical datasheets.
- · Product catalogs.

5

Quick start guide

5.1 Procedure

Follow this procedure:

- 1. Put a battery into the battery compartment.
- 2. Charge the battery for 4 hours before starting the camera for the first time.
- 3. Insert a memory card into the card slot.
- 4. Push the On/off button ① to turn on the camera.
- 5. Aim the camera toward the object of interest.
- 6. Adjust the focus.

Note It is very important to adjust the focus correctly. Incorrect focus adjustment affects how the image modes work. It also affects the temperature measurement.

- 7. Push the Autofocus/save button fully down to save an image.
- 8. Go to http://support.flir.com/tools and download FLIR Tools.
- 9. Install FLIR Tools on your computer.
- 10. Start FLIR Tools.
- 11. Connect the camera to the computer using a USB cable.
- 12. Import the images into FLIR Tools.
- 13. Select one or more images.
- 14. Click Generate report.
- 15. Click Export to export the report as a PDF file.
- 16. Send the PDF report to your client.

6

List of accessories and services

Product name	Part number
Battery charger, incl. power supply with multi plugs T6xx	T198126
Bluetooth Headset	T197771ACC
Calibration including General maintenance T6xx series	T199838
Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.	T198509
Close-up IR lens, 1.5× (25 μm) with case	T198066
Close-up IR lens, 2.9× (50 μm) with case	T198059
Close-up IR lens, 5.8× (100 μm) with case	T198060
FLIR Reporter Professional (license only)	T198586
FLIR ResearchIR 3 (license only)	T198578
FLIR ResearchIR 3 Max (license only)	T198574
FLIR ResearchIR Max + HSDR 4	T198697
FLIR ResearchIR Max 4	T198696
FLIR ResearchIR Standard 4	T198731
FLIR Tools	T198584
FLIR Tools+ (license only)	T198583
Hard transport case for T6xx series	T198625ACC
HDMI type C to DVI cable 1.5 m	T910930ACC
HDMI type C to HDMI type A cable 1.5 m	T910891ACC
High temp option +300°C to 2000°C (+572°F to 3632°F) for FLIR A6xxsc and T6xx	T197896
IR lens, f=13.1 mm (45°) with case	T197915
IR lens, f=24.6 mm (25°) with case	T197922
IR lens, f=41.3 mm (15°) with case	T197914
IR lens, f=6.5 mm (80°) with case	T198065
IR lens, f=88.9 mm (7°) with case and support for T6xx	T198166
IR Window 2 in	19250-100
IR Window 3 in.	19251-100
IR Window 4 in.	19252-100
Large eyecup	T198497
Li-lon Battery pack 3.7V 29Wh	T198506
Memory card SDHC 4 GB	T911230ACC
Neck strap	T198499
One year extended warranty for T6xx series	T199836
Pouch for FLIR T6xx and T4xx series	T198495
Power supply, incl. multi plugs	T910814
SS IR Window 2 in.	19250-200
SS IR Window 3 in.	19251-200
SS IR Window 4 in.	19252-200
Tool belt	T911093

Product name	Part number	
Tripod Adapter	T198498	
USB cable Std A <-> Mini-B	1910423	

Note FLIR Systems reserves the right to discontinue models, parts or accessories, and other items, or to change specifications at any time without prior notice.

A note about ergonomics


7.1 General

To prevent strain-related injuries, it is important that you hold the camera ergonomically correct. This section gives advice and examples on how to hold the camera.

Note Please note the following:

- Always tilt the touch-screen LCD to suit your work position.
- When you hold the camera, make sure that you support the optics housing with your left hand too. This decreases the strain on your right hand.


7.2 Figure



Camera parts

8.1 View from the right

8.1.1 Figure




8.1.2 Explanation

- 1. Knob to change the dioptric correction for the viewfinder.
 - Note This item is dependent on the camera model.
- 2. Hand strap.
- 3. Digital zoom button.
- 4. Autofocus button (push half-way down)/Save button (push fully down).

8.2 View from the left

8.2.1 Figure



8.2.2 Explanation


- 1. Camera lamp.
- 2. Laser pointer.

Note The laser pointer may not be enabled in all markets.

- 3. Camera lamp.
- 4. Infrared lens.
- 5. Digital camera.
- 6. Focusing ring.
- 7. Button to operate the laser pointer.

8.3 View from the rear

8.3.1 Figure



8.3.2 Explanation

- 1. Sensor that adjusts the touch-screen LCD intensity automatically.
- 2. Button to switch between touch-screen LCD mode and viewfinder mode.

Note This item is dependent on the camera model.


3. Viewfinder.

Note This item is dependent on the camera model.

- 4. Programmable button.
- 5. Joystick with push-button functionality.
- 6. Back button.
- 7. Camera lamp button.
- 8. Button to switch between automatic and manual image adjustment mode.
- 9. Image archive button.
- 10. Touch-screen LCD.
- 11. Power indicator.
- 12. On/off button.

8.4 View from the bottom

8.4.1 Figure



8.4.2 Explanation


- 1. Memory card.
- 2. Indicator showing that the memory card is busy.

Note

- Do not eject the memory card when this LED is flashing.
- Do not connect the camera to a computer when this LED is flashing.
- 3. USB Mini-B cable (to connect the camera to a computer).
- 4. HDMI cable (for digital video output).
- 5. Battery condition LED indicator.
- 6. Power cable (to power the camera and charge the battery).
- 7. USB-A cable (to connect an external USB device to the camera).
- 8. Tripod mount. Requires an adapter (included).
- 9. Latch to release the battery.

8.5 Battery condition LED indicator

8.5.1 Figure




8.5.2 Explanation

Type of signal	Explanation	
The green LED flashes twice per second.	The battery is being charged.	
The green LED glows continuously.	The battery is fully charged.	

8.6 Power LED indicator

8.6.1 Figure



8.6.2 Explanation

Type of signal	Explanation	
The LED is off.	The camera is off.	
The LED is blue.	The camera is on.	

8.7 Laser pointer

8.7.1 Figure





Figure 8.1 This figure shows the difference in position between the laser pointer and the optical center of the infrared lens.



Note The symbol is displayed on the screen when the laser pointer is on.

Note The laser pointer is enabled by a setting. Select (Settings) > Device settings > Set up camera > Lamp & laser > Enable lamp & laser.

Note The laser pointer may not be enabled in all markets.

8.7.2 Laser warning label

A laser warning label with the following information is attached to the camera:




8.7.3 Laser rules and regulations

Wavelength: 635 nm. Maximum output power: 1 mW.

This product complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.

Screen elements

9.1 Figure




9.2 Explanation

- 1. Measurement toolbar.
- 2. Measurement tool (e.g., spotmeter).
- 3. Zoom factor.
- 4. Result table.
- 5. Status icons.
- 6. Temperature scale.
- 7. Settings toolbar button.
- 8. Color toolbar button.
- 9. Measurement toolbar button.
- 10. Image mode toolbar button.
- 11. Measurement parameters toolbar button.
- 12. Recording mode toolbar button.

Navigating the menu system

10.1 Figure



10.2 Explanation

The figure above shows the two ways to navigate the menu system in the camera:

- Using the index finger or a stylus pen specially designed for capacitive touch usage to navigate the menu system (left).
- Using the joystick to navigate the menu system (right).

You can also use a combination of the two.

In this manual it is assumed that the joystick is used, but most tasks can also be carried out using the index finger or a stylus pen.

Pairing Bluetooth devices

11.1 General

Before you can use a Bluetooth device with the camera, you need to pair the devices.

11.2 Procedure

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Device settings and push the joystick.
- 5. Select Bluetooth including METERLiNK and push the joystick.
- 6. If the Bluetooth check box is unchecked, push the joystick to activate Bluetooth.
 - Note You also need to activate Bluetooth connectivity on the external device.
- 7. Select Scan for Bluetooth devices and push the joystick.
- 8. Wait until a list of available devices is displayed. This will take about 15 seconds.
- 9. When a Bluetooth device is found, select the device to add it, and begin the pairing procedure. The device is then ready to be used.

Note

- Only METERLiNK devices and Bluetooth-enabled headsets will appear in the list of available devices.
- · You can add several devices.
- You can remove a device by selecting the device and then selecting Unpair device.
- After adding a METERLINK device, such as the FLIR MR77 or FLIR DM93, the result from the meter will be visible in the result table and stored with the images. For more information, see section 17 Fetching data from external FLIR meters, page 54.
- After adding a Bluetooth-enabled headset, it is ready to be used for adding voice annotations.

Configuring Wi-Fi

12.1 General

Depending on your camera configuration, you can connect the camera to a wireless local area network (WLAN) using Wi-Fi, or let the camera provide Wi-Fi access to another device.

You can connect the camera in two different ways:

- Most common use: Setting up a peer-to-peer connection (also called an ad hoc or P2P connection). This method is primarily used with other devices, e.g., an iPhone or iPad.
- Less common use: Connecting the camera to a WLAN.

12.2 Setting up a peer-to-peer connection (most common use)

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Device settings and push the joystick.
- 5. Select Wi-Fi and push the joystick.
- 6. Select Share and push the joystick.
- (Optional step.) To display and change the parameters, select Settings and push the joystick.
 - To change the channel (the channel that the camera is broadcasting on), select *Channel* and push the joystick.
 - To activate WEP (encryption algorithm), select WEP and push the joystick. This will check the WEP check box.
 - To change the WEP password, select Password and push the joystick.

Note These parameters are set for your camera's network. They will be used by the external device to connect that device to the network.

12.3 Connecting the camera to a wireless local area network (less common use)

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Device settings and push the joystick.
- 5. Select Wi-Fi and push the joystick.
- 6. Select Connect to network and push the joystick.
- 7. To display a list of the available networks, select *Networks* and push the joystick.
- Select one of the available networks.
 Password-protected networks are indicated with a padlock icon, and for these you will need to enter a password.

Note Some networks do not broadcast their existence. To connect to such a network, select *Settings* from the *Networks* list and push the joystick. Then select *Add network...* and set all parameters manually according to that network.

Handling the camera

13.1 Charging the battery

Note You must charge the battery for 4 hours before you start using the camera for the first time.

13.1.1 Using the power supply to charge the battery

13.1.1.1 Procedure

Follow this procedure:

- 1. Connect the power supply cable plug to the power connector on the camera.
- 2. Connect the power supply mains-electricity plug to a mains socket.
- Disconnect the power supply cable plug when the green light of the battery condition LED indicator is continuous.

13.1.2 Using the stand-alone battery charger to charge the battery

13.1.2.1 Explanation

Type of signal	Explanation
The blue LED flashes.	The battery is being charged.
The blue LED glows continuous.	The battery is fully charged.

13.1.2.2 Procedure

Follow this procedure:

- 1. Put the battery in the battery charger.
- 2. Connect the power supply cable plug to the connector on the battery charger.
- 3. Connect the power supply mains-electricity plug to a mains socket.
- Disconnect the power supply cable plug when the blue LED on the battery charger is continuous.

13.2 Turning on the camera

13.2.1 Procedure

Follow this procedure:

1. To turn on the camera, push and release the ① button.

13.3 Turning off the camera


13.3.1 Procedure

Follow this procedure:

1. To turn off the camera, push and hold the button for more than 0.2 second.

13.4 Adjusting the viewfinder's dioptric correction

13.4.1 Figure



<u>^</u>

CAUTION

Applicability: Cameras with a viewfinder.

Make sure that the beams from the intensive energy sources do not go into the viewfinder. The beams can cause damage to the camera. This includes the devices that emit laser radiation, or the sun.

Note This item is dependent on the camera model.

13.4.2 Procedure

Follow this procedure:


1. To adjust the viewfinder's dioptric correction, look at the displayed text or graphics on the screen, and rotate the adjustment knob clockwise or counter-clockwise for best sharpness.

Note

- Maximum dioptric correction: +2.
- Minimum dioptric correction: -2.


13.5 Adjusting the angle of the lens

13.5.1 Figure



13.6 Adjusting the infrared camera focus manually

13.6.1 Figure



13.6.2 Procedure


- 1. Do one of the following:
 - For far focus, rotate the focus ring clockwise (looking at the touch-screen LCD side).
 - For near focus, rotate the focus ring counter-clockwise (looking at the touch-screen LCD side).

Note

- Do not touch the lens surface when you adjust the infrared camera focus manually. If this happens, clean the lens according to the instructions in 27.2 Infrared lens, page 483
- The focus ring can be rotated infinitely, but only a certain amount of rotation is needed when focusing.

13.7 Autofocusing the infrared camera

13.7.1 Figure



13.7.2 Procedure

Follow this procedure:

 To autofocus the camera when continuos autofocus is disabled, push the Autofocus/ Save button half-way down.

13.8 Continuous autofocus

13.8.1 General

The camera can be set up to perform continuous autofocusing.

Note

- In this mode, the digital camera is used, which means that continuous autofocus will not work in darkness.
- When continuous autofocus is enabled, it is not possible to manually adjust the focus by rotating the focus ring.

13.8.2 Procedure

Follow this procedure:


- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select *Device settings* and push the joystick.
- 5. Select Set up camera and push the joystick.
- 6. Select *Continuous autofocus*. If the check box is unchecked, push the joystick to enable continuous autofocus.
- Aim the camera toward the object of interest. The camera will now continuously autofocus.

Note To pause continuous autofocusing, push the Autofocus/Save button half-way down.

13.9 Operating the laser pointer

Note The laser pointer is enabled by a setting. Select (Settings) > Device settings > Set up camera > Lamp & laser > Enable lamp & laser.

13.9.1 Figure



13.9.2 Procedure

Follow this procedure:


- 1. To turn on the laser pointer, push and hold the laser button.
- 2. To turn off the laser pointer, release the laser button.

Note

- A warning indicator is displayed on the screen when the laser pointer is turned on.
- The position of the laser dot is indicated on the infrared image (depending on the camera model).

13.10 Using the digital zoom function

13.10.1 Figure



13.10.2 Procedure


Follow this procedure:

1. To zoom, push the zoom button left or right.

13.11 Changing lenses

Follow this procedure:

1. Take a firm grip around the outermost part of the lens.




2. Rotate the lens 30° degrees counter-clockwise.




3. Carefully pull out the lens from the lens bayonet mount.




4. The infrared detector is now fully exposed. Do not touch this surface. If you see dust on the detector, follow the instructions in 27.3 *Infrared detector*, page 484.



5. Note the index marks on the lens bayonet mount and on the lens.








7. Carefully push the lens into position.



8. Rotate the lens 30° degrees clockwise.



13.12 Calibrating the compass

13.12.1 Procedure

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select *Device settings* and push the joystick.
- 5. Select GPS & compass and push the joystick.
- 6. Select *Compass*. If the *Compass* check box is unchecked, push the joystick to enable the compass.

Select Calibrate compass and push the joystick. Follow the on-screen instructions.
 Note You have to rotate the camera slowly.

13.13 Changing the viewfinder eyecup



CAUTION

Applicability: Cameras with a viewfinder.


Make sure that the beams from the intensive energy sources do not go into the viewfinder. The beams can cause damage to the camera. This includes the devices that emit laser radiation, or the sun.

Note This item is dependent on the camera model.


Follow this procedure:


1. Put your thumbs at the lower part of the eyecup. Push the eyecup horizontally, away from the touch-screen LCD side, until the eyecup slides out from its mount.


Note To remove the eyecup, you must slide it out from its mount. Do not pull the eyecup straight up.




2. Note the grooves on the eyecup mount on the camera and on the new eyecup.







4. Carefully slide the eyecup into position.



13.14 Using the camera lamp as a flash

13.14.1 General

The camera lamp can be used as a flash for the digital camera. When the flash function is activated, the camera lamp will flash when an image is saved by pushing the Autofocus/ Save button fully down.

13.14.2 Procedure

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Device settings and push the joystick.
- 5. Select Set up camera and push the joystick.
- 6. Select Lamp & laser and push the joystick.
- 7. Select *Enable lamp & laser*. If the check box is unchecked, push the joystick to enable the camera lamp.
- 8. Select *Use lamp as flash*. If the check box is unchecked, push the joystick to activate the flash function.

Working with images

14.1 Saving an image

14.1.1 General

You can save images to a memory card.

The camera saves an image file including all thermal and visual information. This means that you can open an image file at a later stage and, for example, select another image mode, apply color alarms, and add measurement tools.

The image jpg file is fully radiometric and saved lossless, which enables full post-processing in FLIR Tools. There is also a regular jpg part (lossy) for convenient viewing in non-FLIR Systems software (Explorer).

14.1.2 About UltraMax

UltraMax is an image enhancement feature that increases the image resolution and lowers the noise, making small objects easier to see and measure. An UltraMax image is twice as wide and high as an ordinary image.

When an UltraMax image is captured by the camera, several ordinary images are saved in the same file. Capturing all the images can take up to 1 second. To fully utilize UltraMax, the images need to be slightly different, which can be accomplished by a slight movement of the camera. You should hold the camera firmly in your hands (do not put it on a tripod), which will make these images vary just a little during the capture. Correct focus, a high-contrast scene, and a non-moving target are other conditions that help to achieve a good-quality UltraMax image.

At the moment, only FLIR Tools has the ability to process UltraMax images. Other FLIR software will treat the image as a regular image.

14.1.3 Image capacity

The capacity of a 4 GB memory card is theoretically 3600 images (with no annotations).

14.1.4 Naming convention

The naming convention for image files is FLIRxxxx.jpg, where xxxx is a unique counter.

14.1.5 Procedure

Follow this procedure:

1. To save an image, push the Autofocus/Save button fully down.

Note

- Depending on the settings in (Settings) > Save options, the following may happen:
 - A preview image is displayed before the image is saved.
 - An annotation tool or the annotation menu is displayed when the image has been saved.
- To configure UltraMax, select (Settings) > Save options > Image resolution = UltraMax.
- The camera can be configured to also save the visual image as a separate file. Select
 - (Settings) > Save options > Photo as separate JPEG = On.

14.2 Previewing an image

14.2.1 General

You can preview an image before you save it. This enables you to see if the image contains the information you want before you save it. You can also adjust and edit the image.

Note The camera must be configured to display a preview image before saving. Select

(Settings) > Save options > Preview image before saving = On.

14.2.2 Procedure

Follow this procedure:

- 1. To preview an image, push the Autofocus/Save button fully down. This displays the preview.
- 2. Manual image adjust mode is now active, and the status icon is displayed. For image adjustment instructions, see 14.5 *Adjusting an infrared image*, page 39.
- 3. To edit the image, push the joystick. This displays a context menu. For editing instructions, see 14.4 *Editing a saved image*, page 38.
- 4. Do one of the following:
 - To save the image, push the Autofocus/Save button fully down.
 - To exit preview mode without saving, push the Back button ...

14.3 Opening a saved image

14.3.1 Genera

When you save an image, the image file is stored on the memory card. To display the image again, open it from the image archive.

14.3.2 Procedure

Follow this procedure:

- 1. Push the Image archive button
- 2. Move the joystick up/down or left/right to select the image you want to view.
- 3. Push the joystick. This will display the image at full size.
- 4. Do one or more of the following:
 - To switch between an infrared image and a visual image, move the joystick up/down.
 - To view the previous/next image, move the joystick left/right.
 - To edit the image, add annotations, display information, or delete the image, push the joystick. This displays a context menu.
 - To return to the image archive overview, push the Back button

14.4 Editing a saved image

14.4.1 General

You can edit a saved image. You can also edit an image in preview mode.

14.4.2 Procedure

Follow this procedure:

- 1. Open the image in the image archive.
- 2. Push the joystick and select (Edit) from the menu.
- 3. Manual image adjust mode is now active, and the status icon is displayed. For image adjustment instructions, see 14.5 *Adjusting an infrared image*, page 39.
- 4. Push the joystick. This displays a context menu.
 - Select (Cancel) to exit edit mode.
 - Select (Measurement parameters) to change the global parameters.
 - Select (Image mode) to change the image mode.

 - Select (Color) to change the color palette or set a color alarm.
 - Select (Save) to save and exit edit mode.

14.5 Adjusting an infrared image


14.5.1 General

An infrared image can be adjusted automatically or manually. When manual image adjust mode is active, the status icon $^{\parallel}$ is displayed.

- In live mode, push the button 1 to switch between automatic and manual image adjust modes. You can also switch between the modes by touching the temperature scale on the screen.
- In preview/edit mode, manual image adjust mode is active.


14.5.2 Example 1

Here are two infrared images of a building. In the left image, which is auto-adjusted, the large temperature span between the clear sky and the heated building makes a correct analysis difficult. You can analyze the building in more detail if you change the temperature scale to values close to the temperature of the building.



14.5.3 Example 2

Here are two infrared images of an isolator in a power line. To make it easier to analyze the temperature variations in the isolator, the temperature scale in the right image has been changed to values close to the temperature of the isolator.



14.5.4 Procedure

- 1. In live mode, push the button 1 to enter manual image adjust mode.
- 2. To change the temperature scale minimum and maximum limits simultaneously, move the joystick up/down.
- 3. To change the temperature scale minimum or maximum limit, do the following:
 - Move the joystick left/right to select (highlight) the maximum or minimum temperature.
 - Move the joystick up/down to change the value of the highlighted temperature.
- 4. (Optional step). In preview/edit mode, push the button to perform a one-shot auto-adjust sequence.

14.6 Performing a non-uniformity correction (NUC)

14.6.1 What is a non-uniformity correction?

A non-uniformity correction is an image correction carried out by the camera software to compensate for different sensitivities of detector elements and other optical and geometrical disturbances1.

14.6.2 When to perform a non-uniformity correction?

The non-uniformity correction process should be carried out whenever the output image becomes spatially noisy. The output can become spatially noisy when the ambient temperature changes (such as from day to night operation, and vice versa).

14.6.3 Procedure

To perform a non-uniformity correction, push and hold the Image archive button for more than 2 seconds.



Changing the temperature range 14.7

14.7.1 General

You must change the temperature range according to the expected temperature of the object you are inspecting.

14.7.2 Procedure

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select *Device settings* and push the joystick.
- 5. Select Set up camera and push the joystick.
- 6. Select Camera temperature range and push the joystick.
- 7. Select the appropriate temperature range and push the joystick.

Note You can also assign the function *Switch temperature range* to the programmable

button. Select (Settings) > Programmable button > Switch temperature range.

Hiding overlay graphics (programmable 14.8 button)

14.8.1 General

Overlay graphics provide information about an image, e.g., measurement functions and parameters. You can choose to hide all overlay graphics.

^{1.} Definition from the impending international adoption of DIN 54190-3 (Non-destructive testing - Thermographic testing - Part 3: Terms and definitions).

14.8.2 Procedure

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Programmable button and push the joystick.
- 5. Select *Hide graphics* and push the joystick. You have now assigned this function to the button **P**. This is a programmable button, and you can assign other functions to it.

Note Other functions that can be associated with the programmable button include the following:

- Hide graphics
- Calibrate
- Switch Thermal <> Digital camera
- Switch Thermal <> Thermal MSX
- Switch 1x zoom <> Max zoom
- · Switch between two latest palettes
- · Switch temperature range
- · Continuous autofocus

14.9 Changing the color palette

14.9.1 General

You can change the color palette that the camera uses to display different temperatures. A different palette can make it easier to analyze an image.

14.9.2 Procedure

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Color).
- 3. Push the joystick to display a submenu.
- 4. Use the joystick to select a different palette.
- 5. Push the joystick.

14.10 Deleting an image

14.10.1 General

You can delete an image from the memory card.

14.10.2 Procedure

- 1. Push the Image archive button
- 2. Move the joystick up/down or left/right to select the image you want to delete.

- 3. Push the joystick to display the image.
- 4. Push the joystick to display a menu.
- 5. On the menu, select (Delete).
- 6. Push the joystick and confirm the choice.

Note Note that both images in the image file (thermal and visual) will be deleted.

14.11 Deleting all images

14.11.1 General

You can delete all images from the memory card.

14.11.2 Procedure

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Reset options and push the joystick.
- 5. Select Delete all saved images... and confirm the choice.

14.12 Creating a PDF report in the camera

14.12.1 General

You can create a PDF report and save it to the memory card. You can then transfer the PDF report to a computer, iPhone, or iPad using FLIR Tools, and send the report to a customer.

14.12.2 Naming convention

The naming convention for report files is REPORTxxxx.jpg, where xxxx is a unique counter.

14.12.3 Procedure

- 1. Push the Image archive button
- 2. Move the joystick up/down or left/right to select an image.
- 3. Push the joystick to display the image.
- 4. Push the joystick to display a context menu.
- 5. Select (*Information & reports*) and push the joystick. This displays information about the image.
- 6. Select *Create report* and push the joystick. The created report will be available in the archive.

Working with image modes

15.1 General

The camera captures both thermal and visual images at the same time. By your choice of image mode, you select which type of image to display on the screen.

The camera supports the following image modes:

- Thermal MSX (Multi Spectral Dynamic Imaging): The camera displays infrared images where the edges of the objects are enhanced with visual image details.
- Thermal: A full infrared image is displayed.
- Picture in picture: An infrared image frame is displayed on top of the visual image.
- Digital camera: The visual image captured by the digital camera is displayed.

Note

- These image modes only work correctly for calibrated lenses. The lens that ships with the camera is factory calibrated. To have a new lens calibrated, you must send in the camera and the lens to your local service department.
- All thermal and visual information is stored when an image is saved. This means that
 you can edit the image later, in the image archive or in FLIR Tools, and select any of the
 image modes.

15.2 Image examples

This table explains the different types of image modes.

Image mode	Image
Thermal	
Thermal MSX	

Image mode	Image
Picture in picture	
Digital camera	

15.3 Selecting the image mode

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Image mode).
- 3. Push the joystick to display a submenu.
- 4. Use the joystick to go to one of the image modes:
 - (Thermal MSX)
 - (Thermal)
 - (Picture in picture)
- 5. Push the joystick confirm.
- 6. If *Picture in picture* mode is selected, you can at this point move and resize the infrared image frame using the touch screen.

Working with measurement tools

16.1 General

To measure a temperature, you can use one or more measurement tools, e.g., a spotmeter or a box.

16.2 Adding/removing measurement tools

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Measurement).
- 3. Push the joystick to display a submenu.
 - Select * (No measurements) to remove all tools.
 - Select (Center spot) to add a center spot.
 - Select (Hot spot) to add a hot spot detection within a box area.
 - Select (Cold spot) to add a cold spot detection within a box area.
 - Select [1] (User preset 1) to add user preset 1. (Not available in all camera models.)
 - Select [2] (User preset 2) to add user preset 2. (Not available in all camera models.)
- 4. Push the joystick. This displays the measurement tool or the group of preset tools on the screen.

16.3 Working with user presets

16.3.1 General

A user preset is a measurement tool, or a group of measurement tools, with predefined characteristics.

16.3.2 Procedure

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Select Define user presets and push the joystick.
- 5. Select *Define preset 1* or *Define preset 2* and push the joystick. This displays a context menu.
- 6. Select (Add measurement).

- 7. Push the joystick. This displays a submenu.
 - Select \diamondsuit (Add spot) to add a spot.
 - Select [(Add box) to add a box.
 - Select (Add circle) to add a circle.
 - Select (Add line) to add a line.
 - Select \triangle (Add delta) to set up a differential calculation.
- 8. Push the joystick. This displays the measurement tool on the screen.
- 9. Push the joystick. This displays a context menu, where you can select one or more of the following actions (depending on the type of tool):
 - · Remove the tool.
 - · Resize, move, center, and rotate the tool.
 - · Display maximum, minimum, and average values.
 - · Set alarms.
 - Set local parameters.
 - When completed, select [⊘] (*Done*).

10. When all measurement tools have been added, select (Save as preset).

16.4 Resizing or moving a measurement tool

16.4.1 General

You can resize and move a measurement tool.

16.4.2 Procedure

Note

- This procedure assumes that you have previously laid out a measurement tool or user preset on the screen.
- You can also move and resize the measurement tool by touching the screen.

Follow this procedure:

1. To select the measurement tool, touch the tool on the screen. The tool is now displayed with one or more handles.



•

Area measurement tool:

- 2. Push the joystick—or touch and hold the tool. This displays a context menu.
 - Select ** (Resize) to change the size of the tool.
 - Select $\frac{\mathbb{R}_0 \mathbb{R}}{\mathbb{R}}$ (*Move*) to move the tool.
- 3. Move the joystick up/down and left/right to resize or move the tool.
- 4. When completed, push the joystick and select (Done).

16.5 Changing object parameters

16.5.1 General

For accurate measurements, you must set the object parameters.

16.5.2 Types of parameters

The camera can use these object parameters:

- External IR window compensation, i.e., the temperature of any protective windows, external lenses (e.g., the close-up lens), etc., that are set up between the camera and the object of interest. If no protective window, protective shield, or external lens is used, this value is irrelevant and should be left inactive.
- Object distance, i.e., the distance between the camera and the object of interest.
- Atmospheric temperature, i.e., the temperature of the air between the camera and the object of interest.
- Relative humidity, i.e., the relative humidity of the air between the camera and the object of interest.
- Reflected temperature, which is used when compensating for the radiation from the surroundings reflected by the object into the camera. This property of the object is called "reflectivity".
- Emissivity, i.e., how much radiation an object emits, compared with the radiation of a
 theoretical reference object at the same temperature (called a "blackbody"). The opposite of emissivity is reflectivity. The emissivity determines how much of the radiation
 originates from the object as opposed to being reflected by it.

Note There is an *Emissivity mode* setting, which you can use to enter the emissivity by material instead of by value. Select (Settings) > Device settings > Set up camera > Emissivity mode > Select from materials table.

Of the object parameters, *Emissivity* is the most important parameter to set correctly. If the *Emissivity* is set to a low value, the *Reflected temperature* also becomes important. The parameters *Object distance*, *Atmospheric temperature*, and *Relative humidity* are relevant for longer distances. The *External IR window compensation* must be activated if a protective window or external lens is used.

16.5.3 Recommended values

If you are unsure about the values, the following are recommended:

Object distance	1.0 m (3.3')
Atmospheric temperature	20°C (69°F)
Relative humidity	50%
Reflected temperature	20°C (69°F)
Emissivity	0.95

16.5.4 Procedure

You can set the object parameters globally. You can also change the *Emissivity, Reflected temperature*, and *Object distance* parameters locally for a measurement tool.

Local parameters are normally only effective for a fixed setup, where each measurement tool is set to a specific object of interest. In a general handheld application, the global parameters are usually sufficient.

Note Of the object parameters, *Emissivity* and *Reflected temperature* are the two most important to set correctly in the camera.

16.5.4.1 Setting global parameters

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to [14] (Measurement parameters).
- 3. Push the joystick to display a submenu. Use the joystick to select one or more of the global object parameters:
 - (External IR window compensation)
 - (Object distance)
 - (Atmospheric temperature)
 - (Relative humidity)
 - (Reflected temperature)
 - E[™] (Emissivity)
- 4. Push the joystick to display a dialog box.
- 5. Use the joystick to change the parameter.
- 6. Push the joystick. This closes the dialog box.

16.5.4.2 Changing local parameters

You can change the local parameters for a measurement tool.

A *P* next to the measurement tool on the screen indicates that local parameters are activated for the tool.

- 1. To select the measurement tool, touch the tool on the screen. The tool is now displayed with one or more handles.
- 2. Push the joystick—or touch and hold the tool. This displays a context menu.
- 3. Use the joystick to go to to (Use local parameters).
- 4. Push the joystick. (icon with gray indicator) is displayed.
- 5. Push the joystick to activate the use of local parameters. (icon with blue indicator) is displayed together with a submenu.
- 6. Use the joystick to select an object parameter.
- 7. Push the joystick to display a dialog box.
- 8. Use the joystick to change the parameter.

- 9. Push the joystick. This closes the dialog box.
- 10. When completed, push the joystick and select (Done).

16.5.5 Related topics

For in-depth information about parameters, and how to correctly set the emissivity and reflected apparent temperature, see section 31 *Thermographic measurement techniques*, page 495.

16.6 Displaying values in the result table and displaying a graph

16.6.1 General

For the box, circle, and line tools, you can set the camera to display the maximum, minimum, and average values in the result table.

For the line tool, you can also display a graph.

16.6.2 Procedure

- 1. To select the measurement tool, touch the tool on the screen. The tool is now displayed with one or more handles.
- 2. Push the joystick—or touch and hold the tool. This displays a context menu.
- 3. Use the joystick to go to (depending on the tool) [], or (Max/Min/Avg/Alarm) or (Graph/Max/Min/Avg/Alarm).
- 4. Push the joystick. This displays a submenu.
 - (Option available for the line tool.) Select (Graph) and push the joystick to display a graph.
 - Select (Max) and push the joystick to display the maximum value.
 - Select (Min) and push the joystick to display the minimum value.
 - Select (Avg) and push the joystick to display the average value.
 - (Optional step.) You can choose to show or hide the maximum and minimum
 markers (the hot/cold spots). Select (Max & min markers) and push the joystick
 to toggle:
 - When (icon with grey indicator) is displayed, the markers are hidden.
 - When (icon with blue indicator) is displayed, the markers are shown.
- 5. When completed, move the joystick down to close the submenu.
- 6. Select (Done) and push the joystick.

16.7 Creating and setting up a difference calculation

16.7.1 General

A difference calculation gives the difference between the values of two known measurement results.

16.7.2 Procedure


Note

- You can set up a difference calculation when defining user presets, or when editing an image in the archive.
- This procedure assumes that you have previously laid out at least one measurement tool on the screen.

16.7.2.1 Procedure

Follow this procedure:

- 1. To set up a difference calculation, select \triangle (Add delta).
- 2. Push the joystick. This displays a dialog box where you can select the measurement tools that you want to use in the difference calculation. You can also select a fixed-temperature reference.



3. Push the joystick. The result of the difference calculation is now displayed on the screen.

16.8 Setting a measurement alarm

16.8.1 General

You can make the camera trigger an alarm when certain measurement conditions are met.

16.8.2 Types of alarm

You can choose between the following alarm types:

- Above: Triggers an alarm when the temperature is above the preset alarm temperature.
- Below: Triggers an alarm when the temperature is below the preset alarm temperature.

16.8.3 Alarm signals

When an alarm is set, the symbol $\, \stackrel{\P}{=} \,$ is displayed in the result table.

When an alarm is triggered, the value in the result table is displayed in red (above alarm) or blue (below alarm) and the symbol (above alarm) or (below alarm) is blinking. You can also set an audible alarm (there will be a "beep" when the alarm is triggered).

16.8.4 Procedure

There are different procedures for setting up an alarm for a spot, box, circle, or line and for a difference calculation.

16.8.4.1 Setting up an alarm for a spot

Follow this procedure:

- 1. To select the spot, touch the tool on the screen. The tool is now displayed with a frame.
- 2. Push the joystick—or touch and hold the tool. This displays a context menu.
- 3. Use the joystick to go to (Set alarm on spot).
- 4. Push the joystick. This displays a dialog box where you can define the settings for the alarm.
 - Alarm condition: The condition that triggers the alarm. Applicable values are Above, Below, or Off.
 - Alarm limit: The temperature value that will be the critical condition when an alarm is triggered or not.
 - Alarm sound: Applicable values are Beep or No sound.
- 5. Push the joystick. This closes the dialog box.
- 6. Push the joystick and select ^ℳ (*Done*).

16.8.4.2 Setting up an alarm for a box, circle, or line

Note This procedure assumes that you have previously set the camera to display at least one value (maximum, minimum, or average) in the result table.

- To select the measurement tool, touch the tool on the screen. The tool is now displayed with one or more handles.
- 2. Push the joystick—or touch and hold the tool. This displays a context menu.
- 3. Use the joystick to go to (depending on tool) [], (), or (Max/Min/Avg/Alarm) or (Graph/Max/Min/Avg/Alarm).
- 4. Push the joystick. This displays a submenu.
- 5. Select (Set alarm).

- 6. Push the joystick. This displays a dialog box where you can define the settings for the alarm.
 - Alarm condition: The condition that triggers the alarm. Applicable values are Above, Below, or Off.
 - Select measurement: Applicable settings are the values you have previously defined (Max, Min, and/or Avg).
 - Alarm limit: The temperature value that will be the critical condition when an alarm is triggered or not.
 - Alarm sound: Applicable values are Beep or No sound.
- 7. Push the joystick. This closes the dialog box.
- 8. Push the joystick and select (Done).

16.8.4.3 Setting up an alarm for a difference calculation

Note

- You can set up an alarm for a difference calculation when defining user presets, or when editing an image in the archive.
- This procedure assumes that you have previously set up a difference calculation.

- 1. Select (Add measurement). This displays a submenu.
- 2. Select (Select). This displays a dialog box.
- 3. Select Delta. This displays a context menu.
- 4. Use the joystick to go to 4 (Set alarm on delta).
- 5. Push the joystick. This displays a dialog box where you can define the settings for the alarm.
 - Alarm condition: The condition that triggers the alarm. Applicable values are Above, Below, or Off.
 - Alarm limit: The temperature value that will be the critical condition when an alarm is triggered or not.
 - Alarm sound: Applicable values are Beep or No sound.
- 6. Push the joystick. This closes the dialog box.

Fetching data from external FLIR meters

17.1 General

You can fetch data from an external FLIR meter and merge this data into the infrared image.

When the camera is connected to a FLIR meter via Bluetooth, the measurement value from the meter is displayed in the result table of the camera. The FLIR meter value is also added to the information saved in the image file. In preview mode and when editing an image in the archive, you can add more than one value from the same FLIR meter.

Note

- Before you can use a FLIR meter with the camera, you need to pair the devices. For more information, see 11 Pairing Bluetooth devices, page 23.
- To add more than one FLIR meter value when saving an image, preview mode must be enabled. Select (Settings) > Save options > Preview image before saving = On.

In preview mode and when editing an image in the archive, you can do the following:

- Push the programmable button P to add the value currently displayed by the FLIR meter.
- Push and hold the programmable button P to remove all FLIR meter values from the image.

Note Any function assigned to the programmable button is temporarily disabled when in preview mode or when editing an image in the archive.

17.2 Supported FLIR meters

- FLIR CM78
- FLIR CM83
- FLIR DM93
- FLIR MR77

17.3 Technical support for external meters

Technical support	
Website	http://support.flir.com
E-mail	TMsupport@flir.com
Phone	855-499-3662
Repairs	repair@flir.com

17.4 Typical moisture measurement and documentation procedure

17.4.1 General

The following procedure can form the basis for other procedures using FLIR meters and infrared cameras.

17.4.2 Procedure

Follow this procedure:

- 1. Use the infrared camera to identify any potential damp areas behind walls and ceilings.
- 2. Use the moisture meter to measure the moisture levels at various suspect locations that may have been found.
- 3. When an area of particular interest is located, store the moisture reading in the moisture meter's memory and identify the measurement area with a handprint or other thermal identifying marker.
- 4. Recall the reading from the meter memory. The moisture meter will now continuously transmit this reading to the infrared camera.
- 5. Use the camera to take a thermal image of the area with the identifying marker. The stored data from the moisture meter will also be saved on the image.

17.5 More information

For more information, see the users' manuals that are shipped with the FLIR meters.

Working with color alarms and isotherms

18.1 Color alarms

18.1.1 General

By using color alarms (isotherms), anomalies can easily be discovered in an infrared image. The isotherm command applies a contrasting color to all pixels with a temperature above, below, or between the set temperature levels. The camera also features isotherm types that are specific to the building trade: condensation and insulation alarms.

You can make the camera trigger the following types of color alarms:

- Above alarm: This will apply a contrasting color to all pixels with a temperature above the specified temperature level.
- Below alarm: This will apply a contrasting color to all pixels with a temperature below the specified temperature level.
- Interval alarm: This will apply a contrasting color to all pixels with a temperature between two specified temperature levels.
- Condensation alarm: Triggers when the camera detects a surface where the relative humidity exceeds a preset value.
- Insulation alarm: Triggers when there is an insulation deficiency in a wall.

18.1.2 Image examples

This table explains the different color alarms (isotherms).

Color alarm	Image
Above alarm	
Below alarm	



Setting up above, below, and interval 18.2 alarms

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Color).
 3. Push the joystick to display a submenu. Use the joystick to select the type of alarm:
 - (Above alarm)
 - (Below alarm)
 - (Interval alarm)

- 4. Push the joystick. The threshold temperature is displayed at the bottom of the screen.
- 5. To change the threshold temperature, do the following:
 - For the Interval alarm, move the joystick left/right to select the low/high-temperature value.
 - Move the joystick up/down to change the threshold temperature.

18.3 Building isotherms

Note The Condensation and Insulation alarms are not supported by all camera models.

18.3.1 About the Condensation alarm

To detect areas with potential moisture problems, you can use the *Condensation alarm*. You can set the relative humidity above which the isotherm will colorize the image.

18.3.2 About the Insulation alarm

The *Insulation alarm* can detect areas where there may be an insulation deficiency in the building. It will trigger when the insulation level (which is called the thermal index in the camera) falls below a preset value of the energy leakage through a wall.

Different building codes recommend different values for the insulation level, but typical values are 60–80% for new buildings. Refer to your national building code for recommendations.

18.3.3 Setting up condensation and insulation alarms

Follow this procedure:

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Color).
- 3. Push the joystick to display a submenu. Use the joystick to select the type of alarm:
 - (Condensation alarm)
 - (Insulation alarm)
- 4. Push the joystick. This displays a dialog box where you can define the settings for the alarm.

For the Condensation alarm, the following parameters can be set:

- Atmospheric temperature: The current atmospheric temperature.
- Relative humidity: The current relative humidity.
- Relative humidity limit: The relative humidity level at which you want the alarm to be triggered. A relative humidity of 100% means that water vapor condenses from the air as liquid water (= dewpoint). A relative humidity of about 70% or above can cause mold.

For the *Insulation alarm*, the following parameters can be set:

- Indoor temperature: The current indoor temperature.
- Outdoor temperature: The current outdoor temperature.
- Thermal index: The insulation level, an integer between 0 and 100.
- 5. Push the joystick. This closes the dialog box.

Annotating images

19.1 General

You can save additional information together with an infrared image by using annotations. Annotations make reporting and post-processing more efficient, by providing essential information about the image, e.g., conditions and information about where an image is taken.

Annotations are added to the image file, and can be viewed and edited in the image archive, and also when moving files from the camera to reporting software on the computer.

- You can set the camera to display annotation tools before an image is saved. Select
 (Settings) > Save options > Add annotation after saving.
- You can also add annotations to a saved image in the image archive.

Note This section describes the procedures for adding annotations to a saved image in the image archive. Adding annotations when saving an image works in a similar way.

19.2 Adding a note


19.2.1 General

A text note is grouped with the image file. Using this feature, you can annotate images by entering free-form text.

19.2.2 Procedure

Follow this procedure:

- 1. Open the image in the image archive.
- 2. Push the joystick. This displays a context menu.
- 3. Select (Add note).
- 4. Push the joystick. This displays a soft keyboard where you can enter the text you want to save.



Note To select special characters, press and hold down the corresponding key on the soft keyboard.

5. When completed, touch *Done* on the soft keyboard.

19.3 Adding a table

19.3.1 General

You can save a table with textual information to the image file. This feature is a very efficient way of recording information when you are inspecting a large number of similar objects. The idea behind using a table with textual information is to avoid filling out forms or inspection protocols manually.

The camera has a number of default table templates. You can also import your own table templates from FLIR Tools. The templates are stored on the memory card.

19.3.2 Procedure

Follow this procedure:

- 1. Open the image in the image archive.
- 2. Push the joystick. This displays a context menu.
- 3. Select (Add table) and push the joystick.
- 4. Select (Add table contents) and push the joystick.
- 5. This displays the default table template that ships with the camera.

Note You can select another template by first selecting \boxminus (Select default template).

- 6. For each row in the table, do the following:
 - Push the joystick. This displays the predefined values.
 - Move the joystick up/down to select a predefined value. Push the joystick to confirm.
 - Instead of selecting a predefined value, you can select the keyboard and enter other text.
- 7. When completed, select *Save & Exit* at the bottom of the table. Push the joystick to confirm.

19.4 Adding a voice annotation

19.4.1 General

A voice annotation is an audio recording that is saved to the infrared image file.

The voice annotation is recorded using a Bluetooth headset. The recording can be played back in the camera, and in image analysis and reporting software from FLIR Systems.

19.4.2 Procedure

- 1. Open the image in the image archive.
- 2. Push the joystick. This displays a context menu.
- 3. Select (Add voice annotation) and push the joystick.
- 4. To start a recording, select (Record) and push the joystick.
- 5. To stop the recording, select (Stop) and push the joystick.

- 6. To listen to the recording, select (*Play*) and push the joystick.
- 7. To delete the recording, select (Delete) and push the joystick.
- 8. When completed, select (Done) and push the joystick.

19.5 Adding a sketch

19.5.1 **General**

You can add a freehand drawing to an image.

19.5.2 Procedure

- 1. Open the image in the image archive.
- 2. Push the joystick. This displays a context menu.
- 3. Select (Add sketch) and push the joystick.
- 4. You are now in sketch mode. Draw the sketch by touching the screen.
- 5. Push the joystick. This displays a context menu. Do one or more of the following:
 - To change the color of the sketch tools, select (Draw) and push the joystick. Select the color and push the joystick.
 - To erase, select * (*Eraser*) and push the joystick. Erase parts of the sketch by touching the screen.
 - To add an arrow, circle, or cross, select (Stamp sketch) and push the joystick. Select the type of stamp and push the joystick. The stamp is displayed in the center of the screen. You can move the stamp by touching the screen.
 - To clear, select (Clear all) and push the joystick.
 - When the sketch is completed, select (Save) and push the joystick.

Programming the camera (time lapse)

20.1 General

You can program the camera to save images periodically (time lapse).

20.2 Procedure

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Recording mode).
- 3. Push the joystick. This displays a submenu.
- 4. Select (Time lapse).
- 5. Push the joystick. This displays a dialog box, where you can set the save conditions:
 - Save interval: Use the joystick to set the time interval between each saved image.
 - Total number of images: Periodic saving will stop when the set number of images have been saved.
- 6. Push the joystick. This closes the dialog box. The time interval is displayed at the top of the screen.
- 7. To manually start or stop periodic saving, briefly push and release the Autofocus/Save button.

Recording video clips

21.1 General

You can record and save video clips to the memory card.

Note The camera can be configured to save video in *.mpg or *.csq format. Select (Settings) > Save options > Video compression.

- *Mpeg (*.mpg)*: Mpeg recordings cannot be edited after the file has been saved.
- Radiometric storage (*csq): A *.csq file supports full radiometry but is only supported by FLIR Systems software. The file does not include any visual-image information.

21.2 **Procedure**

- 1. Push the joystick to display the menu system.
- Use the joystick to go to (Recording mode).
 Push the joystick. This displays a submenu.
- 4. Select (Video) and push the joystick.
- 5. Do the following:
 - To start a recording, push and release the Autofocus/Save button. A counter at the top of the screen displays the duration of the recording.
 - To stop a recording, push and release the Autofocus/Save button.
- 6. The recording is automatically saved to the image archive, where you can play or delete it.

Screening alarm

22.1 General

The screening alarm can be used, for example, at airports to detect passengers with elevated body temperatures, which may indicate the presence of a fever.

Activating the screening alarm will turn on a measurement box and screening data in the result table.

X The sampled average temperature.

The alarm temperature.

The measured temperature.

The alarm will trigger when the measurement box measures a temperature higher than the alarm temperature. The alarm temperature is, in turn, the sum of a specified allowed deviation and a sampled average value.

22.2 Procedure

Follow this procedure:

- 1. Enable the screening mode by selecting (Settings) > Device settings > Set up camera > Screening mode = On.
- 2. Push the joystick to display the menu system.
- 3. Use the joystick to go to (Recording mode).
- 4. Push the joystick. This displays a submenu.
- 5. Select (Screening).
- 6. Push the joystick. This displays a dialog box where you can define the settings for the alarm.
 - Allowed deviation: The allowed deviation from the sampled average.
 - Alarm sound: Applicable values are Beep or No sound.
- 7. Push the joystick. This closes the dialog box.
- Aim the camera toward a point of interest. The object should be within the frame of the measurement box.
- 9. Push and hold the programmable button P to reset the sampled average.
- 10. Push the programmable button ${f P}$ to sample.
- 11. Aim the camera toward more points of interest. Sample 10 times to build up a sample base by pushing the programmable button P.

The alarm is now set up and ready to use. Occasionally record a few samples if the alarm is used for a long time or if the conditions change.

Note

- The algorithm has a memory of the last 10 samples. It discriminates between the highest and lowest values, and calculates an average of the remaining values.
- Do not modify the measurement setup or activate another alarm because this will deactivate the screening alarm.

Changing settings

23.1 General

The Settings menu includes the following:

- Define user presets
- Save options
- Programmable button
- Reset options
- · Device settings

23.1.1 Define user presets

- Define preset 1
- Define preset 2

23.1.2 Save options

- Preview image before saving
- · Add annotation after saving
- Image resolution
- Video compression
- Photo as separate JPEG

23.1.3 Programmable button

- No action
- · Hide graphics
- Calibrate
- Switch Thermal <> Digital camera
- Switch Thermal <> Thermal MSX
- Switch 1x zoom <> Max zoom
- · Switch between two latest palettes
- Switch temperature range
- Continuous autofocus

23.1.4 Reset options

- Reset default camera mode...
- · Reset device settings to factory default...
- Delete all saved images...

Note When an option is selected, a dialog box is displayed with more information. You can choose to execute the reset/delete action or to cancel.

23.1.5 Device settings

- · Set up camera
 - Camera temperature range: The temperature range used for measuring objects. You
 must change the temperature range according to the expected temperature of the
 object you are inspecting.
 - Auto orientation
 - Continuous autofocus
 - Display intensity
 - Lamp & laser
 - Viewfinder intensity
 - HDMI
 - Emissivity mode

- Wi-Fi: For more information, see 12 Configuring Wi-Fi, page 24.
- GPS & compass
- Bluetooth including METERLiNK: For more information, see 11 Pairing Bluetooth devices, page 23.
- Language, time & units
- Camera information: Information about the model, serial number, part number, and software versions. No changes can be made.

23.2 Procedure

- 1. Push the joystick to display the menu system.
- 2. Use the joystick to go to (Settings).
- 3. Push the joystick to display the Settings menu.
- 4. Use the joystick to select the setting you want to change.
- 5. To exit the *Settings* menu or a submenu, push the Back button .

Technical data

Table of	of contents	
24.1	Online field-of-view calculator	68
24.2	Note about technical data	68
24.3	Note about authoritative versions	68
24.4	FLIR T600 15° (incl. Wi-Fi and Ext. cal.)	69
24.5	FLIR T600 15° (incl. Wi-Fi)	75
24.6	FLIR T600 25° (incl. Wi-Fi and Ext. cal.)	81
24.7	FLIR T600 25° (incl. Wi-Fi)	87
24.8	FLIR T600 25° and 15° w/case	93
24.9	FLIR T600 25° and 45° w/case	99
24.10	FLIR T600 45° (incl. Wi-Fi and Ext. cal.)	. 105
24.11	FLIR T600 45° (incl. Wi-Fi)	. 111
24.12	FLIR T600bx 25° (incl. Wi-Fi and Ext. cal.)	. 117
24.13	FLIR T600bx 25° (incl. Wi-Fi)	. 123
24.14	FLIR T600bx 45° (incl. Wi-Fi and Ext. cal.)	. 129
24.15	FLIR T600bx 45° (incl. Wi-Fi)	. 135
24.16	FLIR T610 15° (incl. Wi-Fi)	. 141
24.17	FLIR T610 25° (incl. Wi-Fi)	. 147
24.18	FLIR T610 45° (incl. Wi-Fi)	. 153
24.19	FLIR T620 15° (incl. Wi-Fi and Ext. cal.)	. 159
24.20	FLIR T620 15° (incl. Wi-Fi)	. 165
24.21	FLIR T620 25° (incl. Wi-Fi and Ext. cal.)	. 171
24.22	FLIR T620 25° (incl. Wi-Fi)	. 177
24.23	FLIR T620 25° and 15° (incl. Wi-Fi)	. 183
24.24	FLIR T620 25° and 45° (incl. Wi-Fi)	. 189
24.25	FLIR T620 45° (incl. Wi-Fi and Ext. cal.)	. 195
24.26	FLIR T620 45° (incl. Wi-Fi)	. 201
24.27	FLIR T620bx 15° (incl. Wi-Fi and Ext. cal.)	. 207
24.28	FLIR T620bx 15° (incl. Wi-Fi)	. 213
24.29	FLIR T620bx 25° (incl. Wi-Fi and Ext. cal.)	. 219
24.30	FLIR T620bx 25° (incl. Wi-Fi)	. 225
24.31	FLIR T620bx 45° (incl. Wi-Fi and Ext. cal.)	. 231
24.32	FLIR T620bx 45° (incl. Wi-Fi)	. 237
24.33	FLIR T630 15° (incl. Wi-Fi)	. 243
24.34	FLIR T630 25° (incl. Wi-Fi)	. 249
24.35	FLIR T630 45° (incl. Wi-Fi)	. 255
24.36	FLIR T630sc 15° (incl. Wi-Fi)	. 261
24.37	FLIR T630sc 25° (incl. Wi-Fi)	. 267
24.38	FLIR T630sc 25° and 45° w/case	. 273
24.39	FLIR T630sc 45° (incl. Wi-Fi)	. 279
24.40	FLIR T640 15° (incl. Wi-Fi and Ext. cal.)	. 285
24.41	FLIR T640 15° (incl. Wi-Fi)	

24.42	FLIR T640 25° (incl. Wi-Fi and Ext. cal.)	. 298
24.43	FLIR T640 25° (incl. Wi-Fi)	. 305
24.44	FLIR T640 25° and 15° (incl. Wi-Fi)	. 311
24.45	FLIR T640 25° and 45° (incl. Wi-Fi)	. 318
24.46	FLIR T640 45° (incl. Wi-Fi and Ext. cal.)	. 325
24.47	FLIR T640 45° (incl. Wi-Fi)	. 332
24.48	FLIR T640bx 15° (incl. Wi-Fi and Ext. cal.)	. 338
24.49	FLIR T640bx 15° (incl. Wi-Fi)	. 345
24.50	FLIR T640bx 25° (incl. Wi-Fi and Ext. cal.)	. 352
24.51	FLIR T640bx 25° (incl. Wi-Fi)	. 359
24.52	FLIR T640bx 45° (incl. Wi-Fi and Ext. cal.)	. 366
24.53	FLIR T640bx 45° (incl. Wi-Fi)	. 373
24.54	FLIR T650sc 15° (incl. Wi-Fi)	. 380
24.55	FLIR T650sc 25° (incl. Wi-Fi)	. 387
24.56	FLIR T650sc 25° and 15° w/case	. 394
24.57	FLIR T650sc 25° and 45° w/case	. 401
24.58	FLIR T650sc 45° (incl. Wi-Fi)	. 408
24.59	FLIR T660 15° (incl. Wi-Fi and Ext. cal.)	. 415
24.60	FLIR T660 15° (incl. Wi-Fi)	. 422
24.61	FLIR T660 25° (incl. Wi-Fi and Ext. cal.)	. 429
24.62	FLIR T660 25° (incl. Wi-Fi)	. 436
24.63	FLIR T660 25° and 15° w/case	. 443
24.64	FLIR T660 25° and 45° w/case	. 450
24.65	FLIR T660 45° (incl. Wi-Fi and Ext. cal.)	. 457
24.66	FLIR T660 45° (incl. Wi-Fi)	. 464

24.1 Online field-of-view calculator

Please visit http://support.flir.com and click the photo of the camera series for field-of-view tables for all lens-camera combinations.

24.2 Note about technical data

FLIR Systems reserves the right to change specifications at any time without prior notice. Please check http://support.flir.com for latest changes.

24.3 Note about authoritative versions

The authoritative version of this publication is English. In the event of divergences due to translation errors, the English text has precedence.

Any late changes are first implemented in English.

24.4 FLIR T600 15° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-1015

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data		
IR resolution	480 × 360 pixels	
UltraMax	No	
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)	
Field of view (FOV)	15° × 11°	
Minimum focus distance	0.5 m (1.64 ft.)	
Focal length	41 mm (1.63 in.)	
Spatial resolution (IFOV)	0.55 mrad	
Lens identification	Automatic	
F-number	1.0	
Image frequency	30 Hz	
Focus	Automatic (one shot) or manual	
Digital zoom	1-4× continuous	
Digital image enhancement	Adaptive digital noise reduction	

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558011867
UPC-12	845188012977
Country of origin	Sweden

Supplies & accessories:

• T197914; IR lens, f=41.3 mm (15°) with case

- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.5 FLIR T600 15° (incl. Wi-Fi)

P/N: 55903-0922

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data		
IR resolution	480 × 360 pixels	
UltraMax	No	
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)	
Field of view (FOV)	15° × 11°	
Minimum focus distance	0.5 m (1.64 ft.)	
Focal length	41 mm (1.63 in.)	
Spatial resolution (IFOV)	0.55 mrad	
Lens identification	Automatic	
F-number	1.0	
Image frequency	30 Hz	
Focus	Automatic (one shot) or manual	
Digital zoom	1-4× continuous	
Digital image enhancement	Adaptive digital noise reduction	

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up commands Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Blue-tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Storage media Removable memory SD card Image storage mode - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Pill meters with METERLINK Report generation Separate PC software with extensive report generation		
button, Reset options, Set up camera, Wi-Fi, Blue- tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Coptional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table, Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG XIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Video streaming Pull dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Set-up	
Storage of images	Set-up commands	button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera
Storage of images Image storage Storage media Image storage mode Storage media Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file file formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi	Service functions	
Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file Optional to store digital photo as a separate JPEG file Time lapse - 15 seconds to 24 hours - File formats - Standard JPEG, measurement data included - File formats, visual - Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice - Go seconds (via Bluetooth) stored with the image Text - Add table. Select between predefined templates or create your own in FLIR Tools Image description - Add short note (stored in JPEG EXIF tag) Sketch - Draw on thermal/digital photo or add predefined stamps METERLINK - Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Camera software update	Use PC software FLIR Tools
Storage media Removable memory SD card Removable memory SD card Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Storage of images	
Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi	Image storage	
Simultaneous storage or inermal and cigital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Storage media	Removable memory SD card
File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Image storage mode	photo in same JPEG file. Optional to store digital photo as a separate
File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Time lapse	15 seconds to 24 hours
Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming Visual video streaming Visual video streaming NPEG-4 using Wi-Fi • Uncompressed colorized video using USB	File formats	Standard JPEG, measurement data included
Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming Visual video streaming • MPEG-4 using Wi-Fi	File formats, visual	
Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Image annotations (in still images)	
create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Voice	60 seconds (via Bluetooth) stored with the image
Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Text	
METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Image description	Add short note (stored in JPEG EXIF tag)
FLIR meters with METERLiNK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Sketch	
Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	METERLINK	Wireless connection (Bluetooth) to:
Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB		FLIR meters with METERLINK
Non-radiometric IR video recording WPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Report generation	Coparato i C continui o Mini exteriore report
Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video recording in camera	
Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi	Non-radiometric IR video recording	MPEG-4 to memory card
Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Visual video recording	MPEG-4 to memory card
using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video streaming	
MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi	Radiometric IR video streaming	
• WPEG-4 using Wi-Fi	Non-radiometric IR video streaming	
	Visual video streaming	

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006641
UPC-12	845188006990
Country of origin	Sweden

Supplies & accessories:

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case

- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5 \times (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.6 FLIR T600 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-1016

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.92 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up commands Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Blue-tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Storage media Removable memory SD card Image storage mode - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Pill meters with METERLINK Report generation Separate PC software with extensive report generation			
button, Reset options, Set up camera, Wi-Fi, Blue- tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Coptional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table, Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG XIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Video streaming Pull dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Set-up Set-up		
Storage of images	Set-up commands	button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera	
Storage of images Image storage Storage media Image storage mode Storage media Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file file formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi	Service functions		
Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file Optional to store digital photo as a separate JPEG file Time lapse - 15 seconds to 24 hours - File formats - Standard JPEG, measurement data included - File formats, visual - Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice - Go seconds (via Bluetooth) stored with the image Text - Add table. Select between predefined templates or create your own in FLIR Tools Image description - Add short note (stored in JPEG EXIF tag) Sketch - Draw on thermal/digital photo or add predefined stamps METERLINK - Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Camera software update	Use PC software FLIR Tools	
Storage media Removable memory SD card Removable memory SD card Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Storage of images		
Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi	Image storage		
Simultaneous storage or inermal and cigital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Storage media	Removable memory SD card	
File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Image storage mode	photo in same JPEG file. Optional to store digital photo as a separate	
File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Time lapse	15 seconds to 24 hours	
Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming Visual video streaming Visual video streaming NPEG-4 using Wi-Fi • Uncompressed colorized video using USB	File formats	Standard JPEG, measurement data included	
Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming Visual video streaming • MPEG-4 using Wi-Fi	File formats, visual		
Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Image annotations (in still images)		
create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Voice	60 seconds (via Bluetooth) stored with the image	
Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Text		
METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Image description	Add short note (stored in JPEG EXIF tag)	
FLIR meters with METERLiNK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Sketch		
Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	METERLINK	Wireless connection (Bluetooth) to:	
Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB		FLIR meters with METERLINK	
Non-radiometric IR video recording WPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Report generation	Coparato i C continui o Mini exteriore report	
Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video recording in camera		
Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi	Non-radiometric IR video recording	MPEG-4 to memory card	
Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Visual video recording	MPEG-4 to memory card	
using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video streaming		
MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi	Radiometric IR video streaming		
• WPEG-4 using Wi-Fi	Non-radiometric IR video streaming		
	Visual video streaming		

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558011874
UPC-12	845188012984
Country of origin	Sweden

Supplies & accessories:

• T197914; IR lens, f=41.3 mm (15°) with case

- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.7 FLIR T600 25° (incl. Wi-Fi)

P/N: 55903-1022

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.92 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up commands Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Blue-tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Storage media Removable memory SD card Image storage mode - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Pill meters with METERLINK Report generation Separate PC software with extensive report generation			
button, Reset options, Set up camera, Wi-Fi, Blue- tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Coptional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table, Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG XIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Video streaming Pull dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Set-up Set-up		
Storage of images	Set-up commands	button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera	
Storage of images Image storage Storage media Image storage mode Storage media Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file file formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi	Service functions		
Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file Optional to store digital photo as a separate JPEG file Time lapse - 15 seconds to 24 hours - File formats - Standard JPEG, measurement data included - File formats, visual - Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice - Go seconds (via Bluetooth) stored with the image Text - Add table. Select between predefined templates or create your own in FLIR Tools Image description - Add short note (stored in JPEG EXIF tag) Sketch - Draw on thermal/digital photo or add predefined stamps METERLINK - Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Camera software update	Use PC software FLIR Tools	
Storage media Removable memory SD card Removable memory SD card Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Storage of images		
Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi	Image storage		
Simultaneous storage or inermal and cigital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Storage media	Removable memory SD card	
File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Image storage mode	photo in same JPEG file. Optional to store digital photo as a separate	
File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Time lapse	15 seconds to 24 hours	
Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming Visual video streaming Visual video streaming NPEG-4 using Wi-Fi • Uncompressed colorized video using USB	File formats	Standard JPEG, measurement data included	
Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming Visual video streaming • MPEG-4 using Wi-Fi	File formats, visual		
Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Image annotations (in still images)		
create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Voice	60 seconds (via Bluetooth) stored with the image	
Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Text		
METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Image description	Add short note (stored in JPEG EXIF tag)	
FLIR meters with METERLiNK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Sketch		
Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	METERLINK	Wireless connection (Bluetooth) to:	
Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB		FLIR meters with METERLINK	
Non-radiometric IR video recording WPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Report generation	Coparato i C continui o Mini exteriore report	
Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video recording in camera		
Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi	Non-radiometric IR video recording	MPEG-4 to memory card	
Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Visual video recording	MPEG-4 to memory card	
using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video streaming		
MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi	Radiometric IR video streaming		
• WPEG-4 using Wi-Fi	Non-radiometric IR video streaming		
	Visual video streaming		

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006658
UPC-12	845188007003
Country of origin	Sweden

Supplies & accessories:

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case

- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5 \times (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.8 FLIR T600 25° and 15° w/case

P/N: 55903-1007

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.92 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

mage presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up commands Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Blue-tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Storage media Removable memory SD card Image storage mode - Simultaneous storage of thermal and digital photo in same JPEG file.			
button, Reset options, Set up camera, Wi-Fi, Blue- tooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Coptional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table, Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG XIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Video streaming Pull dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Set-up		
Storage of images	Set-up commands	button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera	
Storage of images Image storage Storage media Image storage mode Storage media Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file file formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi	Service functions		
Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card - Simultaneous storage of thermal and digital photo in same JPEG file Optional to store digital photo as a separate JPEG file Optional to store digital photo as a separate JPEG file Time lapse - 15 seconds to 24 hours - File formats - Standard JPEG, measurement data included - File formats, visual - Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice - Go seconds (via Bluetooth) stored with the image Text - Add table. Select between predefined templates or create your own in FLIR Tools Image description - Add short note (stored in JPEG EXIF tag) Sketch - Draw on thermal/digital photo or add predefined stamps METERLINK - Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Camera software update	Use PC software FLIR Tools	
Storage media Removable memory SD card Removable memory SD card Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB	Storage of images		
Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi **Uncompressed colorized video using USB Visual video streaming **MPEG-4 using Wi-Fi	Image storage		
Simultaneous storage or inermal and cigital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Optional to store digital photo as a separate JPEG file. Standard JPEG, measurement data included File formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Storage media	Removable memory SD card	
File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Image storage mode	photo in same JPEG file. Optional to store digital photo as a separate	
File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming - MPEG-4 using Wi-Fi - Uncompressed colorized video using USB	Time lapse	15 seconds to 24 hours	
Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming Visual video streaming Visual video streaming NPEG-4 using Wi-Fi • Uncompressed colorized video using USB	File formats	Standard JPEG, measurement data included	
Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi - Uncompressed colorized video using USB Visual video streaming Visual video streaming • MPEG-4 using Wi-Fi	File formats, visual		
Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Image annotations (in still images)		
create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Voice	60 seconds (via Bluetooth) stored with the image	
Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Text		
METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Image description	Add short note (stored in JPEG EXIF tag)	
FLIR meters with METERLiNK Report generation Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Sketch		
Report generation • Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	METERLINK	Wireless connection (Bluetooth) to:	
Separate PC software with extensive report generation Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB		FLIR meters with METERLINK	
Non-radiometric IR video recording WPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB	Report generation	Coparato i C continui o Mini exteriore report	
Visual video recording MPEG-4 to memory card Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Video recording in camera		
Video streaming Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi	Non-radiometric IR video recording	MPEG-4 to memory card	
Radiometric IR video streaming Full dynamic to PC using USB or to mobile devices using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi	Visual video recording	MPEG-4 to memory card	
using Wi-Fi. Non-radiometric IR video streaming MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi	Video streaming		
MPEG-4 using Wi-Fi Uncompressed colorized video using USB Visual video streaming MPEG-4 using Wi-Fi	Radiometric IR video streaming		
• WPEG-4 using Wi-Fi	Non-radiometric IR video streaming		
	Visual video streaming		

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system .		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=41.3 mm (15°) with case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558011843
UPC-12	845188012953
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, $f=13.1 \text{ mm } (45^{\circ})$ with case
- T198059; Close-up IR lens, 2.9× (50 μ m) with case

- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, $1.5 \times (25 \mu m)$ with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093: Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.9 FLIR T600 25° and 45° w/case

P/N: 55903-1008

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.92 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system .		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=13.1 mm (45°) with case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558011850
UPC-12	845188012960
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μ m) with case

- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, $1.5 \times (25 \mu m)$ with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093: Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.10 FLIR T600 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-1017

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.73 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system .		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558011881
UPC-12	845188012991
Country of origin	Sweden

• T197914; IR lens, f=41.3 mm (15°) with case

- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.11 FLIR T600 45° (incl. Wi-Fi)

P/N: 55903-1522

Rev.: 43545

General description

The FLIR T600 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600 allows you to connect to smart phones or tables for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.73 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Separate PC software with extensive report generation
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system .		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006665
UPC-12	845188007010
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case

- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.12 FLIR T600bx 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-2823

Rev.: 43545

General description

The FLIR T600bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.92 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +350°C (+212°F to +662°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLiNK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera			
Built-in digital camera	5 Mpixels with LED light (photo as separate image)		
Digital camera, FOV	Adapts to the IR lens		
Video lamp	Built-in LED light		
Laser pointer			
Laser	Activated by dedicated button		
Laser alignment	Position is automatic displayed on the IR image		
Laser classification	Class 2		
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)		
Data communication interfaces			
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output		
METERLiNK/Bluetooth	Communication with headset and external sensors		
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)		
SD Card	One card slot for removable SD memory cards		
USB			
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
USB, standard	USB 2.0 high speed		
Video output			
Video out	Digital video output (DVI)		
Video, connector type	HDMI compatible		
Radio			
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm		
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz		
Antenna	Internal		
Power system	Power system .		
Battery type	Rechargeable Li ion battery		
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use		
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger		
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's		
Charging temperature	0°C to +45°C (+32°F to +113°F)		
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)		

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558011898
UPC-12	845188013004
Country of origin	Sweden

• T197914; IR lens, f=41.3 mm (15°) with case

- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.13 FLIR T600bx 25° (incl. Wi-Fi)

P/N: 55903-2822

Rev.: 43545

General description

The FLIR T600bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.92 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

mage presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +350°C (+212°F to +662°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera			
Built-in digital camera	5 Mpixels with LED light (photo as separate image)		
Digital camera, FOV	Adapts to the IR lens		
Video lamp	Built-in LED light		
Laser pointer			
Laser	Activated by dedicated button		
Laser alignment	Position is automatic displayed on the IR image		
Laser classification	Class 2		
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)		
Data communication interfaces			
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output		
METERLiNK/Bluetooth	Communication with headset and external sensors		
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)		
SD Card	One card slot for removable SD memory cards		
USB			
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
USB, standard	USB 2.0 high speed		
Video output			
Video out	Digital video output (DVI)		
Video, connector type	HDMI compatible		
Radio			
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm		
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz		
Antenna	Internal		
Power system	Power system .		
Battery type	Rechargeable Li ion battery		
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use		
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger		
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's		
Charging temperature	0°C to +45°C (+32°F to +113°F)		
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)		

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006696
UPC-12	845188007041
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case

- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.14 FLIR T600bx 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-2923

Rev.: 43545

General description

The FLIR T600bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.73 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

illage presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +350°C (+212°F to +662°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558011904
UPC-12	845188013011
Country of origin	Sweden

• T197914; IR lens, f=41.3 mm (15°) with case

- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.15 FLIR T600bx 45° (incl. Wi-Fi)

P/N: 55903-2922

Rev.: 43545

General description

The FLIR T600bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 480×360 pixel infrared resolution. The FLIR T600bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T600bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T600bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.

Imaging and optical data	
IR resolution	480 × 360 pixels
UltraMax	No
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.73 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +350°C (+212°F to +662°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Separate PC software with extensive report generation	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	

Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system .		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006702
UPC-12	845188007058
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case

- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5 \times (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.16 FLIR T610 15° (incl. Wi-Fi)

P/N: 55903-8022

Rev.: 43545

General description

The FLIR T610 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T610 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T610 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T610 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming		
Non-radiometric IR video streaming		
Non-radiometric in video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz	
Antenna	Internal	
Power system Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	

Power system		
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Physical data		
Physical data Weight	1.3 kg (2.87 lb.)	
	1.3 kg (2.87 lb.) 143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Weight	, , , , , , , , , , , , , , , , , , ,	
Weight Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Weight Camera size, excl. lens (L × W × H) Tripod mounting	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC ¼"-20	
Weight Camera size, excl. lens (L × W × H) Tripod mounting Housing material	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC ¼"-20	
Weight Camera size, excl. lens (L × W × H) Tripod mounting Housing material Shipping information	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC ¼"-20 Magnesium	
Weight Camera size, excl. lens (L × W × H) Tripod mounting Housing material Shipping information Packaging, type	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC ¼"-20 Magnesium Cardboard box Infrared camera with lens Battery (2 ea.) Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter	

7332558006740

EAN-13

Shipping information	
UPC-12	845188007096
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T 199042, FLIN Nesearchin Standard 4 Opyrade (printed lice)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.17 FLIR T610 25° (incl. Wi-Fi)

P/N: 55903-3922

Rev.: 43545

General description

The FLIR T610 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T610 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T610 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T610 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Video streaming

=	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	·
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
	L.
USB	
USB USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
	USB Mini-B: Data transfer to and from PC / un-
USB	USB Mini-B: Data transfer to and from PC / un- compressed colorized video
USB, standard	USB Mini-B: Data transfer to and from PC / un- compressed colorized video
USB, standard Video output	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed
USB, standard Video output Video out	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI)
USB, standard Video output Video out Video, connector type	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI)
USB, standard Video output Video out Video, connector type Radio	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz
USB, standard Video output Video out Video, connector type Radio Wi-Fi	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
USB, standard Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz
USB, standard Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth Antenna	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz
USB, standard Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth Antenna Power system	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz Internal
USB, standard Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth Antenna Power system Battery type	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz Internal Rechargeable Li ion battery

Power system	
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)

Packaging, size

EAN-13

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

7332558006757

Shipping information	
UPC-12	845188007102
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.18 FLIR T610 45° (incl. Wi-Fi)

P/N: 55903-4022

Rev.: 43545

General description

The FLIR T610 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T610 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T610 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T610 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLiNK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming		
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated	

by LED's

Power system	
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
- Salety	_
Physical data	
,	1.3 kg (2.87 lb.)
Physical data	1.3 kg (2.87 lb.) 143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Physical data Weight	
Physical data Weight Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Physical data Weight Camera size, excl. lens (L × W × H) Tripod mounting	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC 1/4"-20
Physical data Weight Camera size, excl. lens (L × W × H) Tripod mounting Housing material	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC 1/4"-20
Physical data Weight Camera size, excl. lens (L × W × H) Tripod mounting Housing material Shipping information	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC 1/4"-20 Magnesium
Physical data Weight Camera size, excl. lens (L × W × H) Tripod mounting Housing material Shipping information Packaging, type	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) UNC 1/4"-20 Magnesium Cardboard box Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter

7332558006764

EAN-13

Shipping information	
UPC-12	845188007119
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696: FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.19 FLIR T620 15° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-5023

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
	, , , , , , , , , , , , , , , , , , , ,
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
	-

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	•
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Radio Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
	Frequency range: 2412–2462 MHz
Wi-Fi	 Frequency range: 2412–2462 MHz Max. output power: 15 dBm
Wi-Fi METERLiNK/Bluetooth	Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz
Wi-Fi METERLiNK/Bluetooth Antenna	Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz
Wi-Fi METERLiNK/Bluetooth Antenna Power system	Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz Internal

Power system
Charging time

Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Weight	1.3 kg (2.87 lb.)	
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Tripod mounting	UNC 1/4"-20	
Housing material	Magnesium	
Shipping information		
Packaging, type	Cardboard box	
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B	

6.6 kg (14.6 lb.)

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, weight

Packaging, size

Shipping information	
EAN-13	7332558011911
UPC-12	845188013028
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.20 FLIR T620 15° (incl. Wi-Fi)

P/N: 55903-5022

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLINK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-	

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated
	by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	 Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006801

Shipping information	
UPC-12	845188007157
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696: FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233: FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.21 FLIR T620 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-5125

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 camera is equipped with the innovative "Multi Spectral Dynamic Imaging (MSX)" feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
	, , , , , , , , , , , , , , , , , , , ,
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
	-

Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system	Power system	
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	

	-
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation

6.6 kg (14.6 lb.)

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, weight

Packaging, size

Shipping information	
EAN-13	7332558011928
UPC-12	845188013035
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.22 FLIR T620 25° (incl. Wi-Fi)

P/N: 55903-5122

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 camera is equipped with the innovative "Multi Spectral Dynamic Imaging (MSX)" feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.		
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Digital camera			
Built-in digital camera	5 Mpixels with LED light (photo as separate image)		
Digital camera, FOV	Adapts to the IR lens		
Video lamp	Built-in LED light		
Laser pointer			
Laser	Activated by dedicated button		
Laser alignment	Position is automatic displayed on the IR image		
Laser classification	Class 2		
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)		
Data communication interfaces			
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output		
METERLiNK/Bluetooth	Communication with headset and external sensors		
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)		
SD Card	One card slot for removable SD memory cards		
USB			
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
USB, standard	USB 2.0 high speed		
Video output			
Video out	Digital video output (DVI)		
Video, connector type	HDMI compatible		
Radio	Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 		
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz		
Antenna	Internal		
Power system			
Battery type	Rechargeable Li ion battery		
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use		
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger		

Davier avalors	
Power system	T
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006818

Shipping information	
UPC-12	845188007164
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.19251-200; SS IR Window 3 in.
- 19251-200, GO IT WINDOW 5 III
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.23 FLIR T620 25° and 15° (incl. Wi-Fi)

P/N: 55903-5123

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 camera is equipped with the innovative "Multi Spectral Dynamic Imaging (MSX)" feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	<u> </u>
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	<u> </u>
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

	,
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, 15° Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	5.7 kg (12.5 lb.)
Packaging, size	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$

2.5 h to 90 % capacity, charging status indicated

by LED's

Shipping information	
EAN-13	7332558011249
UPC-12	845188012120
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- · T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.24 FLIR T620 25° and 45° (incl. Wi-Fi)

P/N: 55903-5124

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 camera is equipped with the innovative "Multi Spectral Dynamic Imaging (MSX)" feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

	*/ *
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, 45° Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	5.7 kg (12.5 lb.)
	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$

2.5 h to 90 % capacity, charging status indicated

by LED's

Shipping information	
EAN-13	7332558011256
UPC-12	845188012137
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5x (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.25 FLIR T620 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-5223

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm			
Color Alarm (isotherm)	Above/below/interval		
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function		
Screening	Difference temperature alarm, audible		
Set-up			
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information		
Service functions			
Camera software update	Use PC software FLIR Tools		
Storage of images			
Image storage	Standard JPEG, including digital photo and measurement data, on memory card		
Storage media	Removable memory SD card		
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 		
Time lapse	15 seconds to 24 hours		
File formats	Standard JPEG, measurement data included		
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image		
Image annotations (in still images)			
Voice	60 seconds (via Bluetooth) stored with the image		
Text	Add table. Select between predefined templates or create your own in FLIR Tools		
Image description	Add short note (stored in JPEG EXIF tag)		
Sketch	Draw on thermal/digital photo or add predefined stamps		
METERLINK	Wireless connection (Bluetooth) to:		
	FLIR meters with METERLINK		
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation		
Geographic Information System	Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS		
Compass	Camera direction automatically added to every still image		
Video recording in camera			
Non-radiometric IR video recording	MPEG-4 to memory card		
Visual video recording	MPEG-4 to memory card		
	•		

Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 	
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	

	3
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B

6.6 kg (14.6 lb.)

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, weight
Packaging, size

Shipping information	
EAN-13	7332558011935
UPC-12	845188013042
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5x (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497: Large evecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100: IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.26 FLIR T620 45° (incl. Wi-Fi)

P/N: 55903-5222

Rev.: 43545

General description

The FLIR T620 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
	, , , , , , , , , , , , , , , , , , , ,
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
	-

Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 	
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	

Davier aveters	
Power system	T
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006825

Shipping information	
UPC-12	845188007171
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696: FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.27 FLIR T620bx 15° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-5623

Rev.: 43545

General description

The FLIR T620bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to: FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLINK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-	

Power system
Charging time

	by LLD 3
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	 Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter

Tripod adapter

6.6 kg (14.6 lb.)

USB cable, Std A to Mini-B

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, weight
Packaging, size

Shipping information	
EAN-13	7332558011942
UPC-12	845188013059
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.28 FLIR T620bx 15° (incl. Wi-Fi)

P/N: 55903-5622

Rev.: 43545

General description

The FLIR T620bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation

illage presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm

Screening	Difference temperature alarm, audible
Humidity alarm	1 humidity alarm, including dew point alarm
Insulation alarm	1 insulation alarm
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
	Oten dend IDEO meses ment dete in de de d
File formats	Standard JPEG, measurement data included
File formats File formats, visual	Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image
	Standard JPEG, automatically associated with cor-
File formats, visual	Standard JPEG, automatically associated with cor-
File formats, visual Image annotations (in still images)	Standard JPEG, automatically associated with corresponding thermal image
File formats, visual Image annotations (in still images) Voice	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or
File formats, visual Image annotations (in still images) Voice Text	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools
File formats, visual Image annotations (in still images) Voice Text Image description	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined
File formats, visual Image annotations (in still images) Voice Text Image description Sketch METERLiNK	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps
File formats, visual Image annotations (in still images) Voice Text Image description Sketch	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps Wireless connection (Bluetooth) to:
File formats, visual Image annotations (in still images) Voice Text Image description Sketch METERLiNK	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps Wireless connection (Bluetooth) to: FLIR meters with METERLiNK Instant Report (*.pdf file) in camera Separate PC software with extensive report
File formats, visual Image annotations (in still images) Voice Text Image description Sketch METERLINK Report generation	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps Wireless connection (Bluetooth) to: FLIR meters with METERLiNK Instant Report (*.pdf file) in camera Separate PC software with extensive report
File formats, visual Image annotations (in still images) Voice Text Image description Sketch METERLiNK Report generation Geographic Information System	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps Wireless connection (Bluetooth) to: FLIR meters with METERLiNK Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
File formats, visual Image annotations (in still images) Voice Text Image description Sketch METERLINK Report generation Geographic Information System GPS	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps Wireless connection (Bluetooth) to: FLIR meters with METERLINK Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still
File formats, visual Image annotations (in still images) Voice Text Image description Sketch METERLINK Report generation Geographic Information System GPS Compass	Standard JPEG, automatically associated with corresponding thermal image 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Add short note (stored in JPEG EXIF tag) Draw on thermal/digital photo or add predefined stamps Wireless connection (Bluetooth) to: FLIR meters with METERLINK Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLINK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-	

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006863

Shipping information	
UPC-12	845188007218
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696: FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.29 FLIR T620bx 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-5723

Rev.: 43545

General description

The FLIR T620bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation

90 procession	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	

Video streaming

video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system

Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap

Power supply, incl. multi-plugs Printed documentation Tripod adapter

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

USB cable, Std A to Mini-B

6.6 kg (14.6 lb.)

Packaging, weight Packaging, size

Shipping information	
EAN-13	7332558011959
UPC-12	845188013066
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.30 FLIR T620bx 25° (incl. Wi-Fi)

P/N: 55903-5722

Rev.: 43545

General description

The FLIR T620bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation

illage presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming

video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system		
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Weight	1.3 kg (2.87 lb.)	
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Tripod mounting	UNC 1/4"-20	
Housing material	Magnesium	
Shipping information		
Packaging, type	Cardboard box	
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B	
Packaging, weight	6.6 kg (14.6 lb.)	
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	
EAN-13	7332558006870	

Shipping information	
UPC-12	845188007225
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.19251-200; SS IR Window 3 in.
- 19251-200, GO IT WINDOW 5 III
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.31 FLIR T620bx 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55903-5823

Rev.: 43545

General description

The FLIR T620bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation

illage presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	

Video streaming

Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system

Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation

Tripod adapter

6.6 kg (14.6 lb.)

USB cable, Std A to Mini-B

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

Packaging, weight Packaging, size

Shipping information	
EAN-13	7332558011966
UPC-12	845188013073
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.32 FLIR T620bx 45° (incl. Wi-Fi)

P/N: 55903-5822

Rev.: 43545

General description

The FLIR T620bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T620bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T620bx is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T620bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function

Alarm		
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Davier aveters	
Power system	T
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006887

Shipping information	
UPC-12	845188007232
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696: FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.33 FLIR T630 15° (incl. Wi-Fi)

P/N: 55904-6222

Rev.: 43545

General description

The FLIR T630 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T630 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T630 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	5
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Video streaming		
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated	

by LED's

Power system

· · · · · · · · · · · · · · · · · · ·	
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006924

Shipping information	
UPC-12	845188007270
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.34 FLIR T630 25° (incl. Wi-Fi)

P/N: 55904-6322

Rev.: 43545

General description

The FLIR T630 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T630 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T630 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	5	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Video streaming			
Non-radiometric IR video streaming	MPEG-4 using Wi-FiUncompressed colorized video using USB		
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Digital camera			
Built-in digital camera	5 Mpixels with LED light (photo as separate image)		
Digital camera, FOV	Adapts to the IR lens		
Video lamp	Built-in LED light		
Laser pointer			
Laser	Activated by dedicated button		
Laser alignment	Position is automatic displayed on the IR image		
Laser classification	Class 2		
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)		
Data communication interfaces			
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output		
METERLiNK/Bluetooth	Communication with headset and external sensors		
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)		
SD Card	One card slot for removable SD memory cards		
USB			
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
USB, standard	USB 2.0 high speed		
Video output			
Video out	Digital video output (DVI)		
Video, connector type	HDMI compatible		
Radio			
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 		
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz		
Antenna	Internal		
Power system			
Battery type	Rechargeable Li ion battery		
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use		
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger		
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's		

Power system

Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	 Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558006931

Shipping information	
UPC-12	845188007287
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.35 FLIR T630 45° (incl. Wi-Fi)

P/N: 55904-6422

Rev.: 43545

General description

The FLIR T630 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T630 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T630 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<40 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	5	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's

Power system

Charging temperature	· · · · · · · · · · · · · · · · · · ·	
Nehicle (cable with standard plug, optional)	Charging temperature	0°C to +45°C (+32°F to +113°F)
To To To To To To To To	External power operation	· · · · · · · · · · · · · · · · · · ·
Storage temperature range	Environmental data	
Humidity (operating and storage)	Operating temperature range	-15°C to +50°C (+5°F to +122°F)
to +40°C (+77°F to +104°F) / 2 cycles EMC ETSI EN 301 489-1 (radio)	Storage temperature range	-40°C to +70°C (-40°F to +158°F)
ETSIEN 301 489-1 (radio)	Humidity (operating and storage)	
E1St B x 30 328 FCC Part 15.247 RSS-247 Issue 2 Encapsulation	EMC	 ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission)
Shock 25 g (IEC 60068-2-27)	Radio spectrum	FCC Part 15.247
Vibration 2 g (IEC 60068-2-6)	Encapsulation	IP 54 (IEC 60529)
Safety EN/UL/CSA/PSE 60950-1 Physical data Weight 1.3 kg (2.87 lb.) Camera size, excl. lens (L × W × H) 143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.) Tripod mounting UNC ¼"-20 Housing material Magnesium Shipping information Packaging, type Cardboard box List of contents Infrared camera with lens Battery (2 ea.) Homi-DVI cable Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size 495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	Shock	25 g (IEC 60068-2-27)
Physical data Weight 1.3 kg (2.87 lb.) Camera size, excl. lens (L × W × H) Tripod mounting UNC ¼"-20 Housing material Magnesium Shipping information Packaging, type Cardboard box Infrared camera with lens Battery (2 ea.) Battery (2 ea.) Battery charger Bluetooth headset Callbration certificate Printed documentation HDMI-DVI cable HADMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size 495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	Vibration	2 g (IEC 60068-2-6)
Weight	Safety	EN/UL/CSA/PSE 60950-1
Camera size, excl. lens (L × W × H) Tripod mounting UNC ¼"-20 Housing material Magnesium Shipping information Packaging, type Cardboard box List of contents Infrared camera with lens Battery (2 ea.) Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size 495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	Physical data	
Tripod mounting Housing material Magnesium Shipping information Packaging, type Cardboard box Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size 495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	Weight	1.3 kg (2.87 lb.)
Housing material Shipping information Packaging, type List of contents Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size Magnesium Magnesium Magnesium Magnesium Magnesium Advantable Lard box Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable Hard transport case Large eyecap Lens cap User Supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size	Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Shipping information Packaging, type List of contents Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Packaging, size Cardboard box Infrared camera with lens Battery (2 ea.) Bat	Tripod mounting	UNC 1/4"-20
Packaging, type List of contents Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B Packaging, weight Cardboard box Infrared camera with lens Battery (2 ea.) Battery (2	Housing material	Magnesium
List of contents • Infrared camera with lens • Battery (2 ea.) • Battery charger • Bluetooth headset • Calibration certificate • Printed documentation • HDMI-DVI cable • Hard transport case • Large eyecap • Lens cap • Memory card • Neck strap • Power supply, incl. multi-plugs • Tripod adapter • USB cable, Std A to Mini-B Packaging, weight 6.6 kg (14.6 lb.) Packaging, size	Shipping information	
• Intrared camera with lens • Battery (2 ea.) • Battery charger • Bluetooth headset • Calibration certificate • Printed documentation • HDMI-DVI cable • HDMI-HDMI cable • Hard transport case • Large eyecap • Lens cap • Memory card • Neck strap • Power supply, incl. multi-plugs • Tripod adapter • USB cable, Std A to Mini-B Packaging, weight 6.6 kg (14.6 lb.) Packaging, size	Packaging, type	Cardboard box
Packaging, size 495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)		Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
, , ,	0 0, 0	, , ,
EAN-13 7332558006948		` ,
	EAN-13	7332558006948

Shipping information	
UPC-12	845188007294
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.19251-200; SS IR Window 3 in.
- 19251-200, GO IT WINDOW 5 III
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.36 FLIR T630sc 15° (incl. Wi-Fi)

P/N: 55904-8023

Rev.: 43545

General description

The FLIR T630sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640×480 pixel infrared resolution. High accuracy and sensitivity together with streaming options make the FLIR T630sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T630sc has high accuracy and high sensitivity to accurately measure the smallest temperature differences.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T630sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T630sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen

Image presentation

image presentation	
Auto orientation	Automatic landscape or portrait
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	•
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system
Charging time

	-7
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, size

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

Shipping information	
EAN-13	7332558008737
UPC-12	845188009250
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.37 FLIR T630sc 25° (incl. Wi-Fi)

P/N: 55904-8123

Rev.: 43545

General description

The FLIR T630sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640×480 pixel infrared resolution. High accuracy and sensitivity together with streaming options make the FLIR T630sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T630sc has high accuracy and high sensitivity to accurately measure the smallest temperature differences.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T630sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T630sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen

Image presentation

image presentation	
Auto orientation	Automatic landscape or portrait
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Above/below/interval	Alarm		
Icted measurement function	Color Alarm (isotherm)	Above/below/interval	
Set-up commands Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Storage media Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse Time lapse Tis seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Measurement function alarm		
Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information Service functions	Screening	Difference temperature alarm, audible	
button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information Service functions Camera software update Use PC software FLIR Tools Storage of images Image storage Standard JPEG, including digital photo and measurement data, on memory card Storage media Removable memory SD card • Simultaneous storage of thermal and digital photo in same JPEG file. • Optional to store digital photo as a separate JPEG file. • Optional to store digital photo as a separate JPEG file. Time lapse Time lapse It is seconds to 24 hours Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Plant Report (*.pdf file) in camera • Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Set-up		
Storage of images	Set-up commands	button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units,	
Storage of images	Service functions		
Image storage Standard JPEG, including digital photo and measurement data, on memory card Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Camera software update	Use PC software FLIR Tools	
Storage media Removable memory SD card Image storage mode Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. Time lapse 15 seconds to 24 hours File formats Standard JPEG, measurement data included File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Instant Report (*.pdf file) in camera • Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Storage of images		
Image storage mode * Simultaneous storage of thermal and digital photo in same JPEG file. * Optional to store digital photo as a separate JPEG file. * Time lapse * It is seconds to 24 hours File formats * Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice * 60 seconds (via Bluetooth) stored with the image Text * Add table. Select between predefined templates or create your own in FLIR Tools Image description * Add short note (stored in JPEG EXIF tag) Sketch * Draw on thermal/digital photo or add predefined stamps METERLINK * Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation * Instant Report (*.pdf file) in camera * Separate PC software with extensive report generation Geographic Information System GPS * Location data automatically added to every still image from built-in GPS Compass * Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Image storage		
Simulaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.** Time lapse Time lapse Tile formats Standard JPEG, measurement data included Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Storage media	Removable memory SD card	
File formats File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Instant Report (*.pdf file) in camera • Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Image storage mode	photo in same JPEG file. Optional to store digital photo as a separate	
File formats, visual Standard JPEG, automatically associated with corresponding thermal image Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Time lapse	15 seconds to 24 hours	
Image annotations (in still images) Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation • Instant Report (*.pdf file) in camera • Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	File formats	Standard JPEG, measurement data included	
Voice 60 seconds (via Bluetooth) stored with the image Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	File formats, visual		
Text Add table. Select between predefined templates or create your own in FLIR Tools Image description Add short note (stored in JPEG EXIF tag) Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Image annotations (in still images)		
Create your own in FLIR Tools	Voice	60 seconds (via Bluetooth) stored with the image	
Sketch Draw on thermal/digital photo or add predefined stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Text		
stamps METERLINK Wireless connection (Bluetooth) to: FLIR meters with METERLINK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Image description	Add short note (stored in JPEG EXIF tag)	
FLIR meters with METERLiNK Report generation Instant Report (*.pdf file) in camera Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Sketch	•	
Report generation • Instant Report (*.pdf file) in camera • Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	METERLINK	Wireless connection (Bluetooth) to:	
Separate PC software with extensive report generation Geographic Information System GPS Location data automatically added to every still image from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card		FLIR meters with METERLINK	
GPS Location data automatically added to every still image from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Report generation	Separate PC software with extensive report	
age from built-in GPS Compass Camera direction automatically added to every still image Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	Geographic Information System		
Video recording in camera Non-radiometric IR video recording MPEG-4 to memory card	GPS		
Non-radiometric IR video recording MPEG-4 to memory card	Compass	1 .	
, ,	Video recording in camera		
Visual video recording MPEG-4 to memory card	Non-radiometric IR video recording	MPEG-4 to memory card	
	Visual video recording	MPEG-4 to memory card	

Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system
Charging time

Charging temperature

External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)

2.5 h to 90 % capacity, charging status indicated

0°C to +45°C (+32°F to +113°F)

by LED's

Shipping information	
EAN-13	7332558008713
UPC-12	845188009236
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.38 FLIR T630sc 25° and 45° w/case

P/N: 55904-8124

Rev.: 43545

General description

The FLIR T630sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640×480 pixel infrared resolution. High accuracy and sensitivity together with streaming options make the FLIR T630sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T630sc has high accuracy and high sensitivity to accurately measure the smallest temperature differences.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T630sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T630sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen

Image presentation

mage procentation	
Auto orientation	Automatic landscape or portrait
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLiNK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

_		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=13.1 mm (45°) with case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558012062

Shipping information	
UPC-12	845188013165
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.39 FLIR T630sc 45° (incl. Wi-Fi)

P/N: 55904-8223

Rev.: 43545

General description

The FLIR T630sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640×480 pixel infrared resolution. High accuracy and sensitivity together with streaming options make the FLIR T630sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T630sc has high accuracy and high sensitivity to accurately measure the smallest temperature differences.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T630sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T630sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual
Digital zoom	1-4× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen

Image presentation

Auto orientation	Automatic landscape or portrait	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	tunner that the second	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 	
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	

Power system
Charging time

	-,
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, size

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

Shipping information	
EAN-13	7332558008744
UPC-12	845188009267
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.40 FLIR T640 15° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-6823

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 2^{\circ} C$ ($\pm 3.6^{\circ} F)$ or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-FiUncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device
	USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB Mini-B: Data transfer to and from PC / un-
USB, standard Video output	USB Mini-B: Data transfer to and from PC / un- compressed colorized video
	USB Mini-B: Data transfer to and from PC / un- compressed colorized video
Video output	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed
Video output Video out	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI)
Video output Video out Video, connector type	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI)
Video output Video out Video, connector type Radio	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz
Video output Video out Video, connector type Radio Wi-Fi	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz
Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth Antenna	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz
Video output Video out Video, connector type Radio Wi-Fi METERLiNK/Bluetooth Antenna Power system	USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm Frequency range: 2402–2480 MHz Internal

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)

Shipping information	
Packaging, size	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$
EAN-13	7332558011973
UPC-12	845188013080
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8x (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)

- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.41 FLIR T640 15° (incl. Wi-Fi)

P/N: 55904-6822

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 2^{\circ} C$ ($\pm 3.6^{\circ} F)$ or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-

Power system
Charging time

	,	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Weight	1.3 kg (2.87 lb.)	
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Tripod mounting	UNC 1/4"-20	
Housing material	Magnesium	
Shipping information		
Packaging, type	Cardboard box	
List of contents	Infrared camera with lens Battery (2 ea.) Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B	
Packaging, weight	6.6 kg (14.6 lb.)	

2.5 h to 90 % capacity, charging status indicated

by LED's

Packaging, size

 $495\times192\times370$ mm (19.49 \times 7.56 \times 14.57 in.)

Shipping information	
EAN-13	7332558006986
UPC-12	845188007331
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.42 FLIR T640 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-6925

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
	Duth is 900 400 shalls
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
· · · · · · · · · · · · · · · · · · ·		

Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	<u> </u>
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	<u> </u>
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system		
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2 	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Weight	1.3 kg (2.87 lb.)	
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Tripod mounting	UNC 1/4"-20	
Housing material	Magnesium	
Shipping information		
Packaging, type	Cardboard box	
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B	
Packaging, weight	6.6 kg (14.6 lb.)	

Shipping information	
Packaging, size	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$
EAN-13	7332558011980
UPC-12	845188013097
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
 T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)

- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.43 FLIR T640 25° (incl. Wi-Fi)

P/N: 55904-6922

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	 Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
	•

using Wi-Fi. Non-radiometric IR video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Digital camera Built-in digital camera 5 Mpixels with LED light (photo as separate image built-in digital camera, FOV Adapts to the IR lens Video lamp Built-in LED light Laser pointer Laser Activated by dedicated button Laser alignment Position is automatic displayed on the IR image classification Class 2 Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 mm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensor One card slot for removable SD memory cards USB USB • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard Video output Video output Video output Digital video output (DVI) HDMI compatible Radio Wi-Fi • Standard: 802.11 b/g • Frequency range: 2412–2462 MHz • Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery type Battery type Battery type Battery type Battery type Battery type Battery operating time > 2.5 shours at 25°C (+88°F) and typical use Charging system	video sireanning	
Visual video streaming Visual video streaming Visual video streaming • MPEG-4 using Wi-Fi • Uncompressed colorized video using USB Digital camera Built-in digital camera 5 Mpixels with LED light (photo as separate image Digital camera, FOV Adapts to the IR lens Video lamp Built-in LED light Laser pointer Laser Activated by dedicated button Laser alignment Position is automatic displayed on the IR image Laser alignment Position is automatic displayed on the IR image Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Video output Video output Video, connector type HDMI compatible Radio Wi-Fi • Standard: 802.11 b/g • Frequency range: 2412–2462 MHz • Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz • Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz • Internal Power system Battery type Battery type Battery type Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system	Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Digital camera Built-in digital camera Built-in digital camera Digital camera, FOV Adapts to the IR lens Video lamp Built-in LED light Laser pointer Laser Laser alignment Laser alignment Laser lassification Class 2 Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Wi-Fi Peer to peer (ad hoc) or infrastructure (network) Data Communication USB USB USB USB USB USB USB US	Non-radiometric IR video streaming	· ·
Built-in digital camera	Visual video streaming	
Digital camera, FOV Video lamp Built-in LED light Laser pointer Laser Activated by dedicated button Laser alignment Position is automatic displayed on the IR image Laser classification Class 2 Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLiNK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video output Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Digital camera	
Built-in LED light	Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Laser pointer Laser Activated by dedicated button Laser alignment Position is automatic displayed on the IR image Laser classification Class 2 Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB USB-A: Connect external USB device USB Johigh speed Video output Video output Video output Video output Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Digital camera, FOV	Adapts to the IR lens
Laser alignment Position is automatic displayed on the IR image Laser classification Class 2 Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB. 2.0 high speed Video output Video output Video output Video, connector type HDMI compatible Radio Wi-Fi • Standard: 802.11 b/g • Frequency range: 2412–2462 MHz • Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Video lamp	Built-in LED light
Laser alignment Laser classification Class 2 Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB USB USB USB USB USB USB US	Laser pointer	
Laser classification Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLiNK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video output Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Laser	Activated by dedicated button
Laser type Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) Data communication interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Laser alignment	Position is automatic displayed on the IR image
Interfaces Interfaces Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery S2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Laser classification	Class 2
Interfaces USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery S2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Laser type	
Output METERLINK/Bluetooth Communication with headset and external sensors Wi-Fi Peer to peer (ad hoc) or infrastructure (network) SD Card One card slot for removable SD memory cards USB USB USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLINK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery S2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Data communication interfaces	
Wi-Fi Peer to peer (ad hoc) or infrastructure (network) Decard One card slot for removable SD memory cards USB USB USB USB A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Interfaces	
SD Card One card slot for removable SD memory cards USB USB USB	METERLiNK/Bluetooth	Communication with headset and external sensors
USB USB USB	Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
USB -A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	SD Card	One card slot for removable SD memory cards
USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB, standard USB 2.0 high speed Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	USB	
Video output Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi • Standard: 802.11 b/g • Frequency range: 2412–2462 MHz • Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	USB	USB Mini-B: Data transfer to and from PC / un-
Video out Digital video output (DVI) Video, connector type HDMI compatible Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	USB, standard	USB 2.0 high speed
Video, connector type Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Video output	
Radio Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Video out	Digital video output (DVI)
Wi-Fi Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Video, connector type	HDMI compatible
Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm METERLiNK/Bluetooth Frequency range: 2402–2480 MHz Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Radio	
Antenna Internal Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Wi-Fi	Frequency range: 2412–2462 MHz
Power system Battery type Rechargeable Li ion battery Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Battery type Rechargeable Li ion battery > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Antenna	Internal
Battery operating time > 2.5 hours at 25°C (+68°F) and typical use Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Power system Power system	
Charging system In camera (AC adapter or 12 V from a vehicle) or 2	Battery type	Rechargeable Li ion battery
	Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
bay charger	Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system
Charging time

Charging temperature

External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	 ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm } (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)

2.5 h to 90 % capacity, charging status indicated

0°C to +45°C (+32°F to +113°F)

by LED's

Shipping information	
EAN-13	7332558006993
UPC-12	845188007348
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- · T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.44 FLIR T640 25° and 15° (incl. Wi-Fi)

P/N: 55904-6923

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 2^{\circ} C$ ($\pm 3.6^{\circ} F)$ or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, 15° Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	5.7 kg (12.6 lb.)

Shipping information	
Packaging, size	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$
EAN-13	7332558011263
UPC-12	845188012144
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
 T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)

- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.45 FLIR T640 25° and 45° (incl. Wi-Fi)

P/N: 55904-6924

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Built-in 800 × 480 pixels
Built-in 800 × 480 pixels
Continuous, histogram based
Linear based; possible to adjust level/span/max./ min.
Full-color IR image
Full color visual image
Thermal image with enhanced detail presentation
Resizable and movable IR area on visual image
-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
$\pm 2^{\circ}\text{C} \ (\pm 3.6^{\circ}\text{F})$ or 2%, whichever is greater, at 25°C (77°F) nominal.
10
5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
1 line profile with max/min temp
Auto hot or cold spotmeter markers within area and profile
No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Delta temperature between measurement functions or reference temperature
Manually set using difference temperature
Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Automatic, based on signals from internal sensors
Variable from 0.01 to 1.0 or selected from materials list
Emissivity table of predefined materials
Automatic, based on input of reflected temperature
Automatic, based on inputs of window transmission and temperature
Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	•
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	 Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, 45° Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	5.7 kg (12.6 lb.)

Shipping information	
Packaging, size	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$
EAN-13	7332558011270
UPC-12	845188012151
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)

- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.46 FLIR T640 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-7023

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot,

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	
Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 	
METERLiNK/Bluetooth	Frequency range: 2402-2480 MHz	
Antenna	Internal	
Power system Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	

Power system	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium
Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)

Shipping information	
Packaging, size	$495 \times 192 \times 370 \text{ mm} (19.49 \times 7.56 \times 14.57 \text{ in.})$
EAN-13	7332558011997
UPC-12	845188013103
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, $2.9 \times (50 \mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)

- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.47 FLIR T640 45° (incl. Wi-Fi)

P/N: 55904-7022

Rev.: 43545

General description

The FLIR T640 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640 is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)	
Accuracy	$\pm 2^{\circ} C$ ($\pm 3.6^{\circ} F)$ or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Profile	1 line profile with max/min temp	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	

Video streaming

Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.		
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Digital camera			
Built-in digital camera	5 Mpixels with LED light (photo as separate image)		
Digital camera, FOV	Adapts to the IR lens		
Video lamp	Built-in LED light		
Laser pointer			
Laser	Activated by dedicated button		
Laser alignment	Position is automatic displayed on the IR image		
Laser classification	Class 2		
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)		
Data communication interfaces			
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output		
METERLiNK/Bluetooth	Communication with headset and external sensors		
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)		
SD Card	One card slot for removable SD memory cards		
USB			
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
USB, standard	USB 2.0 high speed		
Video output			
Video out	Digital video output (DVI)		
Video, connector type	HDMI compatible		
Radio	Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 		
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz		
Antenna	Internal		
Power system			
Battery type	Rechargeable Li ion battery		
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use		
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger		

Power system
Charging time

Charging temperature

External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Weight	1.3 kg (2.87 lb.)	
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Tripod mounting	UNC 1/4"-20	
Housing material	Magnesium	
Shipping information		
Packaging, type	Cardboard box	
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B	
Packaging, weight	6.6 kg (14.6 lb.)	
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	

2.5 h to 90 % capacity, charging status indicated

0°C to +45°C (+32°F to +113°F)

by LED's

Shipping information	
EAN-13	7332558007006
UPC-12	845188007355
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065: IR lens. f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- · T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.48 FLIR T640bx 15° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-7423

Rev.: 43545

General description

The FLIR T640bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640bx is equipped with the innovative
 Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640bx the first fully automatic infrared camera on the
 market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen

Image presentation	
	Tax extra
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	

Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal

Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143\times195\times95$ mm (5.6 \times 7.7 \times 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558012000
UPC-12	845188013110
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.49 FLIR T640bx 15° (incl. Wi-Fi)

P/N: 55904-7422

Rev.: 43545

General description

The FLIR T640bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640bx is equipped with the innovative
 Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640bx the first fully automatic infrared camera on the
 market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen

Image presentation	
	Taller of the second
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	

Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal

Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm} (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558007051
UPC-12	845188007393
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.

- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.50 FLIR T640bx 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-7523

Rev.: 43545

General description

The FLIR T640bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640bx is equipped with the innovative
 Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640bx the first fully automatic infrared camera on the
 market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen

Image presentation	
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement func- tions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Humidity alarm	1 humidity alarm, including dew point alarm
Insulation alarm	1 insulation alarm
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation
Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image

Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal

Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data		
	Weight	1.3 kg (2.87 lb.)
	Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm} (5.6 \times 7.7 \times 3.7 \text{ in.})$
	Tripod mounting	UNC 1/4"-20
	Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558012017
UPC-12	845188013127

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 $\mu m)$ with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, $1.5 \times (25 \mu m)$ with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100: IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.

- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.51 FLIR T640bx 25° (incl. Wi-Fi)

P/N: 55904-7522

Rev.: 43545

General description

The FLIR T640bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640bx is equipped with the innovative
 Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640bx the first fully automatic infrared camera on the
 market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen

Image presentation		
	Tax extra	
Auto orientation	Automatic landscape or portrait	
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)	
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Profile	1 line profile with max/min temp	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	

Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
Interfaces METERLiNK/Bluetooth		
	Output	
METERLiNK/Bluetooth	Output Communication with headset and external sensors	
METERLiNK/Bluetooth Wi-Fi	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
METERLiNK/Bluetooth Wi-Fi SD Card	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
METERLiNK/Bluetooth Wi-Fi SD Card	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-	
METERLINK/Bluetooth Wi-Fi SD Card USB USB	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard Video output	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	
METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB Video output Video out	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	
METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB Video output Video out Video, connector type	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	
METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB Video output Video out Video, connector type Radio	Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible • Standard: 802.11 b/g • Frequency range: 2412–2462 MHz	

Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

	Physical data	
	Weight	1.3 kg (2.87 lb.)
	Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm} (5.6 \times 7.7 \times 3.7 \text{ in.})$
	Tripod mounting	UNC 1/4"-20
	Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558007068
UPC-12	845188007409

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 $\mu m)$ with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen

- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
 T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.52 FLIR T640bx 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-7623

Rev.: 43545

General description

The FLIR T640bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640bx is equipped with the innovative
 Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640bx the first fully automatic infrared camera on the
 market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

lmaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen

Image presentation	
	Tax extra
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	

Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible
Radio	
Wi-Fi	Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal

ower system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

	Physical data	
	Weight	1.3 kg (2.87 lb.)
	Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm} (5.6 \times 7.7 \times 3.7 \text{ in.})$
	Tripod mounting	UNC 1/4"-20
	Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558012031
UPC-12	845188013134
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.53 FLIR T640bx 45° (incl. Wi-Fi)

P/N: 55904-7622

Rev.: 43545

General description

The FLIR T640bx is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T640bx is flexible and can meet your every need, and has extensive communication options.

- Highest performance with the latest technology: The FLIR T640bx is equipped with the innovative
 Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T640bx the first fully automatic infrared camera on the
 market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640bx allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen

Image presentation	
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F)
Accuracy	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement func- tions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava

Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Humidity alarm	1 humidity alarm, including dew point alarm	
Insulation alarm	1 insulation alarm	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	
Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	

Video recording in camera		
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635	
	nm (red)	
Data communication interfaces	nm (red)	
Data communication interfaces Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
Interfaces METERLiNK/Bluetooth	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors	
Interfaces METERLiNK/Bluetooth Wi-Fi	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard Video output Video out	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB Video output Video out Video, connector type	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	
Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB, standard Video output Video out Video, connector type Radio	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed Digital video output (DVI) HDMI compatible • Standard: 802.11 b/g • Frequency range: 2412–2462 MHz	

Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)

Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328 FCC Part 15.247 RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1

Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	$143 \times 195 \times 95 \text{ mm} (5.6 \times 7.7 \times 3.7 \text{ in.})$
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558007075
UPC-12	845188007416
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.

- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.54 FLIR T650sc 15° (incl. Wi-Fi)

P/N: 55904-7723

Rev.: 43545

General description

The FLIR T650sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640 × 480 pixel infrared resolution. High accuracy and sensitivity together with radiometric recording and streaming options make the FLIR T650sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T650sc has high accuracy and high sensitivity
 to accurately measure the smallest temperature differences. With real-time radiometric recording by
 the camera, it is possible to capture fast events on an SD card for further analysis by the supplied
 analysis software.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T650sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T650sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the T650sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.

Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image

Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 1^{\circ}\text{C}$ ($\pm 1.8^{\circ}\text{F}$) or $\pm 1\%$ of reading for limited temperature range for measuring object within +5°C to +120°C (+41°F to +248 °F) and ambient temperatures of +10°C to +35°C (+49°F to +95°F). This is only valid for the temperature range -40°C to +120°C (-40°F to +248°F).

Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

		
Measurement analysis		
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	
Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	

	Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Radiometric IR video recording	CSQ to memory card	
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
1		
Laser classification	Class 2	
Laser classification Laser type	Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
	Semiconductor AlGaInP diode laser, 1 mW, 635	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635	
Laser type Data communication interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video	
Data communication interfaces Interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors	
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-	
Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed	

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.95 kg (15.3 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558007082
UPC-12	845188007423
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.55 FLIR T650sc 25° (incl. Wi-Fi)

P/N: 55904-7823

Rev.: 43545

General description

The FLIR T650sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640 × 480 pixel infrared resolution. High accuracy and sensitivity together with radiometric recording and streaming options make the FLIR T650sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T650sc has high accuracy and high sensitivity
 to accurately measure the smallest temperature differences. With real-time radiometric recording by
 the camera, it is possible to capture fast events on an SD card for further analysis by the supplied
 analysis software.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T650sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T650sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the T650sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels	
Capacitive touch screen	
Automatic landscape or portrait	
Built-in 800 × 480 pixels	
Continuous, histogram based	
Linear based; possible to adjust level/span/max./ min.	

Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image

Measurement	
Object temperature range	- 40°C to +150°C (-40°F to +302°F) - +100°C to +650°C (+212°F to +1202°F) - +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 1^{\circ}$ C ($\pm 1.8^{\circ}$ F) or $\pm 1\%$ of reading for limited temperature range for measuring object within +5°C to +120°C (+ 41° F to +248°F) and ambient temperatures of +10°C to +35°C (+49°F to +95°F). This is only valid for the temperature range -40°C to +120°C (-40°F to +248°F).

Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

Measurement analysis		
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	
Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	 Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file. 	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	

Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Radiometric IR video recording	CSQ to memory card	
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output	Video output	
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.95 kg (15.3 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558007099
UPC-12	845188007430
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.56 FLIR T650sc 25° and 15° w/case

P/N: 55904-7824

Rev.: 43545

General description

The FLIR T650sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640 × 480 pixel infrared resolution. High accuracy and sensitivity together with radiometric recording and streaming options make the FLIR T650sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T650sc has high accuracy and high sensitivity
 to accurately measure the smallest temperature differences. With real-time radiometric recording by
 the camera, it is possible to capture fast events on an SD card for further analysis by the supplied
 analysis software.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T650sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T650sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the T650sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels	
Capacitive touch screen	
Automatic landscape or portrait	
Built-in 800 × 480 pixels	
Continuous, histogram based	
Linear based; possible to adjust level/span/max./ min.	

Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image

Measurement	
Object temperature range	- 40°C to +150°C (-40°F to +302°F) - +100°C to +650°C (+212°F to +1202°F) - +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 1^{\circ}\text{C}$ ($\pm 1.8^{\circ}\text{F}$) or $\pm 1\%$ of reading for limited temperature range for measuring object within +5°C to +120°C (+41°F to +248 °F) and ambient temperatures of +10°C to +35°C (+49°F to +95°F). This is only valid for the temperature range -40°C to +120°C (-40°F to +248°F).

Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

Measurement analysis	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Radiometric IR video recording	CSQ to memory card
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser pointer Laser	Activated by dedicated button
•	Activated by dedicated button Position is automatic displayed on the IR image
Laser	·
Laser Laser alignment	Position is automatic displayed on the IR image
Laser Laser alignment Laser classification	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635
Laser Laser alignment Laser classification Laser type	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635
Laser Laser alignment Laser classification Laser type Data communication interfaces	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB USB, standard	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	 Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=41.3 mm (15°) with case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558012048
UPC-12	845188013141
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μ m) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, $1.5 \times$ (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen

- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NETT199234; FLIR Atlas SDK for MATLAB

24.57 FLIR T650sc 25° and 45° w/case

P/N: 55904-7825

Rev.: 43545

General description

The FLIR T650sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640×480 pixel infrared resolution. High accuracy and sensitivity together with radiometric recording and streaming options make the FLIR T650sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T650sc has high accuracy and high sensitivity
 to accurately measure the smallest temperature differences. With real-time radiometric recording by
 the camera, it is possible to capture fast events on an SD card for further analysis by the supplied
 analysis software.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T650sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T650sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the T650sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	

Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image

Measurement	
Object temperature range	- 40°C to +150°C (-40°F to +302°F) - +100°C to +650°C (+212°F to +1202°F) - +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 1^{\circ}\text{C}$ ($\pm 1.8^{\circ}\text{F}$) or $\pm 1\%$ of reading for limited temperature range for measuring object within +5°C to +120°C (+41°F to +248 °F) and ambient temperatures of +10°C to +35°C (+49°F to +95°F). This is only valid for the temperature range -40°C to +120°C (-40°F to +248°F).

Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

Measurement analysis	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Radiometric IR video recording	CSQ to memory card
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
1	
Laser classification	Class 2
Laser classification Laser type	Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
	Semiconductor AlGaInP diode laser, 1 mW, 635
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635
Laser type Data communication interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video
Data communication interfaces Interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-
Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=13.1 mm (45°) with case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558012055
UPC-12	845188013158
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μ m) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, $1.5 \times$ (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen

- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.58 FLIR T650sc 45° (incl. Wi-Fi)

P/N: 55904-7923

Rev.: 43545

General description

The FLIR T650sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640 × 480 pixel infrared resolution. High accuracy and sensitivity together with radiometric recording and streaming options make the FLIR T650sc well suited for advanced research and development.

- Tailor made for research and development: The FLIR T650sc has high accuracy and high sensitivity
 to accurately measure the smallest temperature differences. With real-time radiometric recording by
 the camera, it is possible to capture fast events on an SD card for further analysis by the supplied
 analysis software.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T650sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before.
 Continuous auto-focus makes the FLIR T650sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the T650sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels	
Capacitive touch screen	
Automatic landscape or portrait	
Built-in 800 × 480 pixels	
Continuous, histogram based	
Linear based; possible to adjust level/span/max./ min.	

Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image

Measurement	
Object temperature range	- 40°C to +150°C (-40°F to +302°F) - +100°C to +650°C (+212°F to +1202°F) - +300°C to +2000°C (+572°F to +3632°F)
Accuracy	$\pm 1^{\circ}\text{C}$ ($\pm 1.8^{\circ}\text{F}$) or $\pm 1\%$ of reading for limited temperature range for measuring object within +5°C to +120°C (+41°F to +248 °F) and ambient temperatures of +10°C to +35°C (+49°F to +95°F). This is only valid for the temperature range -40°C to +120°C (-40°F to +248°F).

Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

Measurement analysis		
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	
Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to: FLIR meters with METERLiNK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	

	Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS		
Compass	Camera direction automatically added to every still image		
Video recording in camera			
Radiometric IR video recording	CSQ to memory card		
Non-radiometric IR video recording	MPEG-4 to memory card		
Visual video recording	MPEG-4 to memory card		
Video streaming	Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.		
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB		
Digital camera			
Built-in digital camera	5 Mpixels with LED light (photo as separate image)		
Digital camera, FOV	Adapts to the IR lens		
Video lamp	Built-in LED light		
Laser pointer			
Laser	Activated by dedicated button		
Laser alignment	Position is automatic displayed on the IR image		
1			
Laser classification	Class 2		
Laser classification Laser type	Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)		
	Semiconductor AlGaInP diode laser, 1 mW, 635		
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635		
Laser type Data communication interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video		
Data communication interfaces Interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output		
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors		
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)		
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)		
Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-		
Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video		
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed		

Radio		
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm 	
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz	
Antenna	Internal	
Power system		
Battery type	Rechargeable Li ion battery	
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use	
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger	
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's	
Charging temperature	0°C to +45°C (+32°F to +113°F)	
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)	
Environmental data		
Operating temperature range	-15°C to +50°C (+5°F to +122°F)	
Storage temperature range	-40°C to +70°C (-40°F to +158°F)	
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles	
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003 	
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2	
Encapsulation	IP 54 (IEC 60529)	
Shock	25 g (IEC 60068-2-27)	
Vibration	2 g (IEC 60068-2-6)	
Safety	EN/UL/CSA/PSE 60950-1	
Physical data		
Weight	1.3 kg (2.87 lb.)	
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)	
Tripod mounting	UNC 1/4"-20	

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate FLIR ResearchIR Max 4 Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.95 kg (15.3 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558007105
UPC-12	845188007447
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4 (hardware sec. dev.)
- T199014; FLIR ResearchIR Max + HSDR 4 (printed license key)
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade (printed license key)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- T198731; FLIR ResearchIR Standard 4 (hardware sec. dev.)
- T199012; FLIR ResearchIR Standard 4 (printed license key)
- T199042; FLIR ResearchIR Standard 4 Upgrade (printed license key)
- . T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.59 FLIR T660 15° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-8423

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T660 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)	
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal. 	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Profile	1 line profile with max/min temp	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	

Measurement analysis	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Radiometric IR video recording	CSQ to memory card
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLINK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558012079
UPC-12	845188013172
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.60 FLIR T660 15° (incl. Wi-Fi)

P/N: 55904-8422

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T660 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	15° × 11°
Minimum focus distance	0.5 m (1.64 ft.)
Focal length	41 mm (1.63 in.)
Spatial resolution (IFOV)	0.41 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)	
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal. 	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Profile	1 line profile with max/min temp	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	

Measurement analysis	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Radiometric IR video recording	CSQ to memory card	
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser pointer Laser	Activated by dedicated button	
•	Activated by dedicated button Position is automatic displayed on the IR image	
Laser	·	
Laser Laser alignment	Position is automatic displayed on the IR image	
Laser Laser alignment Laser classification	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635	
Laser Laser alignment Laser classification Laser type	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635	
Laser Laser alignment Laser classification Laser type Data communication interfaces	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB USB, standard	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558008751
UPC-12	845188009274
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.

- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.61 FLIR T660 25° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-8523

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1-8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature

Measurement analysis	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Radiometric IR video recording	CSQ to memory card
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
1	
Laser classification	Class 2
Laser classification Laser type	Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
	Semiconductor AlGaInP diode laser, 1 mW, 635
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635
Laser type Data communication interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video
Data communication interfaces Interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-
Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558012086
UPC-12	845188013189
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.62 FLIR T660 25° (incl. Wi-Fi)

P/N: 55904-8522

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1-8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature

Measurement analysis	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Radiometric IR video recording	CSQ to memory card
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
1	
Laser classification	Class 2
Laser classification Laser type	Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
	Semiconductor AlGaInP diode laser, 1 mW, 635
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635
Laser type Data communication interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video
Data communication interfaces Interfaces	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)
Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-
Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video
Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB USB USB USB, standard	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video USB 2.0 high speed

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558008720
UPC-12	845188009243
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.

- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.63 FLIR T660 25° and 15° w/case

P/N: 55904-8524

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	 -40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F) 	
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal. 	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Profile	1 line profile with max/min temp	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta	
Difference temperature	Delta temperature between measurement func- tions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	

Measurement analysis	
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to:
	FLIR meters with METERLINK
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation

Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Radiometric IR video recording	CSQ to memory card	
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=41.3 mm (15°) with case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558012093
UPC-12	845188013196
Country of origin	Sweden

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen

- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.64 FLIR T660 25° and 45° w/case

P/N: 55904-8525

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T640 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	25° × 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1-8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature

Measurement analysis		
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	
Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	

Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Radiometric IR video recording	CSQ to memory card	
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser pointer Laser	Activated by dedicated button	
•	Activated by dedicated button Position is automatic displayed on the IR image	
Laser	·	
Laser Laser alignment	Position is automatic displayed on the IR image	
Laser Laser alignment Laser classification	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635	
Laser Laser alignment Laser classification Laser type	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635	
Laser Laser alignment Laser classification Laser type Data communication interfaces	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network)	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLiNK/Bluetooth Wi-Fi SD Card USB	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / un-	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
Laser Laser alignment Laser classification Laser type Data communication interfaces Interfaces METERLINK/Bluetooth Wi-Fi SD Card USB USB USB, standard	Position is automatic displayed on the IR image Class 2 Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red) USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output Communication with headset and external sensors Peer to peer (ad hoc) or infrastructure (network) One card slot for removable SD memory cards • USB-A: Connect external USB device • USB Mini-B: Data transfer to and from PC / uncompressed colorized video	

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case IR lens, f=13.1 mm (45°) with case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
EAN-13	7332558012109
UPC-12	845188013202
Country of origin	Sweden

Supplies & accessories:

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μ m) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen

- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.65 FLIR T660 45° (incl. Wi-Fi and Ext. cal.)

P/N: 55904-8623

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

Benefits

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T660 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation	
Viewfinder	Built-in 800 × 480 pixels
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.
Measurement analysis	
Spotmeter	10
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)
Profile	1 line profile with max/min temp
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/profiles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature

Measurement analysis		
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation	
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava	
Alarm		
Color Alarm (isotherm)	Above/below/interval	
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function	
Screening	Difference temperature alarm, audible	
Set-up		
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information	
Service functions		
Camera software update	Use PC software FLIR Tools	
Storage of images		
Image storage	Standard JPEG, including digital photo and measurement data, on memory card	
Storage media	Removable memory SD card	
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.	
Time lapse	15 seconds to 24 hours	
File formats	Standard JPEG, measurement data included	
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image	
Image annotations (in still images)		
Voice	60 seconds (via Bluetooth) stored with the image	
Text	Add table. Select between predefined templates or create your own in FLIR Tools	
Image description	Add short note (stored in JPEG EXIF tag)	
Sketch	Draw on thermal/digital photo or add predefined stamps	
METERLINK	Wireless connection (Bluetooth) to:	
	FLIR meters with METERLINK	
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation	

Geographic Information System		
GPS	Location data automatically added to every still image from built-in GPS	
Compass	Camera direction automatically added to every still image	
Video recording in camera		
Radiometric IR video recording	CSQ to memory card	
Non-radiometric IR video recording	MPEG-4 to memory card	
Visual video recording	MPEG-4 to memory card	
Video streaming		
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.	
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Visual video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB	
Digital camera		
Built-in digital camera	5 Mpixels with LED light (photo as separate image)	
Digital camera, FOV	Adapts to the IR lens	
Video lamp	Built-in LED light	
Laser pointer		
Laser	Activated by dedicated button	
Laser alignment	Position is automatic displayed on the IR image	
Laser classification	Class 2	
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)	
Data communication interfaces		
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output	
METERLiNK/Bluetooth	Communication with headset and external sensors	
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)	
SD Card	One card slot for removable SD memory cards	
USB		
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video	
USB, standard	USB 2.0 high speed	
Video output		
Video out	Digital video output (DVI)	
Video, connector type	HDMI compatible	

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Magnesium

Housing material

Shipping information	
Packaging, type	Cardboard box
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Extended calibration certificate HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Printed documentation Tripod adapter USB cable, Std A to Mini-B
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558012116
UPC-12	845188013219
Country of origin	Sweden

Supplies & accessories:

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, 5.8× (100 μm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.

- 19252-200; SS IR Window 4 in.
- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

24.66 FLIR T660 45° (incl. Wi-Fi)

P/N: 55904-8622

Rev.: 43545

General description

The FLIR T660 is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and a walk-up-and-use interface with superior image quality of 640×480 pixel infrared resolution. The FLIR T660 is flexible and can meet your every need.

Benefits:

- Highest performance with the latest technology: The FLIR T660 is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T660 the first fully automatic infrared camera on the market.
- Ground-breaking efficiency: You can highlight objects of interest, on both the infrared and the visual
 images, by sketching or adding predefined stamps directly onto the camera's capacitive touch screen.
 The user interface is intuitive and logical for effective operation. Auto-orientation allows you to tilt between landscape and portrait views.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T660 allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLiNK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

Imaging and optical data	
IR resolution	640 × 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<20 mK @ +30°C (+86°F)
Field of view (FOV)	45° × 34°
Minimum focus distance	0.15 m (0.49 ft.)
Focal length	13 mm (0.52 in.)
Spatial resolution (IFOV)	1.30 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Continuous, one shot or manual
Digital zoom	1–8× continuous
Digital image enhancement	Adaptive digital noise reduction

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 μm
Detector pitch	17 μm

Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 \times 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait

Image presentation		
Viewfinder	Built-in 800 × 480 pixels	
Automatic image adjustment	Continuous, histogram based	
Manual image adjustment	Linear based; possible to adjust level/span/max./ min.	
Image presentation modes		
Infrared image	Full-color IR image	
Visual image	Full color visual image	
Thermal MSX	Thermal image with enhanced detail presentation	
Picture in Picture	Resizable and movable IR area on visual image	
Measurement		
Object temperature range	-40°C to +150°C (-40°F to +302°F) +100°C to +650°C (+212°F to +1202°F) +300°C to +2000°C (+572°F to +3632°F)	
Accuracy	 ±1°C (±1.8°F) or ±1% of reading for limited temperature range. ±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal. 	
Measurement analysis		
Spotmeter	10	
Area	5 + 5 areas (boxes or circles) with max./min./average (in post-acquisition analysis)	
Profile	1 line profile with max/min temp	
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area and profile	
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2	
User presets (in live images)	The user can select and combine measurements from any number of available spots/boxes/circles/ profiles/delta	
Difference temperature	Delta temperature between measurement functions or reference temperature	
Reference temperature	Manually set using difference temperature	
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity	
Optics transmission correction	Automatic, based on signals from internal sensors	
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list	
Emissivity table	Emissivity table of predefined materials	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature	
External optics/windows correction	Automatic, based on inputs of window transmission and temperature	

Measurement analysis			
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation		
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava		
Alarm			
Color Alarm (isotherm)	Above/below/interval		
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function		
Screening	Difference temperature alarm, audible		
Set-up			
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information		
Service functions			
Camera software update	Use PC software FLIR Tools		
Storage of images			
Image storage	Standard JPEG, including digital photo and measurement data, on memory card		
Storage media	Removable memory SD card		
Image storage mode	Simultaneous storage of thermal and digital photo in same JPEG file. Optional to store digital photo as a separate JPEG file.		
Time lapse	15 seconds to 24 hours		
File formats	Standard JPEG, measurement data included		
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image		
Image annotations (in still images)			
Voice	60 seconds (via Bluetooth) stored with the image		
Text	Add table. Select between predefined templates or create your own in FLIR Tools		
Image description	Add short note (stored in JPEG EXIF tag)		
Sketch	Draw on thermal/digital photo or add predefined stamps		
METERLINK	Wireless connection (Bluetooth) to:		
	FLIR meters with METERLINK		
Report generation	Instant Report (*.pdf file) in camera Separate PC software with extensive report generation		

Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Radiometric IR video recording	CSQ to memory card
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	MPEG-4 using Wi-Fi Uncompressed colorized video using USB
Visual video streaming	MPEG-4 using Wi-FiUncompressed colorized video using USB
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	USB-A: Connect external USB device USB Mini-B: Data transfer to and from PC / uncompressed colorized video
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible

Radio	
Wi-Fi	 Standard: 802.11 b/g Frequency range: 2412–2462 MHz Max. output power: 15 dBm
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	 ETSI EN 301 489-1 (radio) ETSI EN 301 489-17 EN 61000-6-2 (Immunity) EN 61000-6-3 (Emission) FCC 47 CFR Part 15 Class B (Emission) ICES-003
Radio spectrum	ETSI EN 300 328FCC Part 15.247RSS-247 Issue 2
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens $(L \times W \times H)$	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20

Magnesium

Housing material

Shipping information		
Packaging, type	Cardboard box	
List of contents	Infrared camera with lens Battery (2 ea.) Battery charger Bluetooth headset Calibration certificate Printed documentation HDMI-DVI cable HDMI-HDMI cable Hard transport case Large eyecap Lens cap Memory card Neck strap Power supply, incl. multi-plugs Tripod adapter USB cable, Std A to Mini-B	
Packaging, weight	6.6 kg (14.6 lb.)	
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)	
EAN-13	7332558008768	
UPC-12	845188009281	
Country of origin	Sweden	

Supplies & accessories:


- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9× (50 μm) with case
- T198060; Close-up IR lens, $5.8 \times (100 \mu m)$ with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5× (25 μm) with case
- T197896; High temperature option +300°C to 2000°C (+572°F to 3632°F)
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T199406ACC; Battery Li-ion 3.7 V, 7.8 Ah, 29 Wh
- T911650ACC; Memory card SD Card 8 GB
- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case
- T198495; Pouch
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100: IR Window 2 in
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.


- T198496; Stylus pen
- T198586; FLIR Reporter Professional (license only)
- T198584; FLIR Tools
- T198583; FLIR Tools+ (download card incl. license key)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T199233; FLIR Atlas SDK for .NET
- T199234; FLIR Atlas SDK for MATLAB

25

Mechanical drawings


[See next page]






© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.




© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.




© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.




© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.




© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.




© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.



© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.



© 2012, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmittlen permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values, Products may be subject to regional market considerations. License procedures may apply.

Product may be subject to US Export Regulations. Please refer to exportingentialing any questions. Diversion contrary to US law is prohibited.

26

CE Declaration of conformity

[See next page]



August 02, 2017 Täby, Sweden AQ320250

CE Declaration of Conformity - EU Declaration of Conformity

Product: FLIR T6XX -series

Name and address of the manufacturer:

FLIR Systems AB PO Box 7376

SE-187 15 Täby, Sweden

This declaration of conformity is issued under the sole responsibility of the manufacturer.

The object of the declaration: FLIR T6XX -series (Product Model Name FLIR-T5590).

The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:

Di	re	ct	iv	es

Directive	2014/30/EU	Electromagnetic Compability
Directive	2014/35/EU	Low Voltage Directive
Directive	2012/19/EU	Waste electrical and electric equipment
Directive	2014/53/EU	Radio Equipment Directive (RED)
Directive	1999/519/EC	Limitation of exposure to electromagnetic fields (SAR)
Directive	2011/65/EU	RoHS and 2015/830/EU (Phtalates)

Standards:		
Emission:	EN 61000-6-3:2007	EMC – Generic standards
Immunity:	EN 61000-6-2:2005	Electromagnetic Compability Generic
	EN 301489-1:2008 v1.8.0	ERM – EMC for radio equipment
	EN 301489-17:2009 v2.1.1	ERM – EMC Wideband data
Laser:	EN 60825-1	Safety of laser products
Radio:	ETSI EN 300 328 v2.1.1	Harmonized EN covering essential
		requirements of the R&TTE Directive
	ETSI EN 301 893 v.2.1.1	5GHz WLAN
SAR:	EN 50360:2001/A1:2012	Human exposure (300 MHz – 3 GHz)
	EN 50566:2013/AC:2014	Handheld general public (30 MHz – 6 GHz)

Information technology equipment

EN 60950-1:2006+A11:2009+A1:2010

Technical documentation **RoHS** EN 50581:2012

IEC 60950-1:2005+A1:2009+

FLIR Systems AB Quality Assurance

ca Dolm

Lea Dabiri

Safety:

Quality Manager

Cleaning the camera

27.1 Camera housing, cables, and other items

27.1.1 Liquids

Use one of these liquids:

- · Warm water
- · A weak detergent solution

27.1.2 Equipment

A soft cloth

27.1.3 Procedure

Follow this procedure:

- 1. Soak the cloth in the liquid.
- 2. Twist the cloth to remove excess liquid.
- 3. Clean the part with the cloth.



CAUTION

Do not apply solvents or similar liquids to the camera, the cables, or other items. This can cause damage.

27.2 Infrared lens

27.2.1 Liquids

Use one of these liquids:

- A commercial lens cleaning liquid with more than 30% isopropyl alcohol.
- 96% ethyl alcohol (C₂H₅OH).

27.2.2 Equipment

Cotton wool



CAUTION

If you use a lens cleaning cloth it must be dry. Do not use a lens cleaning cloth with the liquids that are given in section 27.2.1 above. These liquids can cause material on the lens cleaning cloth to become loose. This material can have an unwanted effect on the surface of the lens.

27.2.3 Procedure

Follow this procedure:

- 1. Soak the cotton wool in the liquid.
- 2. Twist the cotton wool to remove excess liquid.
- 3. Clean the lens one time only and discard the cotton wool.



WARNING

Make sure that you read all applicable MSDS (Material Safety Data Sheets) and warning labels on containers before you use a liquid: the liquids can be dangerous.



CAUTION

- Be careful when you clean the infrared lens. The lens has a delicate anti-reflective coating.
- · Do not clean the infrared lens too vigorously. This can damage the anti-reflective coating.

27.3 Infrared detector

27.3.1 General

Even small amounts of dust on the infrared detector can result in major blemishes in the image. To remove any dust from the detector, follow the procedure below.

Note

- This section only applies to cameras where removing the lens exposes the infrared detector
- In some cases the dust cannot be removed by following this procedure: the infrared detector must be cleaned mechanically. This mechanical cleaning must be carried out by an authorized service partner.



CAUTION

In Step 2 below, do not use pressurized air from pneumatic air circuits in a workshop, etc., as this air usually contains oil mist to lubricate pneumatic tools.

27.3.2 Procedure

Follow this procedure:

- 1. Remove the lens from the camera.
- 2. Use pressurized air from a compressed air canister to blow off the dust.

Application examples

28.1 Moisture & water damage

28.1.1 General

It is often possible to detect moisture and water damage in a house by using an infrared camera. This is partly because the damaged area has a different heat conduction property and partly because it has a different thermal capacity to store heat than the surrounding material.

Many factors can come into play as to how moisture or water damage will appear in an infrared image.

For example, heating and cooling of these parts takes place at different rates depending on the material and the time of day. For this reason, it is important that other methods are used as well to check for moisture or water damage.

28.1.2 Figure

The image below shows extensive water damage on an external wall where the water has penetrated the outer facing because of an incorrectly installed window ledge.



28.2 Faulty contact in socket

28.2.1 General


Depending on the type of connection a socket has, an improperly connected wire can result in local temperature increase. This temperature increase is caused by the reduced contact area between the connection point of the incoming wire and the socket, and can result in an electrical fire.

A socket's construction may differ dramatically from one manufacturer to another. For this reason, different faults in a socket can lead to the same typical appearance in an infrared image.

Local temperature increase can also result from improper contact between wire and socket, or from difference in load.

28.2.2 Figure

The image below shows a connection of a cable to a socket where improper contact in the connection has resulted in local temperature increase.



28.3 Oxidized socket

28.3.1 General


Depending on the type of socket and the environment in which the socket is installed, oxides may occur on the socket's contact surfaces. These oxides can lead to locally increased resistance when the socket is loaded, which can be seen in an infrared image as local temperature increase.

A socket's construction may differ dramatically from one manufacturer to another. For this reason, different faults in a socket can lead to the same typical appearance in an infrared image.

Local temperature increase can also result from improper contact between a wire and socket, or from difference in load.

28.3.2 Figure

The image below shows a series of fuses where one fuse has a raised temperature on the contact surfaces against the fuse holder. Because of the fuse holder's blank metal, the temperature increase is not visible there, while it is visible on the fuse's ceramic material.



28.4 Insulation deficiencies

28.4.1 General


Insulation deficiencies may result from insulation losing volume over the course of time and thereby not entirely filling the cavity in a frame wall.

An infrared camera allows you to see these insulation deficiencies because they either have a different heat conduction property than sections with correctly installed insulation, and/or show the area where air is penetrating the frame of the building.

When you are inspecting a building, the temperature difference between the inside and outside should be at least 10°C (18°F). Studs, water pipes, concrete columns, and similar components may resemble an insulation deficiency in an infrared image. Minor differences may also occur naturally.

28.4.2 Figure

In the image below, insulation in the roof framing is lacking. Due to the absence of insulation, air has forced its way into the roof structure, which thus takes on a different characteristic appearance in the infrared image.



28.5 Draft

28.5.1 General

Draft can be found under baseboards, around door and window casings, and above ceiling trim. This type of draft is often possible to see with an infrared camera, as a cooler air-stream cools down the surrounding surface.


When you are investigating draft in a house, there should be sub-atmospheric pressure in the house. Close all doors, windows, and ventilation ducts, and allow the kitchen fan to run for a while before you take the infrared images.

An infrared image of draft often shows a typical stream pattern. You can see this stream pattern clearly in the picture below.

Also keep in mind that drafts can be concealed by heat from floor heating circuits.

28.5.2 Figure

The image below shows a ceiling hatch where faulty installation has resulted in a strong draft.



About FLIR Systems

FLIR Systems was established in 1978 to pioneer the development of high-performance infrared imaging systems, and is the world leader in the design, manufacture, and marketing of thermal imaging systems for a wide variety of commercial, industrial, and government applications. Today, FLIR Systems embraces five major companies with outstanding achievements in infrared technology since 1958—the Swedish AGEMA Infrared Systems (formerly AGA Infrared Systems), the three United States companies Indigo Systems, FSI, and Inframetrics, and the French company Cedip.

Since 2007, FLIR Systems has acquired several companies with world-leading expertise in sensor technologies:

- Extech Instruments (2007)
- Ifara Tecnologías (2008)
- Salvador Imaging (2009)
- OmniTech Partners (2009)
- Directed Perception (2009)
- Raymarine (2010)
- ICx Technologies (2010)
- TackTick Marine Digital Instruments (2011)
- Aerius Photonics (2011)
- Lorex Technology (2012)
- Traficon (2012)
- MARSS (2013)
- DigitalOptics micro-optics business (2013)
- DVTEL (2015)
- Point Grey Research (2016)
- Prox Dynamics (2016)




Figure 29.1 Patent documents from the early 1960s

FLIR Systems has three manufacturing plants in the United States (Portland, OR, Boston, MA, Santa Barbara, CA) and one in Sweden (Stockholm). Since 2007 there is also a

manufacturing plant in Tallinn, Estonia. Direct sales offices in Belgium, Brazil, China, France, Germany, Great Britain, Hong Kong, Italy, Japan, Korea, Sweden, and the USA—together with a worldwide network of agents and distributors—support our international customer base.

FLIR Systems is at the forefront of innovation in the infrared camera industry. We anticipate market demand by constantly improving our existing cameras and developing new ones. The company has set milestones in product design and development such as the introduction of the first battery-operated portable camera for industrial inspections, and the first uncooled infrared camera, to mention just two innovations.




Figure 29.2 1969: Thermovision Model 661. The camera weighed approximately 25 kg (55 lb.), the oscilloscope 20 kg (44 lb.), and the tripod 15 kg (33 lb.). The operator also needed a 220 VAC generator set, and a 10 L (2.6 US gallon) jar with liquid nitrogen. To the left of the oscilloscope the Polaroid attachment (6 kg (13 lb.)) can be seen.



Figure 29.3 2015: FLIR One, an accessory to iPhone and Android mobile phones. Weight: 90 g (3.2 oz.).

FLIR Systems manufactures all vital mechanical and electronic components of the camera systems itself. From detector design and manufacturing, to lenses and system electronics, to final testing and calibration, all production steps are carried out and supervised by our own engineers. The in-depth expertise of these infrared specialists ensures the accuracy and reliability of all vital components that are assembled into your infrared camera.

29.1 More than just an infrared camera

At FLIR Systems we recognize that our job is to go beyond just producing the best infrared camera systems. We are committed to enabling all users of our infrared camera systems to work more productively by providing them with the most powerful camera–software combination. Especially tailored software for predictive maintenance, R & D, and process monitoring is developed in-house. Most software is available in a wide variety of languages.

We support all our infrared cameras with a wide variety of accessories to adapt your equipment to the most demanding infrared applications.

29.2 Sharing our knowledge

Although our cameras are designed to be very user-friendly, there is a lot more to thermography than just knowing how to handle a camera. Therefore, FLIR Systems has founded the Infrared Training Center (ITC), a separate business unit, that provides certified training courses. Attending one of the ITC courses will give you a truly hands-on learning experience.

The staff of the ITC are also there to provide you with any application support you may need in putting infrared theory into practice.

29.3 Supporting our customers

FLIR Systems operates a worldwide service network to keep your camera running at all times. If you discover a problem with your camera, local service centers have all the equipment and expertise to solve it within the shortest possible time. Therefore, there is no need to send your camera to the other side of the world or to talk to someone who does not speak your language.

Terms, laws, and definitions

Term	Definition
Absorption and emission ²	The capacity or ability of an object to absorb incident radiated energy is always the same as the capacity to emit its own energy as radiation
Apparent temperature	uncompensated reading from an infrared instrument, containing all radiation incident on the instrument, regardless of its sources ³
Color palette	assigns different colors to indicate specific levels of apparent temperature. Palettes can provide high or low contrast, depending on the colors used in them
Conduction	direct transfer of thermal energy from molecule to molecule, caused by collisions between the molecules
Convection	heat transfer mode where a fluid is brought into motion, either by gravity or another force, thereby transferring heat from one place to another
Diagnostics	examination of symptoms and syndromes to determine the nature of faults or failures ⁴
Direction of heat transfer ⁵	Heat will spontaneously flow from hotter to colder, thereby transferring thermal energy from one place to another ⁶
Emissivity	ratio of the power radiated by real bodies to the power that is radiated by a blackbody at the same temperature and at the same wavelength ⁷
Energy conservation ⁸	The sum of the total energy contents in a closed system is constant
Exitant radiation	radiation that leaves the surface of an object, regardless of its original sources
Heat	thermal energy that is transferred between two objects (systems) due to their difference in temperature
Heat transfer rate ⁹	The heat transfer rate under steady state conditions is directly proportional to the thermal conductivity of the object, the cross-sectional area of the object through which the heat flows, and the temperature difference between the two ends of the object. It is inversely proportional to the length, or thickness, of the object ¹⁰
Incident radiation	radiation that strikes an object from its surroundings
IR thermography	process of acquisition and analysis of thermal information from non-contact thermal imaging devices
Isotherm	replaces certain colors in the scale with a contrasting color. It marks an interval of equal apparent temperature ¹¹

^{2.} Kirchhoff's law of thermal radiation.

^{3.} Based on ISO 18434-1:2008 (en).

^{4.} Based on ISO 13372:2004 (en).

^{5. 2}nd law of thermodynamics.

^{6.} This is a consequence of the 2nd law of thermodynamics, the law itself is more complicated.

^{7.} Based on ISO 16714-3:2016 (en).

^{8. 1}st law of thermodynamics.

^{9.} Fourier's law.

^{10.} This is the one-dimensional form of Fourier's law, valid for steady-state conditions.

^{11.} Based on ISO 18434-1:2008 (en)

Term	Definition
Qualitative thermography	thermography that relies on the analysis of thermal patterns to reveal the existence of and to locate the position of anomalies ¹²
Quantitative thermography	thermography that uses temperature measurement to determine the seriousness of an anomaly, in order to establish repair priorities ¹²
Radiative heat transfer	Heat transfer by the emission and absorption of thermal radiation
Reflected apparent temperature	apparent temperature of the environment that is reflected by the target into the IR camera ¹³
Spatial resolution	ability of an IR camera to resolve small objects or details
Temperature	measure of the average kinetic energy of the molecules and atoms that make up the substance
Thermal energy	total kinetic energy of the molecules that make up the object14
Thermal gradient	gradual change in temperature over distance ¹³
Thermal tuning	process of putting the colors of the image on the object of analysis, in order to maximize contrast

^{12.} Based on ISO 10878-2013 (en).

^{13.} Based on ISO 16714-3:2016 (en).

^{14.} Thermal energy is part of the internal energy of an object.

Thermographic measurement techniques

31.1 Introduction

An infrared camera measures and images the emitted infrared radiation from an object. The fact that radiation is a function of object surface temperature makes it possible for the camera to calculate and display this temperature.

However, the radiation measured by the camera does not only depend on the temperature of the object but is also a function of the emissivity. Radiation also originates from the surroundings and is reflected in the object. The radiation from the object and the reflected radiation will also be influenced by the absorption of the atmosphere.

To measure temperature accurately, it is therefore necessary to compensate for the effects of a number of different radiation sources. This is done on-line automatically by the camera. The following object parameters must, however, be supplied for the camera:

- · The emissivity of the object
- The reflected apparent temperature
- The distance between the object and the camera
- · The relative humidity
- · Temperature of the atmosphere

31.2 Emissivity

The most important object parameter to set correctly is the emissivity which, in short, is a measure of how much radiation is emitted from the object, compared to that from a perfect blackbody of the same temperature.

Normally, object materials and surface treatments exhibit emissivity ranging from approximately 0.1 to 0.95. A highly polished (mirror) surface falls below 0.1, while an oxidized or painted surface has a higher emissivity. Oil-based paint, regardless of color in the visible spectrum, has an emissivity over 0.9 in the infrared. Human skin exhibits an emissivity 0.97 to 0.98.

Non-oxidized metals represent an extreme case of perfect opacity and high reflexivity, which does not vary greatly with wavelength. Consequently, the emissivity of metals is low – only increasing with temperature. For non-metals, emissivity tends to be high, and decreases with temperature.

31.2.1 Finding the emissivity of a sample

31.2.1.1 Step 1: Determining reflected apparent temperature

Use one of the following two methods to determine reflected apparent temperature:

31.2.1.1.1 Method 1: Direct method

Follow this procedure:

1. Look for possible reflection sources, considering that the incident angle = reflection angle (a = b).




Figure 31.1 1 = Reflection source

2. If the reflection source is a spot source, modify the source by obstructing it using a piece if cardboard.




Figure 31.2 1 = Reflection source

- 3. Measure the radiation intensity (= apparent temperature) from the reflection source using the following settings:
 - Emissivity: 1.0
 - D_{obj}: 0

You can measure the radiation intensity using one of the following two methods:




Figure 31.3 1 = Reflection source

Figure 31.4 1 = Reflection source

You can not use a thermocouple to measure reflected apparent temperature, because a thermocouple measures *temperature*, but apparent temperature is *radiation intensity*.

31.2.1.1.2 Method 2: Reflector method

Follow this procedure:

- 1. Crumble up a large piece of aluminum foil.
- 2. Uncrumble the aluminum foil and attach it to a piece of cardboard of the same size.
- 3. Put the piece of cardboard in front of the object you want to measure. Make sure that the side with aluminum foil points to the camera.
- 4. Set the emissivity to 1.0.

5. Measure the apparent temperature of the aluminum foil and write it down. The foil is considered a perfect reflector, so its apparent temperature equals the reflected apparent temperature from the surroundings.




Figure 31.5 Measuring the apparent temperature of the aluminum foil.

31.2.1.2 Step 2: Determining the emissivity

Follow this procedure:

- 1. Select a place to put the sample.
- Determine and set reflected apparent temperature according to the previous procedure.
- 3. Put a piece of electrical tape with known high emissivity on the sample.
- 4. Heat the sample at least 20 K above room temperature. Heating must be reasonably
- 5. Focus and auto-adjust the camera, and freeze the image.
- 6. Adjust Level and Span for best image brightness and contrast.
- 7. Set emissivity to that of the tape (usually 0.97).
- 8. Measure the temperature of the tape using one of the following measurement functions:
 - *Isotherm* (helps you to determine both the temperature and how evenly you have heated the sample)
 - Spot (simpler)
 - Box Avg (good for surfaces with varying emissivity).
- 9. Write down the temperature.
- 10. Move your measurement function to the sample surface.
- 11. Change the emissivity setting until you read the same temperature as your previous measurement.
- 12. Write down the emissivity.

Note

- · Avoid forced convection
- Look for a thermally stable surrounding that will not generate spot reflections
- Use high quality tape that you know is not transparent, and has a high emissivity you are certain of
- This method assumes that the temperature of your tape and the sample surface are the same. If they are not, your emissivity measurement will be wrong.

31.3 Reflected apparent temperature

This parameter is used to compensate for the radiation reflected in the object. If the emissivity is low and the object temperature relatively far from that of the reflected it will be important to set and compensate for the reflected apparent temperature correctly.

31.4 Distance

The distance is the distance between the object and the front lens of the camera. This parameter is used to compensate for the following two facts:

- That radiation from the target is absorbed by the atmosphere between the object and the camera.
- · That radiation from the atmosphere itself is detected by the camera.

31.5 Relative humidity

The camera can also compensate for the fact that the transmittance is also dependent on the relative humidity of the atmosphere. To do this set the relative humidity to the correct value. For short distances and normal humidity the relative humidity can normally be left at a default value of 50%.

31.6 Other parameters

In addition, some cameras and analysis programs from FLIR Systems allow you to compensate for the following parameters:

- Atmospheric temperature i.e. the temperature of the atmosphere between the camera and the target
- External optics temperature i.e. the temperature of any external lenses or windows used in front of the camera
- External optics transmittance i.e. the transmission of any external lenses or windows
 used in front of the camera

History of infrared technology

Before the year 1800, the existence of the infrared portion of the electromagnetic spectrum wasn't even suspected. The original significance of the infrared spectrum, or simply 'the infrared' as it is often called, as a form of heat radiation is perhaps less obvious today than it was at the time of its discovery by Herschel in 1800.



Figure 32.1 Sir William Herschel (1738-1822)

The discovery was made accidentally during the search for a new optical material. Sir William Herschel – Royal Astronomer to King George III of England, and already famous for his discovery of the planet Uranus – was searching for an optical filter material to reduce the brightness of the sun's image in telescopes during solar observations. While testing different samples of colored glass which gave similar reductions in brightness he was intrigued to find that some of the samples passed very little of the sun's heat, while others passed so much heat that he risked eye damage after only a few seconds' observation.

Herschel was soon convinced of the necessity of setting up a systematic experiment, with the objective of finding a single material that would give the desired reduction in brightness as well as the maximum reduction in heat. He began the experiment by actually repeating Newton's prism experiment, but looking for the heating effect rather than the visual distribution of intensity in the spectrum. He first blackened the bulb of a sensitive mercury-inglass thermometer with ink, and with this as his radiation detector he proceeded to test the heating effect of the various colors of the spectrum formed on the top of a table by passing sunlight through a glass prism. Other thermometers, placed outside the sun's rays, served as controls.

As the blackened thermometer was moved slowly along the colors of the spectrum, the temperature readings showed a steady increase from the violet end to the red end. This was not entirely unexpected, since the Italian researcher, Landriani, in a similar experiment in 1777 had observed much the same effect. It was Herschel, however, who was the first to recognize that there must be a point where the heating effect reaches a maximum, and that measurements confined to the visible portion of the spectrum failed to locate this point.



Figure 32.2 Marsilio Landriani (1746-1815)

Moving the thermometer into the dark region beyond the red end of the spectrum, Herschel confirmed that the heating continued to increase. The maximum point, when he found it, lay well beyond the red end – in what is known today as the 'infrared wavelengths'.

When Herschel revealed his discovery, he referred to this new portion of the electromagnetic spectrum as the 'thermometrical spectrum'. The radiation itself he sometimes referred to as 'dark heat', or simply 'the invisible rays'. Ironically, and contrary to popular opinion, it wasn't Herschel who originated the term 'infrared'. The word only began to appear in print around 75 years later, and it is still unclear who should receive credit as the originator.

Herschel's use of glass in the prism of his original experiment led to some early controversies with his contemporaries about the actual existence of the infrared wavelengths. Different investigators, in attempting to confirm his work, used various types of glass indiscriminately, having different transparencies in the infrared. Through his later experiments, Herschel was aware of the limited transparency of glass to the newly-discovered thermal radiation, and he was forced to conclude that optics for the infrared would probably be doomed to the use of reflective elements exclusively (i.e. plane and curved mirrors). Fortunately, this proved to be true only until 1830, when the Italian investigator, Melloni, made his great discovery that naturally occurring rock salt (NaCl) – which was available in large enough natural crystals to be made into lenses and prisms – is remarkably transparent to the infrared. The result was that rock salt became the principal infrared optical material, and remained so for the next hundred years, until the art of synthetic crystal growing was mastered in the 1930's.



Figure 32.3 Macedonio Melloni (1798-1854)

Thermometers, as radiation detectors, remained unchallenged until 1829, the year Nobili invented the thermocouple. (Herschel's own thermometer could be read to $0.2\,^{\circ}\text{C}$ ($0.036\,^{\circ}$ F), and later models were able to be read to $0.05\,^{\circ}\text{C}$ ($0.09\,^{\circ}\text{F}$)). Then a breakthrough occurred; Melloni connected a number of thermocouples in series to form the first thermopile. The new device was at least 40 times as sensitive as the best thermometer of the day for detecting heat radiation – capable of detecting the heat from a person standing three meters away.

The first so-called 'heat-picture' became possible in 1840, the result of work by Sir John Herschel, son of the discoverer of the infrared and a famous astronomer in his own right. Based upon the differential evaporation of a thin film of oil when exposed to a heat pattern focused upon it, the thermal image could be seen by reflected light where the interference effects of the oil film made the image visible to the eye. Sir John also managed to obtain a primitive record of the thermal image on paper, which he called a 'thermograph'.



Figure 32.4 Samuel P. Langley (1834-1906)

The improvement of infrared-detector sensitivity progressed slowly. Another major breakthrough, made by Langley in 1880, was the invention of the bolometer. This consisted of a thin blackened strip of platinum connected in one arm of a Wheatstone bridge circuit upon which the infrared radiation was focused and to which a sensitive galvanometer responded. This instrument is said to have been able to detect the heat from a cow at a distance of 400 meters.

An English scientist, Sir James Dewar, first introduced the use of liquefied gases as cooling agents (such as liquid nitrogen with a temperature of –196°C (–320.8°F)) in low temperature research. In 1892 he invented a unique vacuum insulating container in which it is possible to store liquefied gases for entire days. The common 'thermos bottle', used for storing hot and cold drinks, is based upon his invention.

Between the years 1900 and 1920, the inventors of the world 'discovered' the infrared. Many patents were issued for devices to detect personnel, artillery, aircraft, ships – and even icebergs. The first operating systems, in the modern sense, began to be developed during the 1914–18 war, when both sides had research programs devoted to the military exploitation of the infrared. These programs included experimental systems for enemy intrusion/detection, remote temperature sensing, secure communications, and 'flying torpedo' guidance. An infrared search system tested during this period was able to detect an approaching airplane at a distance of 1.5 km (0.94 miles), or a person more than 300 meters (984 ft.) away.

The most sensitive systems up to this time were all based upon variations of the bolometer idea, but the period between the two wars saw the development of two revolutionary new infrared detectors: the image converter and the photon detector. At first, the image converter received the greatest attention by the military, because it enabled an observer for the first time in history to literally 'see in the dark'. However, the sensitivity of the image converter was limited to the near infrared wavelengths, and the most interesting military targets (i.e. enemy soldiers) had to be illuminated by infrared search beams. Since this involved the risk of giving away the observer's position to a similarly-equipped enemy observer, it is understandable that military interest in the image converter eventually faded.

The tactical military disadvantages of so-called 'active' (i.e. search beam-equipped) thermal imaging systems provided impetus following the 1939–45 war for extensive secret military infrared-research programs into the possibilities of developing 'passive' (no search beam) systems around the extremely sensitive photon detector. During this period, military secrecy regulations completely prevented disclosure of the status of infrared-imaging technology. This secrecy only began to be lifted in the middle of the 1950's, and from that time adequate thermal-imaging devices finally began to be available to civilian science and industry.

Theory of thermography

33.1 Introduction

The subjects of infrared radiation and the related technique of thermography are still new to many who will use an infrared camera. In this section the theory behind thermography will be given.

33.2 The electromagnetic spectrum

The electromagnetic spectrum is divided arbitrarily into a number of wavelength regions, called *bands*, distinguished by the methods used to produce and detect the radiation. There is no fundamental difference between radiation in the different bands of the electromagnetic spectrum. They are all governed by the same laws and the only differences are those due to differences in wavelength.




Figure 33.1 The electromagnetic spectrum. 1: X-ray; 2: UV; 3: Visible; 4: IR; 5: Microwaves; 6: Radiowaves.

Thermography makes use of the infrared spectral band. At the short-wavelength end the boundary lies at the limit of visual perception, in the deep red. At the long-wavelength end it merges with the microwave radio wavelengths, in the millimeter range.

The infrared band is often further subdivided into four smaller bands, the boundaries of which are also arbitrarily chosen. They include: the *near infrared* (0.75–3 μ m), the *middle infrared* (3–6 μ m), the *far infrared* (6–15 μ m) and the *extreme infrared* (15–100 μ m). Although the wavelengths are given in μ m (micrometers), other units are often still used to measure wavelength in this spectral region, *e.g.* nanometer (nm) and Ångström (Å).

The relationships between the different wavelength measurements is:

$$10\ 000\ \text{Å} = 1\ 000\ \text{nm} = 1\ \mu = 1\ \mu\text{m}$$

33.3 Blackbody radiation

A blackbody is defined as an object which absorbs all radiation that impinges on it at any wavelength. The apparent misnomer *black* relating to an object emitting radiation is explained by Kirchhoff's Law (after *Gustav Robert Kirchhoff*, 1824–1887), which states that a body capable of absorbing all radiation at any wavelength is equally capable in the emission of radiation.



Figure 33.2 Gustav Robert Kirchhoff (1824-1887)

The construction of a blackbody source is, in principle, very simple. The radiation characteristics of an aperture in an isotherm cavity made of an opaque absorbing material represents almost exactly the properties of a blackbody. A practical application of the principle to the construction of a perfect absorber of radiation consists of a box that is light tight except for an aperture in one of the sides. Any radiation which then enters the hole is scattered and absorbed by repeated reflections so only an infinitesimal fraction can possibly escape. The blackness which is obtained at the aperture is nearly equal to a blackbody and almost perfect for all wavelengths.

By providing such an isothermal cavity with a suitable heater it becomes what is termed a *cavity radiator*. An isothermal cavity heated to a uniform temperature generates blackbody radiation, the characteristics of which are determined solely by the temperature of the cavity. Such cavity radiators are commonly used as sources of radiation in temperature reference standards in the laboratory for calibrating thermographic instruments, such as a FLIR Systems camera for example.

If the temperature of blackbody radiation increases to more than 525°C (977°F), the source begins to be visible so that it appears to the eye no longer black. This is the incipient red heat temperature of the radiator, which then becomes orange or yellow as the temperature increases further. In fact, the definition of the so-called *color temperature* of an object is the temperature to which a blackbody would have to be heated to have the same appearance.

Now consider three expressions that describe the radiation emitted from a blackbody.

33.3.1 Planck's law



Figure 33.3 Max Planck (1858-1947)

Max Planck (1858–1947) was able to describe the spectral distribution of the radiation from a blackbody by means of the following formula:

$$W_{\lambda b} = rac{2\pi hc^2}{\lambda^5 \left(e^{hc/\lambda kT}-1
ight)}\! imes\!10^{-6}[Watt\,/\,m^2,\mu m]$$

where:

W _{λb}	Blackbody spectral radiant emittance at wavelength λ.
С	Velocity of light = 3 × 108 m/s
h	Planck's constant = 6.6×10^{-34} Joule sec.
k	Boltzmann's constant = 1.4 × 10 ⁻²³ Joule/K.
Т	Absolute temperature (K) of a blackbody.
λ	Wavelength (μm).

Note The factor 10^{-6} is used since spectral emittance in the curves is expressed in Watt/ m^2 , μm .

Planck's formula, when plotted graphically for various temperatures, produces a family of curves. Following any particular Planck curve, the spectral emittance is zero at $\lambda=0$, then increases rapidly to a maximum at a wavelength λ_{max} and after passing it approaches zero again at very long wavelengths. The higher the temperature, the shorter the wavelength at which maximum occurs.




Figure 33.4 Blackbody spectral radiant emittance according to Planck's law, plotted for various absolute temperatures. 1: Spectral radiant emittance (W/cm² \times 10³(μ m)); 2: Wavelength (μ m)

33.3.2 Wien's displacement law

By differentiating Planck's formula with respect to λ , and finding the maximum, we have:

$$\lambda_{\max} = \frac{2898}{T} [\mu m]$$

This is Wien's formula (after *Wilhelm Wien*, 1864–1928), which expresses mathematically the common observation that colors vary from red to orange or yellow as the temperature of a thermal radiator increases. The wavelength of the color is the same as the wavelength calculated for λ_{max} . A good approximation of the value of λ_{max} for a given blackbody temperature is obtained by applying the rule-of-thumb 3 000/T μm . Thus, a very hot star such as Sirius (11 000 K), emitting bluish-white light, radiates with the peak of spectral radiant emittance occurring within the invisible ultraviolet spectrum, at wavelength 0.27 μm .



Figure 33.5 Wilhelm Wien (1864–1928)

The sun (approx. 6 000 K) emits yellow light, peaking at about 0.5 μm in the middle of the visible light spectrum.

At room temperature (300 K) the peak of radiant emittance lies at $9.7 \,\mu m$, in the far infrared, while at the temperature of liquid nitrogen (77 K) the maximum of the almost insignificant amount of radiant emittance occurs at 38 μm , in the extreme infrared wavelengths.




Figure 33.6 Planckian curves plotted on semi-log scales from 100 K to 1000 K. The dotted line represents the locus of maximum radiant emittance at each temperature as described by Wien's displacement law. 1: Spectral radiant emittance (W/cm² (μ m)); 2: Wavelength (μ m).

33.3.3 Stefan-Boltzmann's law

By integrating Planck's formula from $\lambda=0$ to $\lambda=\infty$, we obtain the total radiant emittance (W_b) of a blackbody:

$$W_b = \sigma T^4 \text{ [Watt/m}^2]$$

This is the Stefan-Boltzmann formula (after Josef Stefan, 1835–1893, and Ludwig Boltzmann, 1844–1906), which states that the total emissive power of a blackbody is proportional to the fourth power of its absolute temperature. Graphically, W_b represents the area below the Planck curve for a particular temperature. It can be shown that the radiant emittance in the interval $\lambda=0$ to λ_{max} is only 25% of the total, which represents about the amount of the sun's radiation which lies inside the visible light spectrum.



Figure 33.7 Josef Stefan (1835–1893), and Ludwig Boltzmann (1844–1906)

Using the Stefan-Boltzmann formula to calculate the power radiated by the human body, at a temperature of 300 K and an external surface area of approx. 2 m², we obtain 1 kW. This power loss could not be sustained if it were not for the compensating absorption of radiation from surrounding surfaces, at room temperatures which do not vary too drastically from the temperature of the body – or, of course, the addition of clothing.

33.3.4 Non-blackbody emitters

So far, only blackbody radiators and blackbody radiation have been discussed. However, real objects almost never comply with these laws over an extended wavelength region – although they may approach the blackbody behavior in certain spectral intervals. For example, a certain type of white paint may appear perfectly *white* in the visible light spectrum, but becomes distinctly gray at about 2 μ m, and beyond 3 μ m it is almost black.

There are three processes which can occur that prevent a real object from acting like a blackbody: a fraction of the incident radiation α may be absorbed, a fraction ρ may be reflected, and a fraction τ may be transmitted. Since all of these factors are more or less wavelength dependent, the subscript λ is used to imply the spectral dependence of their definitions. Thus:

- The spectral absorptance α_λ= the ratio of the spectral radiant power absorbed by an object to that incident upon it.
- The spectral reflectance ρ_λ = the ratio of the spectral radiant power reflected by an object to that incident upon it.
- The spectral transmittance τ_{λ} = the ratio of the spectral radiant power transmitted through an object to that incident upon it.

The sum of these three factors must always add up to the whole at any wavelength, so we have the relation:

$$\alpha_{\lambda} + \rho_{\lambda} + \tau_{\lambda} = 1$$

For opaque materials $\tau_{\lambda} = 0$ and the relation simplifies to:

$$\varepsilon_{\lambda} + \rho_{\lambda} = 1$$

Another factor, called the emissivity, is required to describe the fraction ϵ of the radiant emittance of a blackbody produced by an object at a specific temperature. Thus, we have the definition:

The spectral emissivity ε_{λ} = the ratio of the spectral radiant power from an object to that from a blackbody at the same temperature and wavelength.

Expressed mathematically, this can be written as the ratio of the spectral emittance of the object to that of a blackbody as follows:

$$\varepsilon_{\lambda} = \frac{W_{\lambda o}}{W_{\lambda b}}$$

Generally speaking, there are three types of radiation source, distinguished by the ways in which the spectral emittance of each varies with wavelength.

- A blackbody, for which $\varepsilon_{\lambda} = \varepsilon = 1$
- A graybody, for which ε_λ = ε = constant less than 1
- A selective radiator, for which ε varies with wavelength

According to Kirchhoff's law, for any material the spectral emissivity and spectral absorptance of a body are equal at any specified temperature and wavelength. That is:

$$\varepsilon_{\lambda} = \alpha$$

From this we obtain, for an opaque material (since $\alpha_{\lambda} + \rho_{\lambda} = 1$):

$$\varepsilon_{\lambda} + \rho_{\lambda} = 1$$

For highly polished materials ϵ_{λ} approaches zero, so that for a perfectly reflecting material (i.e. a perfect mirror) we have:

$$\rho_{\lambda} = 1$$

For a graybody radiator, the Stefan-Boltzmann formula becomes:

$$W = \varepsilon \sigma T^4 \left[\text{Watt/m}^2 \right]$$

This states that the total emissive power of a graybody is the same as a blackbody at the same temperature reduced in proportion to the value of ϵ from the graybody.




Figure 33.8 Spectral radiant emittance of three types of radiators. 1: Spectral radiant emittance; 2: Wavelength; 3: Blackbody; 4: Selective radiator; 5: Graybody.




Figure 33.9 Spectral emissivity of three types of radiators. 1: Spectral emissivity; 2: Wavelength; 3: Blackbody; 4: Graybody; 5: Selective radiator.

33.4 Infrared semi-transparent materials

Consider now a non-metallic, semi-transparent body – let us say, in the form of a thick flat plate of plastic material. When the plate is heated, radiation generated within its volume must work its way toward the surfaces through the material in which it is partially absorbed. Moreover, when it arrives at the surface, some of it is reflected back into the interior. The back-reflected radiation is again partially absorbed, but some of it arrives at the other surface, through which most of it escapes; part of it is reflected back again. Although the progressive reflections become weaker and weaker they must all be added up when the total emittance of the plate is sought. When the resulting geometrical series is summed, the effective emissivity of a semi-transparent plate is obtained as:

$$\varepsilon_{\boldsymbol{\lambda}} = \frac{\left(1-\rho_{\boldsymbol{\lambda}}\right)\left(1-\tau_{\boldsymbol{\lambda}}\right)}{1-\rho_{\boldsymbol{\lambda}}\tau_{\boldsymbol{\lambda}}}$$

When the plate becomes opaque this formula is reduced to the single formula:

$$\varepsilon_{\lambda} = 1 - \rho_{\lambda}$$

This last relation is a particularly convenient one, because it is often easier to measure reflectance than to measure emissivity directly.

The measurement formula

As already mentioned, when viewing an object, the camera receives radiation not only from the object itself. It also collects radiation from the surroundings reflected via the object surface. Both these radiation contributions become attenuated to some extent by the atmosphere in the measurement path. To this comes a third radiation contribution from the atmosphere itself.

This description of the measurement situation, as illustrated in the figure below, is so far a fairly true description of the real conditions. What has been neglected could for instance be sun light scattering in the atmosphere or stray radiation from intense radiation sources outside the field of view. Such disturbances are difficult to quantify, however, in most cases they are fortunately small enough to be neglected. In case they are not negligible, the measurement configuration is likely to be such that the risk for disturbance is obvious, at least to a trained operator. It is then his responsibility to modify the measurement situation to avoid the disturbance e.g. by changing the viewing direction, shielding off intense radiation sources etc.

Accepting the description above, we can use the figure below to derive a formula for the calculation of the object temperature from the calibrated camera output.




Figure 34.1 A schematic representation of the general thermographic measurement situation.1: Surroundings; 2: Object; 3: Atmosphere; 4: Camera

Assume that the received radiation power W from a blackbody source of temperature T_{source} on short distance generates a camera output signal U_{source} that is proportional to the power input (power linear camera). We can then write (Equation 1):

$$U_{source} = CW(T_{source})$$

or, with simplified notation:

$$U_{source} = CW_{source}$$

where C is a constant.

Should the source be a graybody with emittance ϵ , the received radiation would consequently be $\epsilon W_{\text{source}}.$

We are now ready to write the three collected radiation power terms:

1. Emission from the object = $\varepsilon \tau W_{obj}$, where ε is the emittance of the object and τ is the transmittance of the atmosphere. The object temperature is T_{obj} .

2. Reflected emission from ambient sources = $(1-\epsilon)\tau W_{refl}$, where $(1-\epsilon)$ is the reflectance of the object. The ambient sources have the temperature T_{refl} . It has here been assumed that the temperature T_{refl} is the same for all emitting surfaces within the halfsphere seen from a point on the object surface. This is of course sometimes a simplification of the true situation. It is, however, a necessary simplification in order to derive a workable formula, and T_{refl} can – at least theoretically – be given a value that represents an efficient temperature of a complex surrounding.

Note also that we have assumed that the emittance for the surroundings = 1. This is correct in accordance with Kirchhoff's law: All radiation impinging on the surrounding surfaces will eventually be absorbed by the same surfaces. Thus the emittance = 1. (Note though that the latest discussion requires the complete sphere around the object to be considered.)

3. Emission from the atmosphere = $(1 - \tau)\tau W_{atm}$, where $(1 - \tau)$ is the emittance of the atmosphere. The temperature of the atmosphere is T_{atm} .

The total received radiation power can now be written (Equation 2):

$$W_{tot} = \varepsilon \tau W_{obj} + (1 - \varepsilon) \tau W_{refl} + (1 - \tau) W_{atm}$$

We multiply each term by the constant C of Equation 1 and replace the CW products by the corresponding U according to the same equation, and get (Equation 3):

$$U_{\rm tot} = \varepsilon \tau U_{\rm obj} + (1-\varepsilon) \tau U_{\rm refl} + (1-\tau) U_{\rm atm}$$

Solve Equation 3 for Uobj (Equation 4):

$$U_{\textit{obj}} = \frac{1}{\varepsilon\tau} U_{\textit{tot}} - \frac{1-\varepsilon}{\varepsilon} U_{\textit{refl}} - \frac{1-\tau}{\varepsilon\tau} U_{\textit{atm}}$$

This is the general measurement formula used in all the FLIR Systems thermographic equipment. The voltages of the formula are:

Table 34.1 Voltages

U _{obj}	Calculated camera output voltage for a blackbody of temperature T_{obj} i.e. a voltage that can be directly converted into true requested object temperature.
U _{tot}	Measured camera output voltage for the actual case.
U _{refl}	Theoretical camera output voltage for a blackbody of temperature T_{refl} according to the calibration.
U _{atm}	Theoretical camera output voltage for a blackbody of temperature T_{atm} according to the calibration.

The operator has to supply a number of parameter values for the calculation:

- the object emittance ε,
- · the relative humidity,
- T_{atm}
- object distance (D_{obi})
- the (effective) temperature of the object surroundings, or the reflected ambient temperature T_{refl}, and
- the temperature of the atmosphere Tatm

This task could sometimes be a heavy burden for the operator since there are normally no easy ways to find accurate values of emittance and atmospheric transmittance for the

actual case. The two temperatures are normally less of a problem provided the surroundings do not contain large and intense radiation sources.

A natural question in this connection is: How important is it to know the right values of these parameters? It could though be of interest to get a feeling for this problem already here by looking into some different measurement cases and compare the relative magnitudes of the three radiation terms. This will give indications about when it is important to use correct values of which parameters.

The figures below illustrates the relative magnitudes of the three radiation contributions for three different object temperatures, two emittances, and two spectral ranges: SW and LW. Remaining parameters have the following fixed values:

- $\tau = 0.88$
- $T_{refl} = +20^{\circ}C (+68^{\circ}F)$
- $T_{atm} = +20^{\circ}C (+68^{\circ}F)$

It is obvious that measurement of low object temperatures are more critical than measuring high temperatures since the 'disturbing' radiation sources are relatively much stronger in the first case. Should also the object emittance be low, the situation would be still more difficult.

We have finally to answer a question about the importance of being allowed to use the calibration curve above the highest calibration point, what we call extrapolation. Imagine that we in a certain case measure $U_{tot} = 4.5$ volts. The highest calibration point for the camera was in the order of 4.1 volts, a value unknown to the operator. Thus, even if the object happened to be a blackbody, i.e. $U_{obj} = U_{tot}$, we are actually performing extrapolation of the calibration curve when converting 4.5 volts into temperature.

Let us now assume that the object is not black, it has an emittance of 0.75, and the transmittance is 0.92. We also assume that the two second terms of Equation 4 amount to 0.5 volts together. Computation of U_{obj} by means of Equation 4 then results in $U_{\text{obj}}=4.5\,/\,0.75\,/\,0.92-0.5=6.0$. This is a rather extreme extrapolation, particularly when considering that the video amplifier might limit the output to 5 volts! Note, though, that the application of the calibration curve is a theoretical procedure where no electronic or other limitations exist. We trust that if there had been no signal limitations in the camera, and if it had been calibrated far beyond 5 volts, the resulting curve would have been very much the same as our real curve extrapolated beyond 4.1 volts, provided the calibration algorithm is based on radiation physics, like the FLIR Systems algorithm. Of course there must be a limit to such extrapolations.




Figure 34.2 Relative magnitudes of radiation sources under varying measurement conditions (SW camera). 1: Object temperature; 2: Emittance; Obj: Object radiation; Refl: Reflected radiation; Atm: atmosphere radiation. Fixed parameters: $\tau = 0.88$; $T_{refl} = 20^{\circ}C$ (+68°F); $T_{atm} = 20^{\circ}C$ (+68°F).




Figure 34.3 Relative magnitudes of radiation sources under varying measurement conditions (LW camera). 1: Object temperature; 2: Emittance; Obj: Object radiation; Refl: Reflected radiation; Atm: atmosphere radiation. Fixed parameters: $\tau = 0.88$; $T_{refl} = 20^{\circ}C$ (+68°F); $T_{atm} = 20^{\circ}C$ (+68°F).

Emissivity tables

This section presents a compilation of emissivity data from the infrared literature and measurements made by FLIR Systems.

35.1 References

- Mikaél A. Bramson: Infrared Radiation, A Handbook for Applications, Plenum press, N. Y.
- William L. Wolfe, George J. Zissis: The Infrared Handbook, Office of Naval Research, Department of Navy, Washington, D.C.
- 3. Madding, R. P.: *Thermographic Instruments and systems*. Madison, Wisconsin: University of Wisconsin Extension, Department of Engineering and Applied Science.
- 4. William L. Wolfe: *Handbook of Military Infrared Technology*, Office of Naval Research, Department of Navy, Washington, D.C.
- Jones, Smith, Probert: External thermography of buildings..., Proc. of the Society of Photo-Optical Instrumentation Engineers, vol.110, Industrial and Civil Applications of Infrared Technology, June 1977 London.
- Paljak, Pettersson: Thermography of Buildings, Swedish Building Research Institute, Stockholm 1972.
- 7. Vlcek, J: Determination of emissivity with imaging radiometers and some emissivities at $\lambda = 5 \,\mu m$. Photogrammetric Engineering and Remote Sensing.
- Kern: Evaluation of infrared emission of clouds and ground as measured by weather satellites, Defence Documentation Center, AD 617 417.
- Öhman, Claes: Emittansmätningar med AGEMA E-Box. Teknisk rapport, AGEMA 1999. (Emittance measurements using AGEMA E-Box. Technical report, AGEMA 1999.)
- 10. Matteï, S., Tang-Kwor, E: Emissivity measurements for Nextel Velvet coating 811-21 between -36°C AND 82°C.
- 11. Lohrengel & Todtenhaupt (1996)
- 12. ITC Technical publication 32.
- 13. ITC Technical publication 29.
- 14. Schuster, Norbert and Kolobrodov, Valentin G. *Infrarotthermographie*. Berlin: Wiley-VCH, 2000.

Note The emissivity values in the table below are recorded using a shortwave (SW) camera. The values should be regarded as recommendations only and used with caution.

35.2 Tables

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference

1	2	3	4	5	6
3M type 35	Vinyl electrical tape (several colors)	< 80	LW	≈ 0.96	13
3M type 88	Black vinyl electrical tape	< 105	LW	≈ 0.96	13
3M type 88	Black vinyl electrical tape	< 105	MW	< 0.96	13
3M type Super 33 +	Black vinyl electrical tape	< 80	LW	≈ 0.96	13
Aluminum	anodized sheet	100	Т	0.55	2

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Aluminum	anodized, black, dull	70	SW	0.67	9
Aluminum	anodized, black, dull	70	LW	0.95	9
Aluminum	anodized, light gray, dull	70	SW	0.61	9
Aluminum	anodized, light gray, dull	70	LW	0.97	9
Aluminum	as received, plate	100	Т	0.09	4
Aluminum	as received, sheet	100	Т	0.09	2
Aluminum	cast, blast cleaned	70	SW	0.47	9
Aluminum	cast, blast cleaned	70	LW	0.46	9
Aluminum	dipped in HNO ₃ , plate	100	Т	0.05	4
Aluminum	foil	27	10 μm	0.04	3
Aluminum	foil	27	3 µm	0.09	3
Aluminum	oxidized, strongly	50-500	Т	0.2-0.3	1
Aluminum	polished	50–100	Т	0.04-0.06	1
Aluminum	polished plate	100	Т	0.05	4
Aluminum	polished, sheet	100	Т	0.05	2
Aluminum	rough surface	20-50	Т	0.06-0.07	1
Aluminum	roughened	27	10 μm	0.18	3
Aluminum	roughened	27	3 µm	0.28	3
Aluminum	sheet, 4 samples differently scratched	70	SW	0.05-0.08	9
Aluminum	sheet, 4 samples differently scratched	70	LW	0.03-0.06	9
Aluminum	vacuum deposited	20	Т	0.04	2
Aluminum	weathered, heavily	17	SW	0.83-0.94	5
Aluminum bronze		20	Т	0.60	1
Aluminum hydroxide	powder		Т	0.28	1
Aluminum oxide	activated, powder		Т	0.46	1
Aluminum oxide	pure, powder (alumina)		Т	0.16	1
Asbestos	board	20	Т	0.96	1
Asbestos	fabric		Т	0.78	1
Asbestos	floor tile	35	SW	0.94	7
Asbestos	paper	40–400	Т	0.93-0.95	1

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Asbestos	powder		Т	0.40-0.60	1
Asbestos	slate	20	Т	0.96	1
Asphalt paving		4	LLW	0.967	8
Brass	dull, tarnished	20–350	Т	0.22	1
Brass	oxidized	100	Т	0.61	2
Brass	oxidized	70	SW	0.04-0.09	9
Brass	oxidized	70	LW	0.03-0.07	9
Brass	oxidized at 600°C	200–600	Т	0.59-0.61	1
Brass	polished	200	Т	0.03	1
Brass	polished, highly	100	Т	0.03	2
Brass	rubbed with 80- grit emery	20	Т	0.20	2
Brass	sheet, rolled	20	Т	0.06	1
Brass	sheet, worked with emery	20	Т	0.2	1
Brick	alumina	17	SW	0.68	5
Brick	common	17	SW	0.86-0.81	5
Brick	Dinas silica, glazed, rough	1100	Т	0.85	1
Brick	Dinas silica, refractory	1000	Т	0.66	1
Brick	Dinas silica, un- glazed, rough	1000	Т	0.80	1
Brick	firebrick	17	SW	0.68	5
Brick	fireclay	1000	Т	0.75	1
Brick	fireclay	1200	Т	0.59	1
Brick	fireclay	20	Т	0.85	1
Brick	masonry	35	SW	0.94	7
Brick	masonry, plastered	20	Т	0.94	1
Brick	red, common	20	Т	0.93	2
Brick	red, rough	20	Т	0.88-0.93	1
Brick	refractory, corundum	1000	Т	0.46	1
Brick	refractory, magnesite	1000–1300	Т	0.38	1
Brick	refractory, strongly radiating	500–1000	Т	0.8–0.9	1
Brick	refractory, weakly radiating	500–1000	Т	0.65-0.75	1
Brick	silica, 95% SiO ₂	1230	Т	0.66	1
Brick	sillimanite, 33% SiO ₂ , 64% Al ₂ O ₃	1500	Т	0.29	1

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

Brick	1	2	3	4	5	6
Bronze phosphor bronze 70 SW 0.08 9 Bronze phosphor bronze 70 LW 0.06 9 Bronze polished 50 T 0.1 1 Bronze porous, rough 50-150 T 0.55 1 Bronze powder T 0.76-0.80 1 Carbon candle soot 20 T 0.95 2 Carbon charcoal powder T 0.96 1 Carbon graphite powder T 0.96 1 Carbon graphite, filed surface 20 T 0.98 2 Carbon lampblack 20-400 T 0.98-0.97 1 Chipboard untreated 20 SW 0.90 6 Chromium polished 500-1000 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Clay fired 70 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>						
Bronze	-	'		_		
Bronze polished 50 T 0.1 1 Bronze porous, rough 50-150 T 0.55 1 Bronze powder T 0.78-0.80 1 Carbon candle soot 20 T 0.95 2 Carbon charcoal powder T 0.96 1 Carbon graphite, filed surface 20 T 0.97 1 Carbon lampblack 20-400 T 0.95-0.97 1 Chronium polished 20 SW 0.90 6 Chronium polished 50 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Clay fired 70 T 0.91 1 Cloth black 20 T 0.98 1 Concrete dry 36 SW 0.97 5 Concrete walkway 5 LLW		 	-			
Bronze		 				
Bronze		+				
Carbon candle soot 20 T 0.95 2 Carbon charcoal powder T 0.96 1 Carbon graphite powder T 0.97 1 Carbon graphite, filed surface 20 T 0.98 2 Carbon lampblack 20-400 T 0.95-0.97 1 Chipboard untreated 20 SW 0.90 6 Chromium polished 50 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Chromium polished 500-1000 T 0.28-0.38 1 Cluy fired 70 T 0.91 1 Cluy fired 70 T 0.91 1 Cluy fired 70 T 0.98 1 Concrete dry 36 SW 0.95 7 Concrete valkway 5 <t< td=""><td></td><td>+</td><td>30-130</td><td></td><td></td><td></td></t<>		+	30-130			
Carbon charcoal powder T 0.96 1 Carbon graphite powder T 0.97 1 Carbon graphite, filed surface 20 T 0.98 2 Carbon lampblack 20-400 T 0.95-0.97 1 Chipboard untreated 20 SW 0.90 6 Chromium polished 50 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Chromium polished 500-1000 T 0.91 1 Clay fired 70 T 0.91 1 Clay fired 70 T 0.91 1 Clay fired 70 T 0.98 1 Cloth black 20 T 0.98 1 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW		<u> </u>	20			
Carbon graphite powder T 0.97 1 Carbon graphite, filed surface 20 T 0.98 2 Carbon lampblack 20-400 T 0.95-0.97 1 Chipboard untreated 20 SW 0.90 6 Chromium polished 50 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Chromium polished 500-1000 T 0.28-0.38 1 Clay fired 70 T 0.91 1 Clay fired 70 T 0.991 1 Cloth black 20 T 0.98 1 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, caref		+	20			
Carbon graphite, filed surface 20 T 0.98 2 Carbon lampblack 20-400 T 0.95-0.97 1 Chipboard untreated 20 SW 0.90 6 Chromium polished 50 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Chromium polished 500-1000 T 0.28-0.38 1 Clay fired 70 T 0.91 1 Clay fired 70 T 0.99 2 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Copper blackmay 5 <td></td> <td>·</td> <td></td> <td></td> <td></td> <td></td>		·				
Carbon Iampblack 20-400 T 0.95-0.97 1 Chipboard untreated 20 SW 0.90 6 Chromium polished 50 T 0.10 1 Chromium polished 500-1000 T 0.28-0.38 1 Chromium polished 500-1000 T 0.28-0.38 1 Cloth black 20 T 0.91 1 Cloth black 20 T 0.98 1 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper electrolytic, care-fully polished 20 T 0.07 1 Copper electrolytic, care-fully polished -34 T 0.018 1 Copper molten 1100-1300 T 0.13-0.15 1		graphite, filed	20			
Chromium polished 50 T 0.10 1 Chromium polished 500–1000 T 0.28–0.38 1 Clay fired 70 T 0.91 1 Cloth black 20 T 0.98 1 Concrete 20 T 0.92 2 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper delectrolytic, carefully polished 80 T 0.07 1 Copper electrolytic, carefully polished -34 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper	Carbon	+	20–400	Т	0.95–0.97	1
Chromium polished 500–1000 T 0.28–0.38 1 Clay fired 70 T 0.91 1 Cloth black 20 T 0.98 1 Concrete 20 T 0.92 2 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, carefully prepared surface -34 T 0.018 1 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized, black 27 T 0.78 2 Copper	Chipboard	untreated	20	SW	0.90	6
Clay fired 70 T 0.91 1 Cloth black 20 T 0.98 1 Concrete 20 T 0.92 2 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, carefully prepared surface 34 T 0.018 1 Copper molten 1100-1300 T 0.13-0.15 1 Copper molten 1100-1300 T 0.13-0.15 1 Copper oxidized 50 T 0.6-0.7 1 Copper oxidized, black 27 T 0.78 4 Copper	Chromium	polished	50	Т	0.10	1
Cloth black 20 T 0.98 1 Concrete 20 T 0.92 2 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, carefully prepared surface -34 T 0.018 1 Copper electrolytic, carefully prepared surface -34 T 0.006 4 Copper electrolytic, polished -34 T 0.006 4 Copper oxidized 50 T 0.13-0.15 1 Copper oxidized to blackness T 0.88 1 Copper oxidized, heavily 20 T 0.78 2 <	Chromium	polished	500–1000	Т	0.28-0.38	1
Concrete 20 T 0.92 2 Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to blackness T 0.88 1 Copper oxidized, black 27 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 50–100 T 0.03 2 Copper polished,	Clay	fired	70	Т	0.91	1
Concrete dry 36 SW 0.95 7 Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to black plack 50 T 0.6–0.7 1 Copper oxidized, black 27 T 0.78 4 Copper polished 50–100 T 0.02 1 Copper polished 50–100 T 0.03 2 Copper polished, commercial 27 T 0.03 4	Cloth	black	20	Т	0.98	1
Concrete rough 17 SW 0.97 5 Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to black ess T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished, commercial 27 T 0.03 2 Copper polished, mechanical 22 T 0.015 4	Concrete		20	Т	0.92	2
Concrete walkway 5 LLW 0.974 8 Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to black ess T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.015 4 Copper polished, mechanical 22 T 0.008 4 <td>Concrete</td> <td>dry</td> <td>36</td> <td>SW</td> <td>0.95</td> <td>7</td>	Concrete	dry	36	SW	0.95	7
Copper commercial, burnished 20 T 0.07 1 Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to black ess T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 50–100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper polished, mechanical 22 T 0.008 4<	Concrete	rough	17	SW	0.97	5
Copper electrolytic, carefully polished 80 T 0.018 1 Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to blackness T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Concrete	walkway	5	LLW	0.974	8
Copper electrolytic, polished -34 T 0.006 4 Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to blackness T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper		20	Т	0.07	1
Copper molten 1100–1300 T 0.13–0.15 1 Copper oxidized 50 T 0.6–0.7 1 Copper oxidized to blackness T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper		80	Т	0.018	1
Copper oxidized 50 T 0.6-0.7 1 Copper oxidized to blackness T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50-100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper		-34	Т	0.006	4
Copper oxidized to blackness T 0.88 1 Copper oxidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper	molten	1100–1300	Т	0.13-0.15	1
blackness 0xidized, black 27 T 0.78 4 Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper	oxidized	50	Т	0.6–0.7	1
Copper oxidized, heavily 20 T 0.78 2 Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper			Т	0.88	1
Copper polished 50–100 T 0.02 1 Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper	oxidized, black	27	Т	0.78	4
Copper polished 100 T 0.03 2 Copper polished, commercial 27 T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper	oxidized, heavily	20	Т	0.78	2
Copper polished, commercial T 0.03 4 Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper	polished	50–100	Т	0.02	1
Copper polished, mechanical 22 T 0.015 4 Copper pure, carefully prepared surface 22 T 0.008 4	Copper	polished	100	Т	0.03	2
mechanical Copper pure, carefully prepared surface Description: Descr	Copper		27	Т	0.03	4
prepared surface	Copper		22	Т	0.015	4
Copper scraped 27 T 0.07 4	Copper		22	Т	0.008	4
	Copper	scraped	27	Т	0.07	4

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Copper dioxide	powder		Т	0.84	1
Copper oxide	red, powder		Т	0.70	1
Ebonite			Т	0.89	1
Emery	coarse	80	Т	0.85	1
Enamel		20	Т	0.9	1
Enamel	lacquer	20	Т	0.85-0.95	1
Fiber board	hard, untreated	20	SW	0.85	6
Fiber board	masonite	70	SW	0.75	9
Fiber board	masonite	70	LW	0.88	9
Fiber board	particle board	70	SW	0.77	9
Fiber board	particle board	70	LW	0.89	9
Fiber board	porous, untreated	20	SW	0.85	6
Glass pane (float glass)	non-coated	20	LW	0.97	14
Gold	polished	130	Т	0.018	1
Gold	polished, carefully	200–600	Т	0.02-0.03	1
Gold	polished, highly	100	Т	0.02	2
Granite	polished	20	LLW	0.849	8
Granite	rough	21	LLW	0.879	8
Granite	rough, 4 different samples	70	sw	0.95-0.97	9
Granite	rough, 4 different samples	70	LW	0.77-0.87	9
Gypsum		20	Т	0.8-0.9	1
Ice: See Water					
Iron and steel	cold rolled	70	SW	0.20	9
Iron and steel	cold rolled	70	LW	0.09	9
Iron and steel	covered with red rust	20	Т	0.61-0.85	1
Iron and steel	electrolytic	100	Т	0.05	4
Iron and steel	electrolytic	22	Т	0.05	4
Iron and steel	electrolytic	260	Т	0.07	4
Iron and steel	electrolytic, care- fully polished	175–225	Т	0.05-0.06	1
Iron and steel	freshly worked with emery	20	Т	0.24	1
Iron and steel	ground sheet	950–1100	Т	0.55-0.61	1
Iron and steel	heavily rusted sheet	20	Т	0.69	2
Iron and steel	hot rolled	130	Т	0.60	1
Iron and steel	hot rolled	20	Т	0.77	1
Iron and steel	Hotrolloa	20		0.77	<u> </u>

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Iron and steel	oxidized	100	Т	0.74	1
Iron and steel	oxidized	1227	Т	0.89	4
Iron and steel	oxidized	125–525	Т	0.78-0.82	1
Iron and steel	oxidized	200	Т	0.79	2
Iron and steel	oxidized	200–600	Т	0.80	1
Iron and steel	oxidized strongly	50	Т	0.88	1
Iron and steel	oxidized strongly	500	Т	0.98	1
Iron and steel	polished	100	Т	0.07	2
Iron and steel	polished	400–1000	Т	0.14-0.38	1
Iron and steel	polished sheet	750–1050	Т	0.52-0.56	1
Iron and steel	rolled sheet	50	Т	0.56	1
Iron and steel	rolled, freshly	20	Т	0.24	1
Iron and steel	rough, plane surface	50	Т	0.95-0.98	1
Iron and steel	rusted red, sheet	22	Т	0.69	4
Iron and steel	rusted, heavily	17	SW	0.96	5
Iron and steel	rusty, red	20	Т	0.69	1
Iron and steel	shiny oxide layer, sheet,	20	Т	0.82	1
Iron and steel	shiny, etched	150	Т	0.16	1
Iron and steel	wrought, carefully polished	40–250	Т	0.28	1
Iron galvanized	heavily oxidized	70	SW	0.64	9
Iron galvanized	heavily oxidized	70	LW	0.85	9
Iron galvanized	sheet	92	Т	0.07	4
Iron galvanized	sheet, burnished	30	Т	0.23	1
Iron galvanized	sheet, oxidized	20	Т	0.28	1
Iron tinned	sheet	24	Т	0.064	4
Iron, cast	casting	50	Т	0.81	1
Iron, cast	ingots	1000	Т	0.95	1
Iron, cast	liquid	1300	Т	0.28	1
Iron, cast	machined	800–1000	Т	0.60-0.70	1
Iron, cast	oxidized	100	Т	0.64	2
Iron, cast	oxidized	260	Т	0.66	4
Iron, cast	oxidized	38	Т	0.63	4
Iron, cast	oxidized	538	Т	0.76	4
Iron, cast	oxidized at 600°C	200–600	Т	0.64-0.78	1
Iron, cast	polished	200	Т	0.21	1
Iron, cast	polished	38	Т	0.21	4
Iron, cast	polished	40	Т	0.21	2
l		Ī	I		

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Iron, cast	unworked	900–1100	Т	0.87-0.95	1
Krylon Ultra-flat black 1602	Flat black	Room tempera- ture up to 175	LW	≈ 0.96	12
Krylon Ultra-flat black 1602	Flat black	Room tempera- ture up to 175	MW	≈ 0.97	12
Lacquer	3 colors sprayed on Aluminum	70	SW	0.50-0.53	9
Lacquer	3 colors sprayed on Aluminum	70	LW	0.92-0.94	9
Lacquer	Aluminum on rough surface	20	Т	0.4	1
Lacquer	bakelite	80	Т	0.83	1
Lacquer	black, dull	40–100	Т	0.96-0.98	1
Lacquer	black, matte	100	Т	0.97	2
Lacquer	black, shiny, sprayed on iron	20	Т	0.87	1
Lacquer	heat-resistant	100	Т	0.92	1
Lacquer	white	100	Т	0.92	2
Lacquer	white	40–100	Т	0.8-0.95	1
Lead	oxidized at 200°C	200	Т	0.63	1
Lead	oxidized, gray	20	Т	0.28	1
Lead	oxidized, gray	22	Т	0.28	4
Lead	shiny	250	Т	0.08	1
Lead	unoxidized, polished	100	Т	0.05	4
Lead red		100	Т	0.93	4
Lead red, powder		100	Т	0.93	1
Leather	tanned		Т	0.75-0.80	1
Lime			Т	0.3-0.4	1
Magnesium		22	Т	0.07	4
Magnesium		260	Т	0.13	4
Magnesium		538	Т	0.18	4
Magnesium	polished	20	Т	0.07	2
Magnesium powder			Т	0.86	1
Molybdenum		1500–2200	Т	0.19-0.26	1
Molybdenum		600–1000	Т	0.08-0.13	1
Molybdenum	filament	700–2500	Т	0.1-0.3	1
Mortar		17	sw	0.87	5
Mortar	dry	36	SW	0.94	7
Nextel Velvet 811- 21 Black	Flat black	-60-150	LW	> 0.97	10 and 11

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Nichrome	rolled	700	Т	0.25	1
Nichrome	sandblasted	700	Т	0.70	1
Nichrome	wire, clean	50	Т	0.65	1
Nichrome	wire, clean	500–1000	Т	0.71–0.79	1
Nichrome	wire, oxidized	50–500	Т	0.95-0.98	1
Nickel	bright matte	122	Т	0.041	4
Nickel	commercially pure, polished	100	Т	0.045	1
Nickel	commercially pure, polished	200–400	Т	0.07-0.09	1
Nickel	electrolytic	22	Т	0.04	4
Nickel	electrolytic	260	Т	0.07	4
Nickel	electrolytic	38	Т	0.06	4
Nickel	electrolytic	538	Т	0.10	4
Nickel	electroplated on iron, polished	22	Т	0.045	4
Nickel	electroplated on iron, unpolished	20	Т	0.11–0.40	1
Nickel	electroplated on iron, unpolished	22	Т	0.11	4
Nickel	electroplated, polished	20	Т	0.05	2
Nickel	oxidized	1227	Т	0.85	4
Nickel	oxidized	200	Т	0.37	2
Nickel	oxidized	227	Т	0.37	4
Nickel	oxidized at 600°C	200–600	Т	0.37-0.48	1
Nickel	polished	122	Т	0.045	4
Nickel	wire	200–1000	Т	0.1-0.2	1
Nickel oxide		1000–1250	Т	0.75–0.86	1
Nickel oxide		500–650	Т	0.52-0.59	1
Oil, lubricating	0.025 mm film	20	Т	0.27	2
Oil, lubricating	0.050 mm film	20	Т	0.46	2
Oil, lubricating	0.125 mm film	20	Т	0.72	2
Oil, lubricating	film on Ni base: Ni base only	20	Т	0.05	2
Oil, lubricating	thick coating	20	Т	0.82	2
Paint	8 different colors and qualities	70	SW	0.88-0.96	9
Paint	8 different colors and qualities	70	LW	0.92-0.94	9
Paint	Aluminum, various ages	50–100	Т	0.27-0.67	1
Paint	cadmium yellow		Т	0.28-0.33	1
				•	

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Paint	chrome green		Т	0.65-0.70	1
Paint	cobalt blue		Т	0.7-0.8	1
Paint	oil	17	SW	0.87	5
Paint	oil based, average of 16 colors	100	Т	0.94	2
Paint	oil, black flat	20	SW	0.94	6
Paint	oil, black gloss	20	SW	0.92	6
Paint	oil, gray flat	20	SW	0.97	6
Paint	oil, gray gloss	20	SW	0.96	6
Paint	oil, various colors	100	Т	0.92-0.96	1
Paint	plastic, black	20	SW	0.95	6
Paint	plastic, white	20	SW	0.84	6
Paper	4 different colors	70	SW	0.68-0.74	9
Paper	4 different colors	70	LW	0.92-0.94	9
Paper	black		Т	0.90	1
Paper	black, dull		Т	0.94	1
Paper	black, dull	70	SW	0.86	9
Paper	black, dull	70	LW	0.89	9
Paper	blue, dark		Т	0.84	1
Paper	coated with black lacquer		Т	0.93	1
Paper	green		Т	0.85	1
Paper	red		Т	0.76	1
Paper	white	20	Т	0.7-0.9	1
Paper	white bond	20	Т	0.93	2
Paper	white, 3 different glosses	70	SW	0.76-0.78	9
Paper	white, 3 different glosses	70	LW	0.88-0.90	9
Paper	yellow		Т	0.72	1
Plaster		17	SW	0.86	5
Plaster	plasterboard, untreated	20	SW	0.90	6
Plaster	rough coat	20	Т	0.91	2
Plastic	glass fibre lami- nate (printed circ. board)	70	SW	0.94	9
Plastic	glass fibre lami- nate (printed circ. board)	70	LW	0.91	9
Plastic	polyurethane iso- lation board	70	LW	0.55	9

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Plastic	polyurethane iso- lation board	70	SW	0.29	9
Plastic	PVC, plastic floor, dull, structured	70	SW	0.94	9
Plastic	PVC, plastic floor, dull, structured	70	LW	0.93	9
Platinum		100	Т	0.05	4
Platinum		1000–1500	Т	0.14-0.18	1
Platinum		1094	Т	0.18	4
Platinum		17	Т	0.016	4
Platinum		22	Т	0.03	4
Platinum		260	Т	0.06	4
Platinum		538	Т	0.10	4
Platinum	pure, polished	200–600	Т	0.05-0.10	1
Platinum	ribbon	900-1100	Т	0.12-0.17	1
Platinum	wire	1400	Т	0.18	1
Platinum	wire	500-1000	Т	0.10-0.16	1
Platinum	wire	50–200	Т	0.06-0.07	1
Porcelain	glazed	20	Т	0.92	1
Porcelain	white, shiny		T	0.70-0.75	1
Rubber	hard	20	Т	0.95	1
Rubber	soft, gray, rough	20	T	0.95	1
Sand			Т	0.60	1
Sand		20	Т	0.90	2
Sandstone	polished	19	LLW	0.909	8
Sandstone	rough	19	LLW	0.935	8
Silver	polished	100	Т	0.03	2
Silver	pure, polished	200-600	Т	0.02-0.03	1
Skin	human	32	Т	0.98	2
Slag	boiler	0–100	Т	0.97-0.93	1
Slag	boiler	1400–1800	Т	0.69-0.67	1
Slag	boiler	200-500	Т	0.89-0.78	1
Slag	boiler	600–1200	Т	0.76-0.70	1
Snow: See Water					
Soil	dry	20	Т	0.92	2
Soil	saturated with water	20	Т	0.95	2
Stainless steel	alloy, 8% Ni, 18% Cr	500	Т	0.35	1
Stainless steel	rolled	700	Т	0.45	1
Stainless steel	sandblasted	700	Т	0.70	1
Stainless steel	sheet, polished	70	SW	0.18	9

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Stainless steel	sheet, polished	70	LW	0.14	9
Stainless steel	sheet, untreated, somewhat scratched	70	SW	0.30	9
Stainless steel	sheet, untreated, somewhat scratched	70	LW	0.28	9
Stainless steel	type 18-8, buffed	20	Т	0.16	2
Stainless steel	type 18-8, oxidized at 800°C	60	Т	0.85	2
Stucco	rough, lime	10–90	Т	0.91	1
Styrofoam	insulation	37	SW	0.60	7
Tar			Т	0.79-0.84	1
Tar	paper	20	Т	0.91-0.93	1
Tile	glazed	17	sw	0.94	5
Tin	burnished	20–50	Т	0.04-0.06	1
Tin	tin-plated sheet iron	100	Т	0.07	2
Titanium	oxidized at 540°C	1000	Т	0.60	1
Titanium	oxidized at 540°C	200	Т	0.40	1
Titanium	oxidized at 540°C	500	Т	0.50	1
Titanium	polished	1000	Т	0.36	1
Titanium	polished	200	Т	0.15	1
Titanium	polished	500	Т	0.20	1
Tungsten		1500–2200	Т	0.24-0.31	1
Tungsten		200	Т	0.05	1
Tungsten		600–1000	Т	0.1–0.16	1
Tungsten	filament	3300	Т	0.39	1
Varnish	flat	20	SW	0.93	6
Varnish	on oak parquet floor	70	SW	0.90	9
Varnish	on oak parquet floor	70	LW	0.90-0.93	9
Wallpaper	slight pattern, light gray	20	SW	0.85	6
Wallpaper	slight pattern, red	20	SW	0.90	6
Water	distilled	20	Т	0.96	2
Water	frost crystals	-10	Т	0.98	2
Water	ice, covered with heavy frost	0	Т	0.98	1
Water	ice, smooth	0	Т	0.97	1
Water	ice, smooth	-10	Т	0.96	2
Water	layer >0.1 mm thick	0–100	Т	0.95–0.98	1

35

Table 35.1 T: Total spectrum; SW: 2–5 μm; LW: 8–14 μm, LLW: 6.5–20 μm; 1: Material; 2: Specification; 3: Temperature in $^{\circ}$ C; 4: Spectrum; 5: Emissivity: 6:Reference (continued)

1	2	3	4	5	6
Water	snow		Ţ	0.8	1
Water	snow	-10	Т	0.85	2
Wood		17	SW	0.98	5
Wood		19	LLW	0.962	8
Wood	ground		Т	0.5–0.7	1
Wood	pine, 4 different samples	70	SW	0.67-0.75	9
Wood	pine, 4 different samples	70	LW	0.81-0.89	9
Wood	planed	20	Т	0.8-0.9	1
Wood	planed oak	20	Т	0.90	2
Wood	planed oak	70	SW	0.77	9
Wood	planed oak	70	LW	0.88	9
Wood	plywood, smooth, dry	36	SW	0.82	7
Wood	plywood, untreated	20	SW	0.83	6
Wood	white, damp	20	Т	0.7–0.8	1
Zinc	oxidized at 400°C	400	Т	0.11	1
Zinc	oxidized surface	1000–1200	Т	0.50-0.60	1
Zinc	polished	200–300	Т	0.04-0.05	1
Zinc	sheet	50	Т	0.20	1

A note on the technical production of this publication

This publication was produced using XML — the eXtensible Markup Language. For more information about XML, please visit http://www.w3.org/XML/ $\,$

A note on the typeface used in this publication

This publication was typeset using Linotype Helvetica™ World. Helvetica™ was designed by Max Miedinger (1910–1980)

LOEF (List Of Effective Files)

T501011.xml; en-US; AL; 45866; 2017-10-18 T505552.xml; en-US; 9599; 2013-11-05 T505469.xml; en-US; 39689; 2017-01-25 T505013.xml; en-US; 39689; 2017-01-25 T505652.xml; en-US; 39869; 2017-01-31 T505192.xml; en-US; 39872; 2017-01-31 T505193.xml; en-US; 39571; 2017-01-20 T505194.xml; en-US; 39872; 2017-01-31 T505653.xml; en-US; 39869; 2017-01-31 T505422.xml; en-US; 39571; 2017-01-20 T505654.xml; en-US; 39571; 2017-01-20 T505664.xml; en-US; 39571; 2017-01-20 T505655.xml; en-US; 39872; 2017-01-31 T505656.xml; en-US; 39869; 2017-01-31 T505657.xml; en-US; 39867; 2017-01-31 T505658.xml; en-US; 41842; 2017-04-03 T505411.xml; en-US; 39571; 2017-01-20 T505659.xml; en-US; 39867; 2017-01-31 T505660.xml; en-US; 39571; 2017-01-20 T505661.xml; en-US; 39867; 2017-01-31 T505662.xml; en-US; 39867; 2017-01-31 T505765.xml; en-US; 39867; 2017-01-31 T505663.xml; en-US; 39869; 2017-01-31 T505789.xml; en-US; 39871; 2017-01-31 T505476.xml; en-US; 39581; 2017-01-20 T505012.xml; en-US; 41563; 2017-03-23 T505007.xml; en-US; 42810; 2017-05-23 T506125.xml; en-US; 40753; 2017-03-02 T505000.xml; en-US; 39687; 2017-01-25 T505005.xml; en-US; 43349; 2017-06-14 T505001.xml; en-US; 41563; 2017-03-23 T505006.xml; en-US; 41563; 2017-03-23 T505002.xml; en-US; 39512; 2017-01-18



Website http://www.flir.com

Customer support

http://support.flir.com

Copyright

© 2017, FLIR Systems, Inc. All rights reserved worldwide.

DisclaimerSpecifications subject to change without further notice. Models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

T559880 Publ. No.: Release: Commit: 45866 Head: 45866 Language: en-US Modified: 2017-10-18 Formatted: 2017-11-01