PNP Silicon Epitaxial Transistor

BCP69T1G, NSVBCP69T1G

MEDIUM POWER PNP SILICON HIGH CURRENT TRANSISTOR SURFACE MOUNT

This PNP Silicon Epitaxial Transistor is designed for use in low voltage, high current applications. The device is housed in the SOT−223 package, which is designed for medium power surface mount applications.

Features

- High Current: I_C = −1.0 A
- The SOT−223 Package Can Be Soldered Using Wave or Reflow.
- SOT−223 package ensures level mounting, resulting in improved thermal conduction, and allows visual inspection of soldered joints. The formed leads absorb thermal stress during soldering, eliminating the possibility of damage to the die.
- NPN Complement is BCP68
- AEC−Q101 Qualified and PPAP Capable
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant





SOT−223 (TO−261)
CASE 318E
STYLE 1

MARKING DIAGRAM



CE = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	−20	Vdc
Collector−Base Voltage	V_{CBO}	−25	Vdc
Emitter−Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current	I_C	−1.0	Adc
Total Power Dissipation @ T_A = 25°C (Note 1) Derate above 25°C	P_D	1.5 12	W mW/°C
Operating and Storage Temperature Range	T_J, T_{stg}	−65 to 150	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance − Junction−to−Ambient (Surface Mounted)	$R_{\theta JA}$	83.3	°C/W
Lead Temperature for Soldering, 0.0625 in from case Time in Solder Bath	T_L	260 10	°C s

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Device mounted on a glass epoxy printed circuit board 1.575 in. x 1.575 in. x 0.059 in.; mounting pad for the collector lead min. 0.93 sq. in.

ORDERING INFORMATION

Device	Package	Shipping†
BCP69T1G	SOT−223 (Pb−Free)	1000 / Tape & Reel
NSVBCP69T1G	SOT−223 (Pb−Free)	1000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2011

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristics	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (I_C = −100 μAdc, I_E = 0)	$V_{(BR)CES}$	−25	–	–	Vdc
Collector−Emitter Breakdown Voltage (I_C = −1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	−20	–	–	Vdc
Emitter−Base Breakdown Voltage (I_E = −10 μAdc, I_C = 0)	$V_{(BR)EBO}$	−5.0	–	–	Vdc
Collector−Base Cutoff Current (V_{CB} = −25 Vdc, I_E = 0)	I_{CBO}	–	–	−10	μAdc
Emitter−Base Cutoff Current (V_{EB} = −5.0 Vdc, I_C = 0)	I_{EBO}	–	–	−10	μAdc
ON CHARACTERISTICS					
DC Current Gain (I_C = −5.0 mAdc, V_{CE} = −10 Vdc) (I_C = −500 mAdc, V_{CE} = −1.0 Vdc) (I_C = −1.0 Adc, V_{CE} = −1.0 Vdc)	h_{FE}	 50 85 60	 – – –	 – 375 –	–
Collector−Emitter Saturation Voltage (I_C = −1.0 Adc, I_B = −100 mAdc)	$V_{CE(sat)}$	–	–	−0.5	Vdc
Base−Emitter On Voltage (I_C = −1.0 Adc, V_{CE} = −1.0 Vdc)	$V_{BE(on)}$	–	–	−1.0	Vdc
DYNAMIC CHARACTERISTICS					
Current−Gain − Bandwidth Product (I_C = −10 mAdc, V_{CE} = −5.0 Vdc)	f_T	–	60	–	MHz

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 1. DC Current Gain



Figure 2. Current Gain Bandwidth Product

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 3. Collector Emitter Saturation Voltage vs. Collector Current



Figure 4. Base Emitter Saturation Voltage vs. Collector Current



Figure 5. Base Emitter Voltage vs. Collector Current



Figure 6. Capacitances



Figure 7. Safe Operating Area

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Downloaded from Arrow.com.