

1A, 40V - 200V Schottky Barrier Surface Mount Rectifier

FEATURES

- Low power loss, high efficiency
- Ideal for automated placement
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Switch Mode Power Supply
- Adapters
- On board DC/DC converter

MECHANICAL DATA

- Case: SOD-123FL
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1 whisker test
- Polarity: Indicated by cathode band
- Weight: 0.019g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	1	A
V_{RRM}	40-200	V
I_{FSM}	30	A
$T_J \text{ MAX}$	125,150	°C
Package	SOD-123FL	



SOD-123FL



ABSOLUTE MAXIMUM RATINGS (T _A = 25°C unless otherwise noted)								
PARAMETER		SYMBOL	SS14 FL	SS16 FL	SS110 FL	SS115 FL	SS120 FL	UNIT
Marking code on the device			14FL	16FL	110FL	115FL	120FL	
Repetitive peak reverse voltage		V _{RRM}	40	60	100	150	200	V
Reverse voltage, total rms value		V _{R(RMS)}	28	42	70	105	140	V
DC blocking voltage		V _{DC}	40	60	100	150	200	V
Forward current		I _F	1					A
Surge peak forward current single half sine-wave superimposed on rated load	t = 8.3ms	I _{FSM}	30					A
	t = 1.0ms		60					A
Junction temperature		T _J	-55 to +125	-55 to +150				°C
Storage temperature		T _{STG}	-55 to +150					°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-lead thermal resistance	$R_{\theta JL}$	56	°C/W
Junction-to-ambient thermal resistance	$R_{\theta JA}$	135	°C/W
Junction-to-case thermal resistance	$R_{\theta JC}$	83	°C/W

Thermal Performance Note: Units mounted on PCB (5mm x 5mm Cu pad test board)

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage ⁽¹⁾	SS14FL	$I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$	V_F	0.46	-	V
		$I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$		0.52	0.55	V
		$I_F = 0.5\text{A}, T_J = 100^\circ\text{C}$		0.37	-	V
		$I_F = 1.0\text{A}, T_J = 100^\circ\text{C}$		0.46	0.52	V
	SS16FL	$I_F = 0.5\text{A}, T_J = 125^\circ\text{C}$		0.51	-	V
		$I_F = 1.0\text{A}, T_J = 125^\circ\text{C}$		0.63	0.70	V
		$I_F = 0.5\text{A}, T_J = 125^\circ\text{C}$		0.46	-	V
		$I_F = 1.0\text{A}, T_J = 125^\circ\text{C}$		0.56	0.62	V
	SS110FL	$I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$		0.68	-	V
		$I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$		0.77	0.85	V
		$I_F = 0.5\text{A}, T_J = 125^\circ\text{C}$		0.56	-	V
		$I_F = 1.0\text{A}, T_J = 125^\circ\text{C}$		0.63	0.70	V
	SS115FL	$I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$		0.74	-	V
		$I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$		0.79	0.85	V
		$I_F = 0.5\text{A}, T_J = 125^\circ\text{C}$		0.60	-	V
		$I_F = 1.0\text{A}, T_J = 125^\circ\text{C}$		0.65	0.74	V
	SS120FL	$I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$		0.79	-	V
		$I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$		0.85	0.95	V
		$I_F = 0.5\text{A}, T_J = 125^\circ\text{C}$		0.64	-	V
		$I_F = 1.0\text{A}, T_J = 125^\circ\text{C}$		0.71	0.80	V
Reverse current @ rated V_R ⁽²⁾	SS14FL	$T_J = 25^\circ\text{C}$	I_R	-	0.5	mA
		$T_J = 100^\circ\text{C}$		-	5	mA
	SS16FL	$T_J = 25^\circ\text{C}$		-	0.5	mA
		$T_J = 125^\circ\text{C}$		-	7	mA
	SS110FL SS115FL SS120FL	$T_J = 25^\circ\text{C}$		-	0.1	mA
		$T_J = 125^\circ\text{C}$		-	1	mA
Junction capacitance	SS14FL	1MHz, $V_R = 4.0\text{V}$	C_J	67	-	pF
	SS16FL			44	-	pF
	SS110FL			28	-	pF
	SS115FL			22	-	pF
	SS120FL			18	-	pF

Notes:

- (1) Pulse test with PW = 0.3ms
- (2) Pulse test with PW = 30ms

ORDERING INFORMATION		
ORDERING CODE⁽¹⁾	PACKAGE	PACKING
SS1xFL M3G	SOD-123FL	3,000 / 7" reel
SS1xFL M2G	SOD-123FL	10,000 / 13" reel

Notes:

- (1) "x" defines voltage from 40V(SS14FL) to 200V(SS120FL)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Reverse Characteristics





Fig.6 Typical Forward Characteristics



CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.7 Typical Reverse Characteristics




Fig.8 Typical Forward Characteristics




Fig.9 Typical Reverse Characteristics




Fig.10 Typical Forward Characteristics




Fig.11 Typical Reverse Characteristics






Fig.12 Typical Forward Characteristics



CHARACTERISTICS CURVES


($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.13 Typical Transient Thermal Impedance




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

SOD-123FL



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	1.15	1.45	0.045	0.057
b	0.80	1.20	0.031	0.047
c	0.10	0.30	0.004	0.012
D	1.60	2.00	0.063	0.079
E	3.50	3.90	0.138	0.154
E1	2.60	3.00	0.102	0.118
L	0.35	0.85	0.014	0.033

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	1.50	0.059
B	1.00	0.039
C	2.90	0.114
D	1.90	0.075
E	3.90	0.154

MARKING DIAGRAM



P/N = Marking Code
 YW = Date Code
 F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.