

Part Number: <u>1731120270</u>

Product Description: FCT High Power Contact, Male, Straight, PCB Through Hole, 0.80µm Gold Mating

Plating, 5.00µm Tin Termination Plating, 20.0A,

2.90mm PCB Drilling Diameter **Series Number:** 173112

Status: Active

Product Category : D-Sub Contacts **Engineering Number :** FMP014P104



Documents & Resources

Drawings

1731120270_sd.pdf

STEP AP242

SOLIDWORKS

Creo

Symbol and Footprint (Multi-Format)

Specifications

1731120008-PK-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ⊚ per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

• EU RoHS

- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

| Status | Active |
|--------------|--|
| Category | D-Sub Contacts |
| Series | 173112 |
| Description | FCT High Power Contact, Male, Straight, PCB Through Hole, 0.80µm Gold Mating Plating, 5.00µm Tin Termination Plating, 20.0A, 2.90mm PCB Drilling Diameter |
| Contact Type | High Power |
| Magnetic | Yes |
| Product Name | FCT Products |
| Туре | Mixed Layout |
| UPC | 889056721523 |

Electrical

| Current - Maximum per Contact | 20.0A |
|-------------------------------|-------|
| l l | |

Physical

| Durability (mating cycles min) | 500 |
|--------------------------------|--------------|
| Gender | Male |
| Material - Contact | Copper Alloy |

| Material - Plating Mating | Gold over Nickel |
|--------------------------------|------------------|
| Material - Plating Termination | Tin over Nickel |
| Material - Retaining Clip | Copper Alloy |
| Net Weight | 1.600/g |
| Orientation | Straight |
| Packaging Type | Bag |
| Plating min - Mating | 0.800µm |
| Plating min - Termination | 5.000µm |
| Temperature Range - Operating | -55° to +155°C |
| Termination Style | Through Hole |

Mates With / Use With

Use with Part(s)

| Description | Part Number |
|-------------|-----------------------------|
| Use With | FCT Mixed Layout Connectors |

Application Tooling

Global

| Description | Part Number |
|---|-------------------|
| FCT Removal Tool for Size 8 Contacts | <u>1731121747</u> |

This document was generated on Sep 10, 2025