# molex

Part Number: <u>1120985007</u>

**Product Description :** Brad HarshIO Digital Module for CANopen, Compact 30mm, IP67, 8 Ports M8, 8

Inputs,PNP

Series Number: 112098

Status: Obsolete

Product Category: Industrial I/O Modules Engineering Number: TBDCO-880P-804



#### **Documents & Resources**

#### **3D Models and Design Files**

STEP AP242

SOLIDWORKS

Creo

## **Product Environment Compliance**

#### **Compliance**

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

#### **Compliance Statements**

- EU RoHS
- REACH SVHC
- Low-Halogen

#### **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### Substances of Interest

## **EU RoHS Certificate of Compliance**

## <u>Additional Product Compliance Information</u>

## **Part Details**

#### General

Status	Obsolete
Category	Industrial I/O Modules
Series	112098
Description	Brad HarshIO Digital Module for CANopen, Compact 30mm, IP67, 8 Ports M8, 8 Inputs ,PNP
Application	Filling and Packaging Machines, Machine Tool Industry, Material Handling Systems
Approvals	CiA, UL, cUL, CE
IP Rating	1P67
Product Name	HarshlO CanOpen
Protocol	CANopen
UPC	883906226688

## **Agency**

UL	E200650
----	---------

#### **Electrical**

Current - Maximum Output	N/A
EMC	IEC 61000-6-2
Input Delay	2.5ms
Input Device Supply	200 mA per port at 25°C
Input Type	PNP or Dry Contact

## Physical

Bus Input	5-pole Micro-Change (M12), A- Coded, Male
Bus Output	5-pole Micro-Change (M12), A- Coded, Female

Format	Compact (30mm)
Housing Width	30.00mm
I/O Connector	3-pole Nano-Change (M8), Female
I/O Ports	8x M8
I/O Signal Mix	8 input
Mechanical Shock	10G, 11ms, 3 AXIS
Net Weight	0.201/kg
Power Input	Via Bus Connector
Power Output	None
Temperature Range - Operating	-25°C to +70°C
Vibration	IEC 60068-2-6

This document was generated on Sep 17, 2025