



**Part Number :** [643191211](#)  
**Product Description :** .635mm, 1.50mm, CMC  
Receptacle, 32 Circuits, Left Wire Output,  
Black Coding, Mat Sealed  
**Series Number :** 64319  
**Status :** Active  
**Product Category :** Connector Housings



## Documents & Resources


**Drawings**  
[643191211\\_sd.pdf](#)

**3D Models and Design Files**  
[643191211\\_stp.zip](#)

**Specifications**  
[AS-64319-002-001.pdf](#)  
[AS-64319-002-CH-001.pdf](#)  
[AS-64319-002-FR-001.pdf](#)  
[AS-64319-002-SP-001.pdf](#)  
[984200002-AS-KR-000.pdf](#)  
[AS-98420-002-001.pdf](#)  
[AS-98420-002-CH-001.pdf](#)  
[AS-98420-002-FR-001.pdf](#)  
[AS-98420-002-SP-001.pdf](#)  
[PK-64319-001-001.pdf](#)  
[PS-64319-001-001.pdf](#)  
[PS-64319-002-001.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Compliant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21

REACH SVHC	Contains Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane; Octamethylcyclotetrasiloxane per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Connector Housings
Series	64319
Description	.635mm, 1.50mm, CMC Receptacle, 32 Circuits, Left Wire Output, Black Coding, Mat Sealed
Application	Automotive, Power, Wire-to-Board
Comments	Current tested on a 5 terminals loaded connector, current for temperature increase of 40°C; Current max = 6.0A for 0.635mm Terminal (0.75mm <sup>2</sup> wire) and 12.0A for 1.50mm Terminal (2.00mm <sup>2</sup> wire)
More Detailed Tech Information	Sealed, high-density, modular connecting system for Power Train and Body Electronics applications in cars, trucks, busses
Product Name	CMC
UPC	883906129736

### Physical

Circuits Detail	8 x 1.5mm & 24 x 0.635mm terminals
Circuits (maximum)	32
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Polyester
Net Weight	29.426/g
Number of Rows	4
Packaging Type	Carton
Panel Mount	No
Pitch - Mating Interface	2.54mm, 3.70mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +125°C

## Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

---

## Mates With / Use With

### Mates with Part(s)

Description	Part Number
2.50mm, 3.70mm CMC Header, Right-Angle, 32 Circuits, 1 Port, Black	<u>643340100</u>

### Use with Part(s)

Description	Part Number
CMC Wire Cap for 32 Circuits, CMC Receptacle Mat Sealed	<u>643191201</u>
CMC 0.635mm Blind Cavity Plug	<u>643251010</u>
CMC 1.50mm Blind Cavity Plug	<u>643251023</u>
0.635mm CMC CP Female Terminals	<u>64322</u>

1.50mm CMC CP Female Terminals	64323
--------------------------------	-------

---

## Application Tooling

### Global

Description	Part Number
Continuity Test Pen Assembly	<u>638121100</u>
Unlocking Tool for CMC and CMX Receptacle Connector	<u>638241200</u>

---

This document was generated on Mar 08, 2025