

EMLP 24 (30X12) SR - Plastic label with drill hole



0822330

<https://www.phoenixcontact.com/us/products/0822330>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plastic label with drill hole, Card, silver, unlabeled, can be labeled with: PLOTMARK, ENGRAVING UNIT, CMS-P1-PLOTTER, P1 ENGRAVING UNIT, mounting type: adhesive, lettering field size: 30 x 12 mm, Number of individual labels: 8

Your advantages

- Can be engraved using the P1 ENGRAVING UNIT
- High-quality appearance
- Labeling service: Phoenix Contact can custom-label all EMLP ... markers in accordance with your requirements
- For marking components, devices, and buttons
- Can be labeled easily using the CMS-P1-PLOTTER
- High level of resistance to chemical and mechanical influences

Commercial data

Item number	0822330
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG16
Product key	BG2411
Catalog page	Page 347 (C-3-2019)
GTIN	4046356319379
Weight per piece (including packing)	19.2 g
Weight per piece (excluding packing)	19.2 g
Customs tariff number	39269097
Country of origin	PL

EMLP 24 (30X12) SR - Plastic label with drill hole



0822330

<https://www.phoenixcontact.com/us/products/0822330>

Technical data

Product properties

Product type	Device marking
Marking	
Number of individual labels	8
Number of individual labels per row	2
Identification technology	Plotter

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Adhesive strength	50 µm
Adhesive	Acrylic
Color	silver
Material	TRANSPLY-ABS
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
---------------	---------------------------

EMLP 24 (30X12) SR - Plastic label with drill hole



0822330

<https://www.phoenixcontact.com/us/products/0822330>

Result	Test passed
Ambient conditions	
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	4 °C ... 38 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	12 months

Dimensions

Width	30 mm
Length	40 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

EMLP 24 (30X12) SR - Plastic label with drill hole



0822330

<https://www.phoenixcontact.com/us/products/0822330>

Classifications

ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

ETIM

ETIM 9.0	EC001288
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

EMLP 24 (30X12) SR - Plastic label with drill hole



0822330

<https://www.phoenixcontact.com/us/products/0822330>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

EMLP 24 (30X12) SR - Plastic label with drill hole

0822330

<https://www.phoenixcontact.com/us/products/0822330>



Accessories

P1 ENGRAVING UNIT - Engraving unit

5145546

<https://www.phoenixcontact.com/us/products/5145546>

Engraving unit, weight: 7.6 kg, length: 0.35 m, width: 250 mm




PLOTMARK - Marking plotter

0804499

<https://www.phoenixcontact.com/us/products/0804499>

Marking plotter for the entire portfolio of UC marking materials and materials in sheet and strip format.



EMLP 24 (30X12) SR - Plastic label with drill hole

0822330

<https://www.phoenixcontact.com/us/products/0822330>




CMS-P1-PLOTTER - Marking plotter

5144615

<https://www.phoenixcontact.com/us/products/5144615>

Marking plotter, weight: 8 kg, length: 0.66 m, width: 440 mm, height: 125 mm, color: silver



CMS-P1-M/GPE ENGRAVING - Magazine

5145711

<https://www.phoenixcontact.com/us/products/5145711>

Magazine for CMS-P1-PLOTTER, to accommodate GPE materials, especially for the purpose of engraving



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com