



+ RELAYS, CONTACTORS & SWITCHES

STANDARD POWER RELAYS



✓ Active

TE CONNECTIVITY (TE)

RZ01-1A4-D005-R

3-2158000-5

TE Internal Number: 3-2158000-5

- EU RoHS Compliant
- EU ELV Compliant
- Contact Current Rating (A) 16
- Coil Power Rating (DC) (mW) 400
- Insulation Clearance Class 8
- Insulation Creepage Class 8
- Terminal Type PCB-THT

DOCUMENTATION

No documentation available.

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Electrical Characteristics

- Coil Power Rating (DC) (mW) 400
- Insulation Creepage Class 8
- Coil Voltage Rating (VDC) 5
- Contact Voltage Rating (VAC) 400
- Contact Voltage Rating (VDC) 300
- Contact Switching Voltage (Max) (VAC) 400
- Contact Switching Voltage (Max) (VDC) 300
- Insulation Creepage Between Contact and Coil (mm) 10

Contact Features

**Contact Current Rating (A)** 16  
**Terminal Type** PCB-THT  
**Contact Arrangement** 1 Form A (NO)  
**Contact Number of Poles** 1  
**Contact Material** AgNi90/10

Dimensions

**Insulation Clearance Class** 8  
**Length (mm)** 29  
**Width (mm)** 12.7  
**Height (mm)** 15.7

Usage Conditions

**Environmental Category of Protection** RTII  
**Environmental Ambient Temperature Class (°C)** -40 – 85  
**Environmental Ambient Temperature (Max) (°F)** 85

Other

**Accessories/Socket Type** Socket

Statement of Compliance

**Statement of Compliance**  
PDF