

MC9S08DV60AMLF Information

[Product Summary Page](#)

- ▶ [General Information](#)
- ▶ [Package Information](#)
- ▶ [Environmental and Compliance Information](#)
- ▶ [Manufacturing Information](#)
- ▶ [Ordering Information](#)
- ▶ [Product/Process Change Notice \(PCN\)](#)
- ▶ [Operating Characteristics](#)
- ▶ [Reliability Data Lookup](#)

General Information

Parameter	Value
Part Number	MC9S08DV60AMLF
Description	S08DV 8-bit MCU, S08 core, 60KB Flash, 40MHz, QFP 48
Product Line	G9FZDZ62
PTI	MDTD
Material Type	Tested Packaged Device
Life Cycle Description (code)	REMOVED FROM ACTIVE PORTFOLIO
Status	No Longer Manufactured
Application/Qualification Tier	10-YEARS APPLICATION LIFE

Package Information

Parameter	Value
Package Type and Termination Count	QFP 48
Package Description and Mechanical Drawing	LQFP 48 7*7*1.4P0.5
Device Weight(g)	.17825
Package Material	Plastic
Mounting Style	Surface Mount
Package Length (nominal)(mm)	7.000
Package Width (nominal)(mm)	7.000
Package Thickness (nominal)(mm)	1.400
Maximum Height Above Board(mm)	1.600
Tape & Reel	No

Environmental and Compliance Information

Parameter	Value
Pb-Free	
RoHS Compliant	
Halogen Free	Yes
Material Composition Declaration (MCD)	Download MCD Report  Download MCD Report 
RoHS Certificate of Analysis (CoA)	Download RoHS CoA Report
2nd Level Interconnect	e3
Moisture Sensitivity Level (MSL)	3
Floor Life	168 HOURS
Peak Package Body Temperature (PPT)(°C)	260
Maximum Time at Peak Temperature (s)	40
Number of Reflow Cycles	3
REACH SVHC	Freescaler REACH Statement
UL94 (plastics flammability test)	V0: Burning stops within 10 seconds on a vertical specimen; no drips allowed

Manufacturing Information

Parameter	Value
Micron Size(?m)	.25

Ordering Information

Parameter	Value
Exempt from Minimum Delivery Value	Yes
Export Control Classification Number (US)	3A991
Harmonized Tariff (US) Disclaimer	8542.31.0000
CCATS Document	-
ENC Status	-
Other Trade Compliance Documents	-
Budgetary Price excluding tax(US\$) Change Currency	-
Device Sample Availability	03 Nov2008
Device Production Availability	03 Nov2008
Order	

Product/Process Change Notice (PCN)

Number	Type	Title	Issue Date	Effectivity Date
15375	Product Bulletin	DZ60 2M74K ERRATA DISTRIBUTION	21 Sep 2012	22 Sep 2012
14999	Product Change Notice	9S08DZ60 0.25UM Copper Wire Qualification	02 Feb 2012	02 May 2012
14886	Product Bulletin	S08DZ60 Input Hysteresis Tuning	03 Oct 2011	12 Oct 2011
14726	Product Change Notice	MC9S08DZ60 IMM Product Mask Revision	09 Jun 2011	07 Sep 2011
14515	Product Change Notice	0.25UM Copper Wire Qualification	26 Apr 2011	10 Sep 2011
13796	Product Bulletin	9S08 D-Family Consumer and Industrial Parts Burn-in Elimination	01 Sep 2009	02 Sep 2009

Operating Characteristics

Parameter	Value
Additional Features	COP Low Voltage Detect POR Temperature Sensor Internal Voltage Regulator Analog Comparator
Ambient Operating Temperature (Min-Max) (°C)	-40 to 125
Bus Frequency (Max) (MHz)	20
Core: Type	S08
GPIOs	40
Internal Flash (KB)	60
Internal RAM (KB)	3
Operating Frequency (Max) (MHz)	40
Sample Exception Availability	N
Serial Interface - Number of Serial Interfaces	1 1 2 1
Serial Interface - Serial Interface Type	CAN I2C SCI SPI
Supply Voltage (Min-Max) (V)	2.7 to 5.5
Timer Features	Input Capture Output Compare PWM Watchdog
Timer type	Real Time Clock
Timers - Number of Timers	1 1
Timers - Timer Channels	6 2
Timers - Timer Size (bit)	16 16

[Reliability Data Lookup](#)

Downloaded from [Arrow.com](#)