



Pushing Performance  
Since 1945

# M12 MD PP IDC CC Male Straight 8Pol Xcod



Image is for illustration purposes only. Please refer to product description.

Part number	21 12 283 1830
Specification	M12 MD PP IDC CC Male Straight 8Pol Xcod
HARTING eCatalogue	<a href="https://harting.com/21122831830">https://harting.com/21122831830</a>

## Identification

Category	Connectors
Series	Circular connectors M12
Identification	PushPull
Element	Cable connector
Specification	Straight

## Version

Termination method	IDC termination
Gender	Male
Shielding	Shielded
Number of contacts	8
Coding	X-coding
Locking type	Outer PushPull

## Technical characteristics

Wire outer diameter	0.9 ... 1.6 mm
Rated current	0.5 A
Rated impulse voltage	0.8 kV
Pollution degree	3
Transmission characteristics	Cat. 6 <sub>A</sub> Class E <sub>A</sub> up to 500 MHz
Overvoltage category	III
Data rate	10 Gbit/s
Insulation resistance	>10 <sup>8</sup> Ω



**Pushing Performance**  
Since 1945

## Technical characteristics

Contact resistance	≤10 mΩ
Limiting temperature	-40 ... +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	5.7 ... 8.8 mm
Isolation group	I (600 ≤ CTI)

## Material properties

Material (insert)	PA66
Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	IEC 61076-2-109 acc. to IEC 61076-2-010
----------------	--

## Commercial data

Packaging size	1
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140568761
ETIM	EC002635



**Pushing Performance**  
Since 1945

## Commercial data

eCl@ss

27440116 Circular connector (for field assembly)

---