

Part Number: 5035665102

Product Description: 0.30mm Pitch Easy-On FPC Connector, Right-Angle, Bottom Contact, 0.95mm Height, 51 Circuits, Gold over Nickel

Plating

Series Number: 503566

Status: Active

Product Category: FFC / FPC Connectors



Documents & Resources

Drawings

5035665102_sd.pdf

3D Models and Design Files

5035665102_stp.zip

Specifications

5035660000-A00.pdf

5035669200-200.pdf

5035660000-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|--------------|--|
| Category | FFC / FPC Connectors |
| Series | 503566 |
| Description | 0.30mm Pitch Easy-On FPC Connector, Right-Angle, Bottom Contact, 0.95mm Height, 51 Circuits, Gold over Nickel Plating |
| Product Name | Easy-On |
| UPC | 191128129916 |

Electrical

| Current - Maximum per Contact | 0.3A |
|-------------------------------|------|
| Voltage - Maximum | 50V |

Physical

| Actuator Type | Front Flip |
|--------------------------------|------------------------|
| Circuits (Loaded) | 51 |
| Circuits (maximum) | 51 |
| Color - Resin | Natural |
| Contact Position | Bottom |
| Durability (mating cycles max) | 10 |
| Mated Height | 0.95mm |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Gold |
| Material - Resin | Liquid Crystal Polymer |
| Net Weight | 71.614/mg |
| Orientation | Right Angle |

| Packaging Type | Embossed Tape on Reel |
|-------------------------------|-----------------------|
| PCB Locator | No |
| PCB Mounting | Surface Mount |
| PCB Retention | None |
| Pitch - Mating Interface | 0.30mm |
| Polarized to PCB | Yes |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |
| Wire/Cable Type | FPC only |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|--------------|
| 0.30mm Pitch Premo-Flex FPC Jumpers with Latching Ears | <u>15032</u> |

This document was generated on Mar 18, 2025