

MHQ0603P2N4BT000

Product Status	Production		
Applications	Commercial Grade		
Feature	Multilayer Non-Mag CoreNon-Magnetic Core (Dielectric Ceramic) Super High QSuper High Q		
Series Type	MHQ-P		
Brand	TDK		
Environmental Compliance	ROHS REACH Halogen Free Lead Free		



Size		
Length(L)	0.65mm ±0.05mm	
Width(W)	0.35mm ±0.05mm	
Thickness Height	0.35mm ±0.05mm	
Recommended Land Pattern (A)	0.25mm Nom.	
Recommended Land Pattern (B)	0.30mm Nom.	
Recommended Land Pattern (C)	0.30mm Nom.	

Electrical Characteristics		
Inductance	2.4nH ±0.1nH at 500MHz	
Rated Current	700mA	
DC Resistance [Typ.]	80mΩ	
DC Resistance [Max.]	150mΩ	
Self Resonant Frequency [Min.]	8GHz	
Self Resonant Frequency [Typ.]	11.7GHz	
Q [Min.]	16 at 500MHz	
Q [Typ.]		

C	Other
Operating Temp. Range	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	NO
Packing	Punched (Paper)Taping [180mm Reel, Tape width 8mm]
Package Quantity	15000pcs
Weight	0.0002g


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.


 $^{! \ \}mbox{All specifications}$ are subject to change without notice.


MHQ0603P2N4BT000

Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)










[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

MHQ0603P2N4BT000

Associated Images





[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.