

# Product Data Sheet

Colibri Receptacle 40,  
Part No. 402-51701-51




Illustration similar



Parallel



SMT



High Density



High Speed

- for all PCB pitch sizes
- Number of poles: 40
- SMT Connectivity
- Grid: 0.5 mm
- Data transfer rate up to 25+ Gbps
- for PCIe Gen 4



» to product on [www.ept.de](http://www.ept.de)



» to product group Colibri - 0.5 mm SMT

# Product Data Sheet

Colibri Receptacle 40,  
Part No. 402-51701-51



## Technical Specifications

### Basics

No. of Contacts	40
Termination Technology	SMT
Board-to-Board Distance	5 mm & 8 mm
Operating Temperature Range	-40°F to +125°F

### Material

Insulator Material	LCP, UL 94 V-0
CTI value <i>IEC 60112</i>	175
Contact Material	copper alloy
Plating	Above Ni
Termination area	Au flash over Ni

### Mechanical

Pitch	0.5 mm
Mating Force per Pin	max. 0.9 N
Separating Force per Pin	at least 0.1 N
Durability	30 insertion cycles
Coplanarity	max. 0.1 mm
Center offset in the x direction	± 0.4 mm
Center offset in the y direction	± 0.19 mm
Axial offset when mated (x/y)	± 0.1 mm (8 mm height) / ± 0.115 mm (5 mm height)
Angular offset in the x direction	± 2°

### Electrical

Operational Current	max. 0.5 A
Operational Voltage	50 VAC
Contact Resistance	max. 75 mΩ
Clearance and Creepage	≥ 0.2 mm
Insulation Resistance	> 100 MΩ
Test Voltage	200 VAC
Data Transfer Rate	up to 25+ Gbit/s

### Processing

Soldering Temperature	260°C according to J-STD-020
MSL	1
Assembly	Pick and Place

# Product Data Sheet

Colibri Receptacle 40,  
Part No. 402-51701-51

---



## Technical Specifications

### Approval / Compliance

---

UL file	E130314
Environment	RoHS compliant

# Product Data Sheet

Colibri Receptacle 40,  
Part No. 402-51701-51

---



## Derating Diagram

# Product Data Sheet

Colibri Receptacle 40,  
Part No. 402-51701-51

---



## Modifications

Available on request

- other pole counts
- alternative contact coatings

## Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)