插頭部件 (Plug Component)			頭部剝皮尺寸 (Dimensions)			線材規格 (Wire Styls)	尾部剝皮尺寸 (Dimensions)			端子規格 (Termianl Style)	
顏色(Color)	零件描述(Component)	Qty.	內剝(Strip)	外剝(ROJ)	顏色(Color)	SVT 18AWGx3C (Shielded, A+E) 105°C 黑色 (Black)	外剝(ROJ)	內剝(Strip)	顏色(Color)	規格描述(Instruction)	端子編號(Style No.)
35P 黑色 (Black)	FM-302L(F) (IEC 60320, C13)	1	6^{+1}_{-0}	18 ± 2	黑/Black(L)		50.8±5	6.35±3	黑/Black(L)	絕緣依尺寸剝除,留膠於線上 (Strip and Retain Outside Insulated)	
銅本色 (Brass-Natural)	2.0*4.0 方管端子(GEM 98752A-0) (2.0*4.0 Receptacle Terminal)	3	6^{+1}_{-0}	18 ± 2	白/White(N)		50.8±5	6.35±3	白/White(N)	絕緣依尺寸剝除,留膠於線上 (Strip and Retain Outside Insulated)	
米白色 (Off-White)	GA005-5 品字母插兩件式內模 (Computer 2x4 Serial Housing)	1	6^{+1}_{-0}	18 ± 2	綠/Green(E)	Length : 500±20 (19.7"±0.79")	50.8±5	6.35±3	綠/Green(E)	絕緣依尺寸剝除,留膠於線上 (Strip and Retain Outside Insulated)	





FM-302L (IEC 60320, C13, RA)
(Dimensions of Connector Face)



SVT 18AWGx3C Shielded
(Wire Cross-Section)



B-C1 扎線圖示 (Tied Loop Hank Detail)

REV	DATE	REVISE CONTENT
A	08/30-2012	The first edition is issued and drawing.

NOTE :
1、Hi-Pot Test : 1500V/1Sec ; <0.5mA.
2、Insulation Resistance Test : DC 500/min>100 meg-ohm.
3、Continuity & Polarization Test : No short circuit, break circuit, displacement.
4、Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
5、Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
6、All material according to Non-toxic standard.(Material must be RoHS compliant.)
7、"FMC" logo maybe present on C13.

線材印字 (Wire Printed)	充麻, 油墨印字 (Fillers, Printing Ink)		
包裝方式 (Packing)		DRAWN	Chu8..
Tied Hank	See Hank Detail		
Carton Size	480 x 320 x 150		
Pack Number	200pcs/ UL Laster Labels	DATE	08/30-2012
Carton Print	See Purchase Order		
TYPE	IEC 60320, C13 RA to ROJ(S&R) Power Supply Cord		
DRAWNING NO.	098MM1000	REV	A

CnC Tech, LLC
Industrial Cable and Connector Technology

CUSTOMER	CnC		
P/N No.	800-1803-2-SVT0-BL-00050		
MATERIAL	PVC	UNIT	mm
Customer Approval			

業務校閱：
品管校閱：

Downloaded from Arrow.com.