



Color: ■ gray

Material data

Color	gray
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.043 MJ
Weight	1.4 g

Commercial data

Product Group	2 (Terminal Block Accessories)
PU (SPU)	50 pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332270816
Customs tariff number	39269097900

Product Classification

UNSPSC	39121703
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-109

↓

Documentation				
Bid Text				
249-109	19.02.2019	xml	2.45 KB	↓
249-109	18.08.2017	doc	23.00 KB	↓

CAD/CAE-Data

CAD data

2D/3D Models 249-109

↓

CAE data

WSCAD Universe 249-109

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marker



Item No.: 209-501/000-006
WSB marking card; as card; not stretchable; plain; snap-on type; blue



Item No.: 209-501/000-007
WSB marking card; as card; not stretchable; plain; snap-on type; gray



Item No.: 209-501/000-023
WSB marking card; as card; not stretchable; plain; snap-on type; green



Item No.: 209-501/000-017
WSB marking card; as card; not stretchable; plain; snap-on type; light green



Item No.: 209-501/000-012
WSB marking card; as card; not stretchable; plain; snap-on type; orange



Item No.: 209-501/000-005
WSB marking card; as card; not stretchable; plain; snap-on type; red



Item No.: 209-501/000-024
WSB marking card; as card; not stretchable; plain; snap-on type; violet




Item No.: 209-501
WSB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 209-501/000-002
WSB marking card; as card; not stretchable; plain; snap-on type; yellow

Installation Notes


Installation



Clipping a wire harness support into the marker slot.

Inserting a cable into the wire harness support.

2 x group marking on top
1 x terminal block marking at the bottom



Terminal blocks for matrix patching with wire harness supports:

For 5 mm wide double-potential terminal blocks, two 3-conductor through terminal blocks are offered in one insulating housing on one level. This achieves a width of just 2.5 mm (0.098 inch) versus standard through terminal blocks. On each side of the terminal block are marker slots for WAGO WMB Inline markers. Via the available accessories, these terminal blocks can also be used as 4-conductor disconnect terminal blocks or potential multipliers.

The WAGO wire harness supports are pushed into the terminal blocks (approx. every 8th unit) to form an additional "cable-duct" above the wiring level of the terminal blocks. The two marker slots on the top may be used for group marking, while the lower slot is used for marking the terminal block.