

Product data sheet

Specifications



APC NetShelter Aisle Containment,
Depth Adapter, 600 to750 mm, for
1070 to 1200 mm 42U SX to 48U
SX

ACDC2551

Main

Product or component type	Adapter
---------------------------	---------

Complementary

Mounting mode	Rack-mounted
Height	130 mm
Width	600 mm
Depth	1914 mm
Net weight	18.73 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	33.000 cm
Package 1 Length	200.000 cm
Package 1 Weight	21.200 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	18
Package 2 Height	68.000 cm
Package 2 Width	110.000 cm
Package 2 Length	210.000 cm
Package 2 Weight	405.000 kg

Contractual warranty

Warranty (in months)	60
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	74 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	71 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins