



### **Product brief**


## IRS1125A

### 3D Time-of-Flight single-chip for automotive

As part of Infineon's broad XENSIV™ sensor portfolio, Infineon offers IRS1125A, the automotive qualified variant of the REAL3™ Time-of-Flight (ToF) imager family. Its unbeaten outdoor performance requires a minimum amount of active light at 850 nm and 940 nm wavelengths. Together with the high level of integration this reduces system costs, design complexity and simplifies the thermal management of the 3D camera module.

### **Key features**

- > Time-of-Flight single-chip including illumination control and digital data output
- > CIF resolution: 352 x 288 pixels (~100 k pixels)
- > Patented suppression of background illumination circuitry in every pixel for best sunlight robustness
- > Spread Spectrum Clock (SSC) to avoid interference from other infrared devices
- > Up to 100 MHz modulation frequency
- > Fast global shutter readout
- > CSI-2 or parallel data interface
- > Flexible imager operation after each frame: adaptation of frame rate, exposure time or modulation frequency
- > Optical LFBGA-84 package, 10 mm x 10 mm
- > AEC-Q100 grade 2 qualification
- $T_{Amb} = -40$ °C to 105°C



www.infineon.com/real3-automotive

### Key benefits

## The Infineon ToF solution based on IRS1125A provides

- Best performance in strong sunlight conditions with minimum amount of active light
  - ToF-optimized CMOS process
  - Patented Suppression of Background Illumination (SBI) circuitry in every pixel
  - Support of highly modulated infrared light
  - Independent data streams for brightness and distance
- Small form factor and monocular system architecture
  - Highly integrated single-chip
  - No mechanical baseline
- No risk of de-calibration over lifetime
- > Reliable mass production
  - Standard soldering process: optical BGA package without need of underfiller material
  - AEC-Q100 grade 2 qualified
  - Fast and easy once-in-a-lifetime camera calibration

In corporation with pmdtechnologies AG



### Key applications

- > Car in-cabin sensing
- > Gesture control
- > Short range car exterior (~10 m)

# IRS1125A

### 3D Time-of-Flight single-chip for automotive

Time-of-flight technology is directly measuring the depth and amplitude information in every pixel by using modulated infrared light. The infrared light is emitted to the whole scenery and the reflected light is captured by the ToF imager. The measured phase difference between emitted and received light as well as the amplitude values are resulting into highly reliable distance information and a greyscale picture of the complete scene simultaneously in all ambient light conditions - at night, in sunlight and heavily changing light conditions. Additional benefits compared to other depth sensing technologies are the simple and robust design of a ToF camera module without the need of any mechanical baseline, fast camera calibration for easy and robust mass production and a comparatively lean computational load of the application processor.



Front view - ToF data as overlay of depth and amplitude



Rotated side view - ToF data as 3D pointcloud

Colour-coded distance visualization: red = close blue = far

### **Product variants**

Product type	Pixel resolution	Description	Package
IRS1125A	352 x 288 pixel (~100k pixel)	Single-chip ToF sensor, AEC-Q100 grade 2 qualified	LFBGA-84

Start of production in Q2/2019; ordering details on request

### **Evaluation tools**

To evaluate Infineon's REAL3<sup>™</sup> time-of-flight technology, a set of 3D reference cameras is available (consumer grade). The CamBoard pico family has been designed by our development partner pmdtechnologies and comes along with a powerful SDK providing a high quality depth map for evaluation and application software development.

For further details and ordering please visit http://pmdtec.com/picofamily/







Published by Infineon Technologies AG 81726 Munich, Germany

© 2018 Infineon Technologies AG. All Rights Reserved.

THIS DOCUMENT IS FOR INFORMATION PURPOSES ONLY AND ANY INFORMATION GIVEN HEREIN SHALL IN NO EVENT BE REGARDED AS A WARRANTY, GUARANTEE OR DESCRIPTION OF ANY FUNCTIONALITY, CONDITIONS AND/OR QUALITY OF OUR PRODUCTS OR ANY SUITABILITY FOR A PARTICULAR PURPOSE. WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF OUR PRODUCTS, WE KINDLY ASK YOU TO REFER TO THE RELEVANT PRODUCT DATA SHEETS PROVIDED BY US. OUR CUSTOMERS AND THEIR TECHNICAL DEPARTMENTS ARE REQUIRED TO EVALUATE THE SUITABILITY OF OUR PRODUCTS FOR THE INTENDED APPLICATION.

WE RESERVE THE RIGHT TO CHANGE THIS DOCUMENT AND/OR THE INFORMATION GIVEN HEREIN AT ANY TIME.

### Additional information

For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

### Warnings

Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any lifeendangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury

Order Number: B142-I0746-V1-7600-EU-EC-F