



Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- RoHS Product List
- Customer Feedback

Home> Products > Speed and Direction- Variable Reluctance Speed Sensors> General Purpose > Product Page

3010A



Actual product appearance may vary.

General Purpose VRS Sensor, 15,9 mm [0.625 in] M16 diameter, 40 Vp -p, -55 °C to 120 °C [-67 °F to 250 °F], 24 DP (module 1.06) or coarser, 50 kHz, 64 mm [2.50 in] approx. length

Features

Self-powered operation  
Direct conversion of actuator speed to output frequency  
Simple installation  
No moving parts  
Designed for use over a wide range of speeds  
Adaptable to a wide variety of configurations  
Customized VRS products for unique speed sensing applications  
Housing diameters: 5/8 in (M16), 3/8 in (M12) mm, 1/4 in (M8), 10/32 in  
Housing materials/styles: stainless steel threaded or smooth  
Terminations: MS3106 connector, preleaded  
Output voltages: 8 Vp-p to 40 Vp-p

Potential Applications

Engine RPM (revolutions per minute) measurement on aircraft, automobiles, boats, buses, trucks and rail vehicles  
Motor RPM measurement on drills, grinders, lathes and automatic screw machines  
Motor RPM measurement on precision camera, tape recording and motion picture equipment  
Process speed measurement on food, textile, paper, woodworking, printing, tobacco and pharmaceutical industry machinery  
Motor speed measurement of electrical generating equipment  
Speed measurement of pumps, blowers, mixers, exhaust and ventilating fans  
Flow measurement on turbine meters  
Wheel-slip measurement on autos and locomotives  
Gear speed measurement

General Purpose VRS sensors are designed for use in applications with medium to high speeds or in electrically noisy environments with relatively small air gaps. Passive VRS (Variable Reluctance Speed) Magnetic Speed sensors are simple, rugged devices that do not require an external voltage source for operation. A permanent magnet in the sensor establishes a fixed magnetic field. The approach and passing of a ferrous metal target near the sensor's pole piece (sensing area) changes the flux of the magnetic field, dynamically changing its strength. This change in magnetic field strength induces a current into a coil winding which is attached to the output terminals. The output signal of a VRS sensor is an ac voltage that varies in amplitude and wave frequency as the speed of the monitored device changes, and is usually expressed in peak to peak voltage (Vpp). One complete waveform (cycle) occurs as each target passes the sensor's pole piece. If a standard gear were used as a target, this output signal would resemble a sine wave if viewed on an oscilloscope. Honeywell also offers VRS sensors for high output, power output, high resolution, high temperature and hazardous location applications, as well as low-cost molded versions.

Supporting Documentation

None Available

Product Specifications	
Diameter	15,9 mm [0.625 in]
Available Metric Thread	M16
Test Condition Specifications	Surface Speed = 25 m/s [1000 in/s], Gear = 20 DP [module 1.27], Air Gap = 0.127 mm [0.005 in], Load Resistance = 100 kOhm
Min. Output Voltage (Peak to Peak)	40 Vp -p
Pole Piece Shape and Size	Round; 2,69 mm [0.106 in] diameter
Typ. Operating Temperature Range	- 55 °C to 120 °C [ - 67 °F to 250 °F]
Gear Pitch Range	24 DP (module 1.06) or coarser
Typ. Operating Frequency	50 kHz
Max. Inductance	25 mH
Coil Resistance	45 Ohm to 85 Ohm
Min. Surface Speed	0,50 m/s [20 in/s]
Optimum Actuator	20 DP (module 1.27) ferrous metal gear
Mounting Thread	5/8 - 18 UNF - 2A
Vibration	Mil - Std 202F, Method 204D
Material	Stainless steel threaded
Approximate Housing Length	64 mm [2.50 in]
Termination	MS3106 Connector
Weight	70 g [2.5 oz]
Series Name	General Purpose

My Links

Login to iCOM  
Login as Rep/AD  
Login as Guest  
Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (\*) to expand search

Specification Search