



**Part Number :** [340833002](#)  
**Product Description :** MX150 Cable Seal Female  
Terminal, Tin Plating, 20-18 AWG, Left Reel Payoff  
**Series Number :** 34083  
**Status :** Active  
**Product Category :** Crimp Terminals



## Documents & Resources

### Drawings

[340833002\\_sd.pdf](#)  
[313025040-000.pdf](#)

### Specifications

[AS-34083-002-001.pdf](#)  
[PS-34083-002-001.pdf](#)  
[TS-34083-002-001.pdf](#)

## Product Environment Compliance

### Compliance

|                    |  |
|--------------------|--|
| GADSL/IMDS         | Compliant with Exemption 33; 34                    |
| China RoHS         | Not Relevant                                       |
| EU ELV             | Compliant per 2000/53/EC                           |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                     |
| REACH SVHC         | Not Contained per D(2025)4165-DC<br>(25 June 2025) |
| EU RoHS            | Compliant per EU 2015/863                          |

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### Substances of Interest

- PFAS

#### EU RoHS Certificate of Compliance

#### Additional Product Compliance Information

## Part Details

### General

|              |  |
|--------------|--|
| Status       | Active   |
| Category     | Crimp Terminals  |
| Series       | 34083  |
| Description  | MX150 Cable Seal Female Terminal, Tin Plating, 20-18 AWG, Left Reel Payoff |
| Application  | Power, Wire-to-Board, Wire-to-Wire, Automotive                             |
| Comments     | Left Reel Payoff, Cable Seal   |
| Product Name | MX150  |
| UPC          | 822350084543   |

### Electrical

|                               |               |
|-------------------------------|---------------|
| Current - Maximum per Contact | Contact Molex |
| Voltage - Maximum             | 14V DC        |

### Physical

|                                |                              |
|--------------------------------|------------------------------|
| Gender                         | Female                       |
| Grip Code                      | 18                           |
| Material - Metal               | High Performance Alloy (HPA) |
| Material - Plating Mating      | Tin                          |
| Material - Plating Termination | Tin                          |
| Net Weight                     | 0.387/g                      |
| Packaging Type                 | Reel                         |
| Plating min - Mating           | 0.508µm                      |
| Plating min - Termination      | 0.508µm                      |

|                             |                      |
|-----------------------------|----------------------|
| Termination Interface Style | Crimp or Compression |
| Wire Insulation Diameter    | 2.54mm max.          |
| Wire Size (AWG)             | 18, 20               |
| Wire Size mm <sup>2</sup>   | 0.75-1.00            |

## Solder Process Data

|                              |     |
|------------------------------|-----|
| Lead-Free Process Capability | N/A |
|------------------------------|-----|

## Mates With / Use With

### Use with Part(s)

| Description   | Part Number                  |
|---|------------------------------|
| MX150 Cable-Sealed Single Row Female Connector Assemblies | <u><a href="#">34062</a></u> |
| MX150 Cable Sealed Single Row Female Connectors           | <u><a href="#">34250</a></u> |

---

## Application Tooling

### Global

| Description   | Part Number                       |
|---|-----------------------------------|
| Extraction Toolkit for MX150 Connectors   | <u><a href="#">2002220700</a></u> |
| Extraction Tool for MX150L, MX150, PT Bulb Socket, iGrid, SPOX, and Wire-to-Motor Terminals | <u><a href="#">638131500</a></u>  |
| Hand Crimp Tool for Cable Seal Crimp Terminals  | <u><a href="#">638199200</a></u>  |
| FineAdjust Applicator for Cable Seal Crimp Terminals  | <u><a href="#">639018100</a></u>  |

---

This document was generated on Sep 25, 2025