

Product data sheet

Specifications



Condenser, 46kW, 115F(46C),
208-230V/3, 60Hz

ACCD75229

Main

Main Input Voltage	200 V 3 phases 208 V 3 phases 220 V 3 phases 240 V 3 phases
--------------------	--

General

Air discharge option	Horizontal Upflow
Air flow	7868.3 l/s
Inrush current	10 A

Physical

Height	82.4 cm
Width	97.7 cm
Depth	315.1 cm
Net weight	230.88 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
Length	3.15 m

Input

Minimum circuit ampacity	12 A
Network frequency	60 Hz
Maximum overcurrent protection	15 A

Conformance

Product certifications	ETL
------------------------	-----

Environmental

Ambient air temperature for operation	-20...50 °C
Operating altitude	0...10000 ft
Audible noise at 1 meter from surface of unit	65 dBA

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	88.9 cm
Package 1 Width	330.2 cm
Package 1 Length	109.2 cm
Package 1 Weight	272.16 kg

Contractual warranty

Warranty (in months)	12
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	955 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	912 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	23 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	20 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins