



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: CLD CELL SPONGE

2. COLORS: BLACK

3. RoHS COMPLIANT

4. THIS PART IS UESD ON ARC12-24PX(R) RECEPTACLE WHERE X=A,B,C,D KEYS

5. TEMPERATURE RATING: -57°C TO +107°C [-70°F TO +225°F]

6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

ARC24-GKT			REF		DRC24-GKT							
	IUMBER			DESCRIPTION					ITEM			
QUANTITY MATERIALS LIST												
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64		SIGNATURES		S DATE	Amphenol							
		CHECKED: CRICALLI		9 05APR21								
2 PL DEC ±0.15 3 PL DEC ±0.08	2 PL DEC ±0.15 Angles ±1°		ORION.LI	06APR21	Sine Systems - www.amphenol-sine.com							
3) Note reference = X		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036							
MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS: NEXT ASSY:		APPROVAL: TOMMY.XIE		07APR21			Cilition	OWIISIIIP, IVII 400	030			
		CUSTOMER:			GASKET,RECEPTACLE,24PIN.ARC SERIES							
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES,						,				
		SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECTTO NORMAL MANUFACTURING VARIATIONS.		A	C-	DWG NO:	ARC24-0	SKT		A1		
				SCALE: N	ONE			SHEET	1	OF 1		