


Surface Mount Chip Resistors

Style CW

General Specifications


- **Resistance:** 50 and 100 Ω standard.
- **Resistive Tolerance:** $\pm 5\%$ Standard (2% Available).
- **Operating Temp Range:** -55 to +150°C
- **Temperature Coefficient:** ± 150 ppm/°C
- **Resistive Elements:** Proprietary film.
- **Substrate Material:** Aluminum Nitride.
- **Terminals:** Silver over Nickel
- **Reliability:** MIL-PRF-55342



ATC Part Number	W $\pm .010$	L $\pm .010$	T $\pm .005$	WT $\pm .005$	LT $\pm .005$	Power Max* (Watts)
CW11005T0100G	.050	.100	.025	.045	.030	2
CW12010T0100G	.100	.200	.040	.090	.030	4
CW12525T0100G	.245	.245	.040	.120	.040	6
CW13725T0100G	.250	.375	.040	.120	.050	8
CW13737T0100G	.370	.370	.040	.360	.050	10

* Test Condition: Chip soldered to a via patch on a 30-mil-thick Rogers RO4350 board; Land surfaces at 100° C; maximum rated power applied.
 Specification: The resistance of the film shall change no more than 0.5% during and after a 1000-hr. Burn-in per Mil-PRF-55342

Power Derating




ATC Part Number Code

CW1 2010 T 0100 J TR		
Case Style	Case Size	Termination
Packaging	Tolerance	Value
TR - Tape & Reel	See table below.	
BK - Bulk		

Resistive Tolerances		
Code	G (%)	J (%)
Tol.	± 2	± 5

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product line without prior notice.
 © 2002 American Technical Ceramics ATC 001-971 Rev. B; 2/03



AMERICAN TECHNICAL CERAMICS
 COMPONENT AND CUSTOM INTEGRATED PACKAGING SOLUTIONS
 FOR RF, MICROWAVE AND TELECOMMUNICATIONS

WWW.ATCERAMICS.COM

ATC North America
 631-622-4700
 sales@atceramics.com

ATC Europe
 +46 8 6800410
 sales@atceramics-europe.com

ATC Asia
 +86-755-8399-5205
 sales@atceramics-asia.com