

0603SFF150F/32-2 - 0603SFF Series



Series: 0603SFF

Questions? Contact Littelfuse Support

 Fuse 0603SFF Datasheet

 Fuse 0603SFF Product Specification

✓ Check Stock

Fast-acting chip fuses help provide overcurrent protection for systems using DC power sources up to 63V_{DC}. The fuse's monolithic, multilayer design helps provide the highest hold current in the smallest footprint, reduce diffusion-related aging, improve product reliability and resilience, and enhance high-temperature performance in a wide range of circuit designs.

These RoHS-compliant surface-mount devices offer strong arc suppression characteristics and help facilitate the development of more reliable, high-performance consumer electronics such as laptops, multimedia devices, cell phones and other portable electronics.

Benefits:

- Small size with high current ratings
- Temperature stability
- High reliability and resilience
- Strong arc suppression characteristics

Features:

- Lead-free and RoHS compliant
- Halogen free
- High-temperature performance
- -55°C to +125°C operating temperature range

Applications:

- Laptops
- Digital cameras
- Cell phones
- Printers
- DVD players
- Portable electronics
- Game systems
- LCD monitors
- Scanners

Electrical Characteristics	Technical Resources
Property (Mouseover for details)	Value
Ampere Rating (A)	1.5
Max Operating Temp (°C)	125
Nominal Cold Resistance (Ohms)	0.059
Interrupt Current (Max) AMP	35
Package Size	0603

check our [Privacy Statement](#).



- [Legal](#)
- [Press Room](#)
- [Privacy Statement](#)
- [Supply Chain Transparency](#)
- [Website Feedback](#)

- [Industries](#)
- [Order Samples](#)
- [Products](#)
- [Services](#)

- [Littelfuse University](#)
- [Product Catalogs](#)
- [Quality Documents](#)
- [Technical Documents](#)

Littelfuse, Inc. 8755 West Higgins Road Suite 500, Chicago, IL, A, 773-628-1000 Copyright © 2017 Littelfuse, Inc.