

Part Number: 734150961

Product Description : MMCX Jack, Straight, PCB Receptacle, End Launch, Brass Body, Gold (Au) Plating,

Tray, 50 Ohms

Series Number: 73414

Status: Active

Product Category: RF / Coaxial Connectors



Documents & Resources

Drawings

734150961 sd.pdf

3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | ⊚ per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

• IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

| Status | Active |
|--------------|--|
| Category | RF / Coaxial Connectors |
| Series | 73414 |
| Description | MMCX Jack, Straight, PCB Receptacle, End Launch, Brass Body, Gold (Au) Plating, Tray, 50 Ohms |
| Application | RF |
| Product Name | MMCX |
| Style | PCB |
| Туре | Microminiature |
| UPC | 800753122697 |

Electrical

| Frequency | 6 GHz |
|-----------------|-----------------------------|
| Impedance | 50Ω |
| Power / Voltage | VOLTAGE: 170 Vrms@Sea Level |

Physical

| Cable Attachment | N/A |
|-----------------------|----------|
| Gender | Jack |
| Keying to Mating Part | N/A |
| Net Weight | 0.377/g |
| Orientation | Straight |
| Packaging Type | Tray |

| Panel Mount | No |
|-----------------------------|------------|
| Panel Mount Method | N/A |
| PCB Mounting | Edge Mount |
| PCB Thickness - Recommended | Various |
| Reverse Polar | No |
| Wire/Cable Type | N/A |

Solder Process Data

| Max-Duration | 10 |
|------------------------------|--------|
| Lead-Free Process Capability | REFLOW |
| Max-Cycle | 1 |
| Max-Temp | 260 |

This document was generated on Sep 29, 2025