

COAXIAL CONNECTOR, QN, 50 Ohm, Right angle cable plug (male)

16_QN-50-4-1/133_N

Properties

- Same performance but smaller than N-Interface
- High packing density
- Applicable in frequencies up to 11 GHz
- Easy to mate - No torque or tooling required

**Product configuration**

Interface type	Gender	Standard
QN	plug	QN QLF compliant

Interface and material data

Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data

Impedance	50 Ω
Interface frequency	11 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 4 GHz	24 dB	1.13
4 GHz ... 6 GHz	19 dB	1.24

Mechanical data

Weight	0.0218 kg
Mating cycles	100
Cable entry centre contact	soldered
Cable entry outer contact	crimped

COAXIAL CONNECTOR, QN, 50 Ohm, Right angle cable plug (male)
16_QN-50-4-1/133_N

Environmental data		
Operation temperature		-40 °C ... 125 °C
Ordering Information Table		
Item number	Item description	Packaging type
23033078	16_QN-50-4-1/133_NE	Single
84013859	16_QN-50-4-1/133_NH	Bulk 100 pcs
Suitable cables		
Cable group		S16 - 4 mm / 50 Ohm
Additional cables		LL142(Harbour)
Additional Information		
Only as assembly		No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3050 / Date of publication: 12.08.2024 / uncontrolled copy