




## Material Datasheet

20.03.2023

**TAG22-22TDK1-1221-SR**  
Article Number 596-00574



Material: Type 1221, Polyester, silver (1221)  
Colour: Silver (SR)

Operating Temperature : -40 °C to +90 °C  
Curing Temperature: from +10 °C

Self adhesive (Yes/No): Yes

Width (W): 22 mm  
Height (H): 22 mm  
Width of Liner (WL): 28 mm  
Labels per Row: 1 pc.

Thickness of Foil: 50 µm

Test Method  
FINAT FTM 12

Adhesive: Acrylic  
Peel strength: 45 N/25mm

DIN EN 1939

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved



## Material Datasheet

20.03.2023

Print Method:	Thermal transfer print
Print Method (Alternative):	Laser beam print
Application Tool:	TT431, TT4030
Recommended Ribbon Type:	TT122OUT, TT822OUT
Shelf Life:	Minimum 1 year upon receipt / maximal 2 years after production date.
Storage Temperature:	+21 °C
Storage conditions:	50% relative humidity., The storage in the original packaging is recommended., Please avoid warehousing under impacts such as high humidity, heat and coldness.
Application Method:	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.



We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved