


Part Number : <u>351550900</u>

Product Description: 2.50mm Pitch Wire-to-Board

Housing, Positive Lock, Natural, 9 Circuits

Series Number: 35155

**Status:** Not Recommended For New Design **Product Category:** Connector Housings



### **Documents & Resources**

### **Drawings**

351550900 sd.pdf

351550900 stp.zip

### **Specifications**

351550200-100.pdf

PK-35155-001-001.pdf

PS-35155-001-001.pdf

PS-35155-002-001.pdf

PS-35184-001-001.pdf

PS-68143-001-001.pdf

# **Product Environment Compliance**

### **Compliance**

GADSL/IMDS	Not Relevant
China RoHS	⊚ per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant per EU 2015/863

### **Compliance Statements**

• EU RoHS

- REACH SVHC
- Low-Halogen

## **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### **Substances of Interest**

PFAS

## **EU RoHS Certificate of Compliance**

# Additional Product Compliance Information

## **Part Details**

#### General

Status	Not Recommended For New Design
Category	Connector Housings
Series	35155
Description	2.50mm Pitch Wire-to-Board Housing, Positive Lock, Natural, 9 Circuits
Application	Signal, Wire-to-Wire
Product Name	N/A
UPC	800755465976

### **Agency**

CSA	LR19980
UL	E29179

# **Physical**

Breakaway	No
Circuits (maximum)	9
Color - Resin	Natural
Flammability	94V-0
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	None

Lock to Mating Part	Yes
Material - Resin	Polyester
Net Weight	0.913/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.50mm
Pitch - Termination Interface	2.50mm
Temperature Range - Operating	-40° to +105°C

## Mates With / Use With

# Mates with Part(s)

Description	Part Number
2.50mm Pitch Wire-to-Wire Plug Housings	<u>35184</u>
2.50mm Pitch Vertical Headers	<u>35312</u>

# **Use with Part(s)**

Description	Part Number
SPOX Female Crimp Terminals	<u>5103</u>

This document was generated on Sep 24, 2025