

Q search

What is XX series

How to select series

How it works series

Development Boards

DFR0049 Analog Gas Sensor (QM-NG1)

DFR0100 DFRduino Beginner Kit For Arduino V3

DFR0133 X-Board

DFR0162 X-Board V2

DFR0188 Flymaple V1.1

DFR0182 Wirless GamePad V2.0

DFR0267 Bluno

DFR0282 Beetle

DFR0283 Dreamer Maple V1.0

DFR0296 Bluno Nano

DFR0302 MiniQ 2WD Plus

DFR0304 BLE Wireless Gamepad V2

DFR0305 RoMeo BLE

DFR0306 Bluno Mega 1280

DFR0321 Wido-WIFI IoT Node

DFR0323 Bluno Mega 2560

DFR0329 Bluno M3

DFR0339 Bluno Beetle

DFR0342 Ultra-Low-power

Introduction

Features

Specification

Board Overview

Tutorial

More Documents

SKU:SEN0564



Introduction

DFR0306 Bluno Mega 1280 is a compact module with a 1280KB ATmega4809 microcontroller, 16MB AT24C02 EEPROM, and a CCS811 Air Quality Sensor (V1.0). It is suitable for various applications such as air quality monitoring, environmental protection, and industrial safety.

Precautions for use

- Kindly remove the protective film before usage.
- To prevent exposure to volatile silicon compounds vapors (such as silicone adhesive, hair gel, silicone rubber, or other locations where volatile silicon compounds are present).
- Avoid exposure to high concentrations of corrosive gases (such as H2S, SOX, Cl2, HCl, etc.).
- Prevent contamination from alkalis, alkali metal salts, and halogens.
- Refrain from prolonged exposure to extreme environments (such as high temperatures, high humidity, high pollution).
- Avoid contact with water, condensation, and freezing.
- Minimize excessive vibration, impact, and dropping.
- Please refrain from employing this module in systems that involve personal safety concerns.
- For extended periods of non-usage, it is advisable to preheat the module for at least 24 hours.


SKU	SEN0563	SEN0564	SEN0565	SEN0566	SEN0567
Gas Type	HCHO	CO	CH4	VOC	NH3

SKU	SEN0569	SEN0570	SEN0571	SEN0572	SEN0573
Gas Type	EtOH	Smoke	Odor	H2	NO2

Features

- Compact size, measuring only 13*13*2.5mm
- Low power consumption, minimal heat generation, operating current <20mA
- High sensitivity and rapid response recovery
- Advanced MEMS technology

Specification



- Gas detected: CO
- Detection range: 5-5000ppm
- Operating voltage: 3.3-5V
- Operating current: <20mA
- Output signal: Analog voltage
- Load resistance (RL) : 4.7KΩ
- Sensitivity: R0(in air)/Rs(in 150ppm CO) ≥ 3
- Operating temperature: -10-50°C
- Operating humidity: 15-90%RH (non-condensing)
- Lifespan: ≥5 years (in air)
- Dimension: 13×13 x 2.5mm/0.051×0.51x0.1"

Board Overview

Num	Label	Description
1	A	Analog Voltage Output
2	VCC	+
3	GND	-


Tutorial

NOTE: The module needs to be warmed up for more than 5 minutes when powered on for the first time. It is recommended to warm up for more than 24 hours if it has not been used for a long time.

Requirements

- Hardware
 - DFRduino UNO R3 (or similar) x 1
 - MEMS Gas Sensor x 1
 - Jumper wires
- Software
 - Arduino IDE

Connection Diagram



Sample Code

1.Read the sensor raw value

```
int sensorPin = A0;
int sensorValue = 0;

void setup()
{
  Serial.begin(9600); //Set serial baud rate to 9600 bps
}

void loop()
{
  sensorValue = analogRead(sensorPin);
  Serial.println(sensorValue);
  delay(100);
}
```

Expected Results

Open the serial port monitor and get the original value of the sensor.

More Documents

- Schematics & Dimension
- Characteristic Parameter