

NOTES:

1. MATERIALS AND FINISHES:

BODY & NUT - BRASS (ASTM-B16 H02, C36000), NICKEL PLATING
 CONTACT PIN - BRASS, GOLD PLATING
 INSULATOR - PTFE PER ASTM D 1710 OR EQUIV.
 FERRULE - COPPER, NICKEL PLATING

2. ELECTRICAL:

A. IMPEDANCE: 50 Ω
 B. FREQUENCY RANGE: DC - 11 GHz

3. MECHANICAL:



A. TEMPERATURE RANGE: -65° C TO +165° C

4. PACKAGING:

A. QUANTITY: SINGLE PACK
 B. MARKING: BAG TO BE MARKED
 'AMPHENOL, 31-6157, AND DATE CODE

5. CONTACT PIN = TO SOLDER
 CRIMPED FERRULE HEX CRIMP SIZE .213" [5.41]

31-6157		REVISIONS		
DRAWING NO.	REV	DESCRIPTION	DATE	ECO APPR
THIRD ANGLE PROJ.	A	RELEASE TO MFG.	8/29/06	46222 CPM/
	B	ADD CRIMPED FERRULE... TO NOTE 5	4/26/10	48069 CPM/



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
 ± 0.015 (0.381 mm) $\pm .005$ (0.127 mm) $\pm 1^\circ$

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

DRAWN
 C. McGRATH 4/18/05
 ENGINEER
 D. BARTHELME 4/18/05

TITLE

TNC R/A CRIMP PLUG
 (FOR RG-55/U, 142A/U,
 223/U, 400/U)

Amphenol
 Amphenol Corporation
 RF/Microwave Operations
 Danbury, Conn. U.S.A. 06810

REFERENCE

APPROVED
 D. BARTHELME 8/16/06

SCALE: 2:1 SHEET OF

CAD FILE H:\DEPT611\TNC\031\ASSY\6157

CODE ID	DWG SIZE	DRAWING NO.	ISSUE
74868	B	31-6157	B