

f	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6		
e	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
d	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
c	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
b	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
a	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
z	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
P	0					0					1					1					2					2
O	1					5					0					5					0					5
S																										

The technical drawings illustrate the bridge deck geometry. The cross-section (left) shows a total width of 15.40 m (+0/-0.5) and a deck thickness of 11.70 m (+0.10/-0.10). The deck is supported by a central pier with a width of 3.00 m (+0/-0.10). The plan view (right) shows a rectangular deck with a length of 50.00 m (MAX) and a width of 48.00 m (24x2). The deck is divided into two main sections: a central section of 10.00 m (5x2) and a side section of 2.00 m (+0.05/-0.05). The plan view also shows a dashed rectangle indicating the location of the bridge piers.

Diagram showing the seating plane for connector 5 and 6. Connector 5 has a length of 9.70 and a width of 3.70. Connector 6 has a length of 11.20 and a width of 3.70. A vertical line indicates the seating plane for the connector.

A diagram showing a rectangular grid of points. The grid is composed of 10 rows and 24 columns of points. The overall width of the grid is labeled as 48.00, and the overall height is labeled as 10.00. The points are arranged in a regular pattern within the rectangle.

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

[illegible]