
KA34U, AL Universal Terminal, 1-Hole, 3/8" Stud, Dual Rated



By Burndy
Catalog # KA34U

Aluminum Universal Terminal, 1 Hole, 4 AWG (Str)-500 kcmil, 3/8" Stud, 1 Screw, Al/Cu Rated, Tin Plated

Features

- Dual Rated Panelboard Lugs
- High strength extruded aluminum alloy
- Electro tin-plated for low contact resistance
- Rated to 35kV

Application

For Aluminum And Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil
Conductor - AL Str Size Range	4 AWG-500 kcmil
Conductor - Copper Str Size	• 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil
Conductor Size	4 AWG-500 KCMIL
Number Of Conductors	1
Conductor Type	• CU C Str-Size • AL C Str-Size
Conductor - Copper Str Size Range	4 AWG-500 kcmil

Configuration

Physical Attribute - Number of Screws	1
Physical Attribute - Number of Holes	1
Connector Type	Terminal

Dimensions

Dimension - Pad Width inch	1.52 in
Package Height	2.300 in
Dimension - Height mm	40.1 mm
Dimension - Height inch	1.58 in
Dimension - Height fraction	1.58 in
Package Weight	3.670 lb.
Package Length	10.250 in
Package Width	3.550 in
Dimension - L Length Overall mm	71 mm
Dimension - Width fraction	1-51/100 in
Dimension - Hole Size mm	11 mm
Dimension - Hole Size inch	0.42 in
Dimension - Stud Size inch	3/8
Dimension - Bolt Hole Size inch	0.38 in
Dimension - Bolt Size fraction	3/8
Dimension - Width mm	38 mm
Dimension - Width inch	1.51 in
Dimension - D inch	1.50 in
Dimension - N inch	0.88 in
Dimension - Length Overall inch	2.81 in

Force Related

Downloaded from Arrow.com.

Installation Torque Recommended in-lb	450
Plating Type	Tin
UPC 14 Digit GTIN	00781810370247

General

Product Family	MECHANICAL
Material - Hardware	Aluminum
Physical Attribute - Screw Type	Allen
Plated	Yes
Sub Brand	UNIVERSAL TERM
Product Type	Terminal
UPC	781810370247
Type	Bolted Lugs & Terminals
Material	Aluminum

Logistics

Minimum Pack Quantity	12
Pallet Quantity	4608
Carton Quantity	120

Operational

Temperature Rating	194

Product Assets

Catalog [English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved

Downloaded from Arrow.com.