

Part Number: <u>1731120188</u>

Product Description : FCT Coaxial Contact, 3 Pins, Male, Straight, PCB Through Hole, 75 Ohms, 1.30µm

Gold Plating

Series Number: 173112

Status: Active

Product Category: D-Sub Contacts
Engineering Number: FME005P102



Documents & Resources

Drawings

1731120188 sd.pdf

3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Symbol and Footprint (Multi-Format)

Specifications

1731120009-PK-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	⊚ per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

<u>Substances of Interest</u>

PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	D-Sub Contacts
Series	173112
Description	FCT Coaxial Contact, 3 Pins, Male, Straight, PCB Through Hole, 75 Ohms, 1.30µm Gold Plating
Contact Type	Coaxial
Magnetic	Yes
Product Name	FCT Products
Туре	Mixed Layout
UPC	889056489430

Electrical

Current - Maximum per Contact	2.0A
Impedance	75Ω

Physical

Durability (mating cycles min)	500
Gender	Male
Material - Contact	Copper Alloy
Material - Plating Mating	Gold over Nickel

Material - Plating Termination	Gold over Nickel
Net Weight	1.000/g
Orientation	Straight
Packaging Type	Adhesive Tape on Reel
Plating min - Mating	1.300µm
Plating min - Termination	0.200µm
Temperature Range - Operating	-55° to +135°C
Termination Style	Through Hole

Mates With / Use With

Use with Part(s)

Description	Part Number
Use With	FCT Mixed Layout Connectors

Application Tooling

Global

Description	Part Number
FCT Removal Tool for Size 8 Contacts	<u>1731121747</u>

This document was generated on Sep 10, 2025