




SCLT Series 3.6V -40~+85°C 2Khrs

■ Features


- Higher temperature
- Quick charge & discharge
- RoHS compliant
- clocking circuit
- Automatic meter reader
- Controller
- Toys



Items	Characteristics			
Rated Voltage	3.6V			
Operating Temperature Range	-40 ~+85°C			
Surge Voltage	4V			
Capacitance Range	0.22~1.5 F			
Capacitance Tolerance (25°C)	-20~+80%			
Temperature Characteristics	The specifications shall be met at category temperature range from -40°C to 85°C	Capacitance range	Within 30% of the value at 25°C	
		ESR	Less than 2 times of the initial specified value	
High Temperature Loaded	The specifications shall be met after rated voltage applied at 85°C for 2000 hours	Capacitance range	Within 30% of the initial value	
		ESR	Less than 4 times of the initial specified value	
High Temperature Storage	The specifications shall be met after storage at 85°C for 2000 hours	Capacitance range	Within 30% of the initial value	
		ESR	Less than 4 times of the initial specified value	

Dimensions

mm



Standard Ratings for SCLT Series

Part No.	V	F	TYPE	ESR (Ω, @1kHz)	Leakage Current mA	ØD	H	P
SCMDCLT3R6224ZVC135008E	3.6	0.22	C	75	0.003	13.5	7.0	5.0
SCMDCLT3R6224ZVH115005E	3.6	0.22	H	75	0.003	11.5	4.5	10
SCMDCLT3R6224ZVV115005E	3.6	0.22	V	75	0.003	11.5	4.5	5.0
SCMDCLT3R6334ZVC135008E	3.6	0.33	C	50	0.005	13.5	7.0	5.0
SCMDCLT3R6334ZVH115005E	3.6	0.33	H	50	0.005	11.5	4.5	10
SCMDCLT3R6334ZVV115005E	3.6	0.33	V	50	0.005	11.5	4.5	5.0
SCMDCLT3R6474ZVC135008E	3.6	0.47	C	50	0.005	13.5	7.0	5.0
SCMDCLT3R6474ZVH115005E	3.6	0.47	H	50	0.005	11.5	4.5	10
SCMDCLT3R6474ZVV115005E	3.6	0.47	V	50	0.005	11.5	4.5	5.0
SCMDCLT3R6105ZVC205008E	3.6	1	C	30	0.008	20.5	8	5.0
SCMDCLT3R6105ZVH190005E	3.6	1	H	30	0.008	19	5	20
SCMDCLT3R6105ZVV190005E	3.6	1	V	30	0.008	19	5	5.0
SCMDCLT3R6155ZVC205008E	3.6	1.5	C	30	0.008	20.5	8	5.0
SCMDCLT3R6155ZVH190005E	3.6	1.5	H	30	0.008	19	5	20
SCMDCLT3R6155ZVV190005E	3.6	1.5	V	30	0.008	19	5	5.0

All product specifications are subject to change without notice (2019E1)