



Part Number : [2207191002](#)

Product Description : HyperQube 6.00mm Copper Alloy Male Crimp Contact, 4 AWG, Bag

Series Number : 220719

Status : Active

Product Category : Crimp Terminals



Documents and Resources

Drawings

[2207191002_sd.pdf](#)

[2207191001-PK-000.pdf](#)

[STEP AP242](#)

[SOLIDWORKS](#)

[Creo](#)


Specifications

[2207170001-AS-000.pdf](#)

[2207170001-PS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)7771-DC (04 Feb 2026)
EU RoHS	Compliant per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	Crimp Terminals
Series	220719
Description	HyperQube 6.00mm Copper Alloy Male Crimp Contact, 4 AWG, Bag
Application	Wire-to-Board, Wire-to-Busbar
Product Name	HyperQube
UPC	196823239113

Electrical

Current - Maximum per Contact	120.0A
Voltage - Maximum	1000V

Physical

Diameter	6.00mm
Durability (mating cycles max)	200
Gender	Male
Material - Metal	High Conductivity Copper Alloy
Material - Plating Mating	Silver
Material - Plating Termination	Silver
Net Weight	9.752/g
Packaging Type	Bag
Termination Interface Style	Crimp or Compression

Wire Insulation Diameter	See Tooling Specification
Wire Size (AWG)	4
Wire Size mm ²	N/A

Mates With / Use With

Use with Part(s)

Description	Part Number
HyperQube 6.00mm, Plug Housing, Black, Bag	<u>2207181001</u>
HyperQube 6.00mm, Plug Housing, Natural, Bag	<u>2207182001</u>
HyperQube 6.00mm, Plug Housing, Blue, Bag	<u>2207183001</u>

Application Tooling

Global

Description	Part Number
Square "Din" Style Die Sets for 6.00mm Coeur CST Receptacle Terminals, 4 AWG	<u>2139380040</u>

This document was generated on May 20, 2026