

Product Line

- DeepTronica >
- Single Pair Ethernet >
- ZConnect >
- Ceres >
- X-Lok >
- M Series >
- FLOS & FLOS+ >
- Power >
- RBL >
- HS-Lok >
- NMEA 2000 >
- Heavy Duty Shielded >
- RJ >
- USB >
- SSL >
- HDMI >
- DVI >
- Fiber Optic >
- RF >
- Cable Joiner >
- Cable Gland >
- Pressure Relief Vent >
- LED Light Guide >
- D-Sub >
- Standard**
- High Density
- Accessory
- ALTW Emporium >



SDB-37PFFS-SL7001

Operating Temperature: -40°C ~ +105°C  
Transmission Speed: N/A  
Shielded: Metal, Shielded  
Jacket Material: N/A  
Certificate: N/A

You must login first for view the price

Quantity - 1 + Check Stock

Add to Cart Inquiry 

Can't find? [Customize your part](#)

Mating Pair & Accessories

Connector Type Search



D-Sub, Standard...  
SDB-37AMMM-...  
-20°C ~ +80°C

- 0 +

☐



D-Sub, Standard...  
SDB-37AMMM-...  
-20°C ~ +80°C

- 0 +

☐



D-Sub, Standard...  
SDB-37AMMM-...  
-20°C ~ +80°C

- 0 +

☐



D-Sub, Standard...  
SDB-37AMMM-...  
-20°C ~ +80°C

- 0 +

☐



D-Sub, Standard...  
SDB-37AMMM-...  
-20°C ~ +80°C

- 0 +

☐



D-Sub, Standard...  
SDB-37AMMM-...  
-20°C ~ +80°C

- 0 +

☐

Add to Cart Inquiry

| Specifications                      | Download / CAD                                  |
|-------------------------------------|-------------------------------------------------|
| Nominal Current<br><b>5A</b>        | Connector Type<br><b>Receptacle</b>             |
| Shielded<br><b>Metal, Shielded</b>  | No. of Contacts<br><b>37</b>                    |
| Connector Gender<br><b>Female</b>   | Backshell<br><b>Straight Without Board Lock</b> |
| Mating Style<br><b>Screw Thread</b> | IP Rating<br><b>IP67</b>                        |
| Assembly Style<br><b>Solder</b>     |                                                 |
| <span>More Options</span>           |                                                 |

People Also Bought

- 

SDB-37PFFS-SL7001
- 

AB-B002ML-B0BL-...
- 

M12A-08BMMM-...
- 

DC-03AFMM-QL8E01
- 

AU-06BMMM-QL8002