

Product Line

DeepTronica >

Single Pair Ethernet >

ZConnect >

Ceres >

X-Lok >

Accessory

Middle Size

Mini Size

Large Size

Standard Size

M Series >

FLOS & FLOS+ >

Power >

RBL >

HS-Lok >

NMEA 2000 >

Heavy Duty Shielded >

RJ >

USB >

SSL >

HDMI >

DVI >

Fiber Optic >

RF >

Cable Joiner >

Cable Gland >

Pressure Relief Vent >

LED Light Guide >

D-Sub >



BD-05BFMA-QL8MP0

Operating Temperature: -40°C ~ +105°C

Transmission Speed: N/A

Shielded: Plastic, Non-shielded

Jacket Material: N/A

Certificate: UL1977


You must login first for view the price

Quantity - 1 +

 Check Stock

 Add to Cart

 Inquiry



Can't find? [Customize your part](#)

Mating Pair & Accessories

Connector Type ▼ Search

- 0 +

☐

- 0 +

☐

- 0 +

☐

- 0 +

☐

- 0 +

☐

- 0 +

☐

 Add to Cart

 Inquiry

| Specifications | Download / CAD |
|--|--|
| Nominal Current 5A | Connector Type Field Installable |
| Shielded Plastic, Non-shielded | No. of Contacts 05 |
| Connector Gender Female | Backshell Straight |
| Mating Style Push Lock | IP Rating IP68 |
| Assembly Style Crimp | |
| + More Options | |

People Also Bought


BD-05BFMA-QL8MP0


CB-04RFMS-RC8DA0


M12D-04BFFM-...


CD-08AFFM-RL7A10


ADC-05PMMS-LC7001