SERIES: PCN2-S | DESCRIPTION: DC-DC CONVERTER

FEATURES

- up to 2 W isolated output
- industry standard SIP package
- nominal input voltages: 5, 12, 24 Vdc
- single/dual unregulated output
- 1,000 Vdc isolation voltage
- low ripple and noise
- -40 to 100°C
- efficiency up to 86%



RoHS

MODEL

MODEL	input voltage typ (Vdc)	input voltage range (Vdc)	output voltage (Vdc)	output current min (mA)	output current max (mA)	output power max (W)	ripple & noise[1] max (mVp-p)	efficiency typ (%)
PCN2-S5-S5-S	5	4.5~5.5	5	0	400	2	100	82
PCN2-S5-S12-S	5	4.5~5.5	12	0	167	2	150	86
PCN2-S5-S15-S	5	4.5~5.5	15	0	134	2	150	85
PCN2-S5-D5-S	5	4.5~5.5	±5	0	±200	2	150	83
PCN2-S5-D12-S	5	4.5~5.5	±12	0	±83	2	150	86
PCN2-S5-D15-S	5	4.5~5.5	±15	0	±67	2	150	86
PCN2-S12-S5-S	12	10.8~13.2	5	0	400	2	100	82
PCN2-S12-S12-S	12	10.8~13.2	12	0	167	2	150	83
PCN2-S12-S15-S	12	10.8~13.2	15	0	134	2	150	84
PCN2-S12-D5-S	12	10.8~13.2	±5	0	±200	2	150	82
PCN2-S12-D12-S	12	10.8~13.2	±12	0	±83	2	150	82
PCN2-S12-D15-S	12	10.8~13.2	±15	0	±67	2	150	84
PCN2-S24-S5-S	24	21.6~26.4	5	0	400	2	100	79
PCN2-S24-S12-S	24	21.6~26.4	12	0	167	2	150	81
PCN2-S24-S15-S	24	21.6~26.4	15	0	134	2	150	82
PCN2-S24-D5-S	24	21.6~26.4	±5	0	±200	2	150	79
PCN2-S24-D12-S	24	21.6~26.4	±12	0	±83	2	150	81
PCN2-S24-D15-S	24	21.6~26.4	±15	0	±67	2	150	82

Notes:
1. At full load, nominal input, 20 MHz bandwidth oscilloscope, with a 0.33 µF ceramic capacitor on the output.
2. Required to add a 2.2 µF (5 & 12 Vdc input models) or 10 µF (24 Vdc input models) ceramic capacitor to the input to reduce input voltage stress.
3. All specifications are measured at Ta=25°C, nominal input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY



Please read our datasheet & drawing disclaimer here.
Downloaded from Arrow.com.

INPUT

parameter	conditions/description	min	typ	max	units
operating input voltage	5 Vdc input models 12 Vdc input models 24 Vdc input models	4.5 10.8 21.6	5 12 24	5.5 13.2 26.4	Vdc Vdc Vdc
surge voltage	for maximum of 100 ms 5 Vdc input models 12 Vdc input models 24 Vdc input models			 9 18 30	 Vdc Vdc Vdc
current	5 Vdc input models 12 Vdc input models 24 Vdc input models		500 210 110		mA mA mA
filter	capacitive				
input reverse polarity protection	no				
input fuse	1 A time delay fuse for 5 Vdc input models (recommended) 500 mA time delay fuse for 12 Vdc input models (recommended) 250 mA time delay fuse for 24 Vdc input models (recommended)				

Notes: 1. Required to add a 2.2 µF (5 & 12 Vdc input models) or 10 µF (24 Vdc input models) ceramic capacitor to the input to reduce input voltage stress.

OUTPUT

parameter	conditions/description	min	typ	max	units
maximum capacitive load	at full load			470	µF
voltage accuracy				±3.0	%
line regulation	1.0% change in input voltage			±1.2	%
load regulation	from full load to 20% load			±10	%
switching frequency	at nominal Vin, full load		80		kHz
temperature coefficient				±0.05	%/°C

PROTECTIONS

parameter	conditions/description	min	typ	max	units
short circuit protection	momentary			1	s

SAFETY AND COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output for 1 minute	1,000			Vdc
isolation resistance	input to output	1,000			MΩ
isolation capacitance	input to output		15		pF
conducted emissions	EN 55022 Class A & Class B (external circuit required, see Figure 4)				
MTBF	as per MIL-HDBK-217F, full load, GB, 25°C		3,300,000		hours
RoHS	yes				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-40		100	°C
storage temperature		-55		125	°C
operating humidity	non-condensing			95	%

Downloaded from Arrow.com.

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
wave soldering	see wave soldering profile			260	°C

Notes:
1. Soldering materials: Sn/Cu/Ni
2. Ramp up rate during preheat: 1.4°C/s (from 50°C to 100°C)
3. Soaking temperature: 0.5°C/s (from 100°C to 130°C), 60±20 seconds
4. Peak temperature: 260°C, above 250°C for 3~6 seconds
5. Ramp down rate during cooling: -10°C/s (from 260°C to 150°C)



MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	0.77 x 0.28 x 0.40 [19.6 x 7.2 x 10.2 mm]				inches
case material	non-conductive black plastic				
weight			2.7		g

MECHANICAL DRAWING

units: inches [mm]
tolerance: X.XX ±0.01 [±0.25]
X.XXX ±0.005 [±0.13]
pin section tolerance: ±0.002[±0.05]

PIN CONNECTIONS		
PIN	Function	
	Single	Dual
1	+Vin	+Vin
2	-Vin	-Vin
4	-Vout	-Vout
5	No pin	Common
6	+Vout	+Vout





Recommended PCB Layout
Top View

Downloaded from Arrow.com.

DERATING CURVE



EFFICIENCY CURVES









Downloaded from Arrow.com.

EFFICIENCY CURVES (CONTINUED)

EFFICIENCY VS OUTPUT LOAD
PCN2-S5-D12-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S5-D15-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S12-S5-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S12-S12-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S12-S15-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S12-D5-S



Downloaded from Arrow.com.

EFFICIENCY CURVES (CONTINUED)

EFFICIENCY VS OUTPUT LOAD
PCN2-S12-D12-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S12-D15-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S24-S5-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S24-S12-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S24-S15-S



EFFICIENCY VS OUTPUT LOAD
PCN2-S24-D5-S



Downloaded from Arrow.com.

EFFICIENCY CURVES (CONTINUED)





PACKAGING

units: mm

Tube size: 20 x 11 x 330 mm
QTY: 14 pcs



Downloaded from Arrow.com.

TEST CONFIGURATIONS

Input Ripple Current & Output Noise

Figure 1 Measuring Input Ripple Current



Table 1

Input Voltage (Vdc)	L1	C1	C2
5	12 µH	2.2 µF tantalum capacitor	NC
12	12 µH	2.2 µF tantalum capacitor	NC
24	12 µH	10 µF ceramic capacitor	NC

Figure 2 Measuring Output Ripple & Noise for Single Output Models



Figure 3 Measuring Output Ripple & Noise for Dual Output Models



Table 2

Input Voltage (Vdc)	Cin
5	2.2 µF ceramic capacitor
12	2.2 µF ceramic capacitor
24	10 µF ceramic capacitor

Downloaded from Arrow.com.

EMC RECOMMENDED CIRCUIT

Test Condition

Input Voltage: Nominal

Output Load: Full Load

Figure 4 Conducted Emissions Test Circuit



Table 3

EN55022 Class A Recommended External Circuit Components			
Model	C1[1]	C2[1]	L1
PCN2-S5-S5-S	4.7 µF / 50 V	NC	2.2 µH
PCN2-S5-S12-S	4.7 µF / 50 V	NC	2.2 µH
PCN2-S5-S15-S	10 µF / 25 V	NC	5.6 µH
PCN2-S5-D5-S	4.7 µF / 50 V	NC	2.2 µH
PCN2-S5-D12-S	4.7 µF / 50 V	NC	2.2 µH
PCN2-S5-D15-S	10 µF / 25 V	NC	5.6 µH
PCN2-S12-S5-S	10 µF / 25 V	NC	5.6 µH
PCN2-S12-S12-S	4.7 µF / 50 V	NC	5.6 µH
PCN2-S12-S15-S	4.7 µF / 50 V	NC	5.6 µH
PCN2-S12-D5-S	10 µF / 25 V	NC	5.6 µH
PCN2-S12-D12-S	4.7 µF / 50 V	NC	5.6 µH
PCN2-S12-D15-S	4.7 µF / 50 V	NC	5.6 µH
PCN2-S24-S5-S	4.7 µF / 50 V	4.7 µF / 50 V	5.6 µH
PCN2-S24-S12-S	4.7 µF / 50 V	4.7 µF / 50 V	5.6 µH
PCN2-S24-S15-S	4.7 µF / 50 V	4.7 µF / 50 V	5.6 µH
PCN2-S24-D5-S	4.7 µF / 50 V	4.7 µF / 50 V	5.6 µH
PCN2-S24-D12-S	4.7 µF / 50 V	4.7 µF / 50 V	5.6 µH
PCN2-S24-D15-S	4.7 µF / 50 V	4.7 µF / 50 V	5.6 µH

Notes: 1. Ceramic Capacitor

Table 4

EN55022 Class B Recommended External Circuit Components			
Model	C1[1]	C2[1]	L1
PCN2-S5-S5-S	10 µF / 25 V	NC	5.6 µH
PCN2-S5-S12-S	10 µF / 25 V	NC	5.6 µH
PCN2-S5-S15-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S5-D5-S	10 µF / 25 V	NC	5.6 µH
PCN2-S5-D12-S	10 µF / 25 V	NC	5.6 µH
PCN2-S5-D15-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S12-S5-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S12-S12-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S12-S15-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S12-D5-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S12-D12-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S12-D15-S	10 µF / 25 V	10 µF / 25 V	5.6 µH
PCN2-S24-S5-S	10 µF / 50 V	10 µF / 50 V	5.6 µH
PCN2-S24-S12-S	10 µF / 50 V	10 µF / 50 V	5.6 µH
PCN2-S24-S15-S	10 µF / 50 V	10 µF / 50 V	5.6 µH
PCN2-S24-D5-S	10 µF / 50 V	10 µF / 50 V	5.6 µH
PCN2-S24-D12-S	10 µF / 50 V	10 µF / 50 V	5.6 µH
PCN2-S24-D15-S	10 µF / 50 V	10 µF / 50 V	5.6 µH

Notes: 1. Ceramic Capacitor

Downloaded from Arrow.com.

REVISION HISTORY

rev.	description	date
1.0	initial release	07/26/2016
1.01	company logo updated	03/30/2021
1.02	derating, efficiency curves and circuit figures updated	07/09/2021
1.03	company address updated	11/05/2024
1.04	datasheet updated	04/24/2025

The revision history provided is for informational purposes only and is believed to be accurate.

CUI INC
a bel group

Headquarters
15575 SW Sequoia Pkwy #100
Portland, OR 97224
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Downloaded from Arrow.com.